GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2017/M02/1016

Dated: 13/7/17-

FIRE SAFETY CERTIFICATE

Certified that the Banana Leaf Restaurant located at N-12, Connaught Place, New Delhi comprises of Ground + 02 Upper floor, Restaurant running at Ground floor only was granted FSC by this department vide letter No.F6/DFS/MS/EH/2014/NDZ/595 dated 09/05/14. The premises was re-inspected by the officer concerned of this department on 05/07/17 in the presence of Mr. Santosh and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D Restaurant running at Ground floor only with effect from 13/12/11>-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 13 7 -- at New Delhi by.

(Vipin Kental) Chief Fire officer Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.

- 2. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 3. The Manager,

Banana Leaf Restaurant located at N-12, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building Banana Leaf Restaurant at N-12,

Connaught Place, New Delhi

Assembly Building Group-D 2. Type of occupancy:-

Gr. + 02 upper floor, Restaurant running at

Ground floor only

3. Type of case:-Renewal

4. Details of previous FSC:-F6/DFS/MS/EH/2014/NDZ/595 dated

09/05/14

N/A 5. Fire safety directives No.-

05/06/17 6. Date of inspection:-

7. Name of the inspecting officer:-

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer from the building side:-

Mr. Santosh

9. Year of construction:-Old Heritage Bldg. 10. Applicant's letter No:-Nil dated 28/06/2017

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR				
1.	Access to Building		- January Edic					
	1) Road width	09 mtr	12 mtr.	MR				
	2) Gate width	N/A	N/A	N/A				
	3) Width of internal road	N/A	N/A	N/A				
2.	Number, Width Type & Arr	angement of E	xits					
	A. Number of staircases							
	1. Upper floors	01 No.	01 No.	MR 1				
	2. Basements	N/A	N/A	N/A				
	B. Width of staircase		V P					
	1. Upper floors	80 cms.	120 cms	MR				
	2. Basements	N/A	N/A	N/A				
	- C. Protection of exits	N/A	N/A	N/A				
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous staircase to terrace	N/A	N/A	N/A				
	E. Width of corridor	N/A	N/A	N/A				
	F. Door size	1.70 mtr.	1.70 mtr.	MR				
3.	Compartmentation							
	1) Fire check door	N/A	N/A	N/A				
	2) Scaling of electrical shafts	N/A	N/A	N/A				
	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A				
	5) Fire Dumpers	N/A	N/A	N/A				
1.	Smoke Whangement System							
	1) Beseineres	30 ACPH	N/A	N/A				
	2) Upper Hoors	12.ACPH	Natural	MR				
5.	Fire Extinguishers							
	1) Totalsiumbers	04 Nos.	06 Nos.	MR				
	2) Types	ABC & CO2	ABC & CO2	MR				
	3) fed marking	Required	Provided	MR				

				T			
6.	First-Aid Hose Reel		0.1		1	m -	
		Total number of eachfloor 01 Length of hose reel hose 30 mtr.		01 30 mtr.			IR IR
						MR	
			05 mm 05 mm		MR		
7.	Automatic Fire Detection &				/ A	N	r/A
					/A		/A
	2) Location of main panel	N/			/A	1	
V-	3) Location of repeater panel	N/		N/A		N/A N/A	
	4) Alternate source of power	N/					
	5) Hooter's Location	N/A				N/A	
8.	MOEFA	Required		Provided		MR	
9.	Public Address System	N/A		N/A		N/A	
10.	Automatic Sprinkler System						
	1) Basement	N/A		N/A		N/A	
	2) Upper floors		equired		Provided		<u>IR</u>
	3) Sprinkler above false	N/A		N/A		N/A	
	ceiling				A)		
11.	Internal Hydrants	Tarri					
	1) Size of riser/down-comer	N/				N/A	
	2) Number of hydrants per	N	'A				I/A
	floor	2.7		7.7			T/A
	3) Hose box	N	<u>'A</u>	N/A		N/A	
12.	Yard Hydrants				/ 4		T / A
	1) Total number of hydrants	N		N/A N/A		N/A N/A	
	2) Hose box	N	'A	IN	/A .	I	I/A
13.	Pumping Arrangement		21/4		21/4		DT/A
9	1) Ground level		N/A		N/A	-	N/A
	a) Discharge of main pum	ıp_	N/A		N/A		N/A
	b) Head of main pump	-	N/A		N/A		N/A
	c) Number of main pump		N/A	N/A			N/A
	d) Jockey pump out put		N/A		N/A N/A	-	N/A N/A
	e) Jockey pump head		N/A N/A		N/A		N/A N/A
	f) Stand by pump output	8					N/A N/A
	g) Stand by pump head				N/A N/A		N/A N/A
-1-1-4	h) Auto starting/Manual		N/A		IN/A		IN/A
	stopping					1	
	2) Terrace level		450 LPM	-	450 LPM		MR
	a) Discharge of pump		30 mtr.		30 mtr.		MR
	b) Head of pump c) Power supply		Required		Provided Provided		MR
- 907			Required		Provided		MR
1.4		iro			Tiovided	1	TVIIC
14.	Captive Water Storage for Fire Fighting 1) Under ground tank N/A N/A					N/A	
	Under ground tank capacity a) Draw-off connection		IV/A		IN/A		11/11
			N/A		N/A		N/A
	a) Draw-off connection b) Fire service inlet		N/A		N/A	-	N/A
	c) Access to tank		N/A		N/A		N/A
	d) Over head tank capacity	2	2500 ltr.		2500 ltr.	1	MR
15			Required		Provided Provided		MR
15.	Exit Signage.		Required		TTOVICCU		THE

1

the

16.	Provision of Lifts.			
0	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System	for Protect	ion of special Risk, if	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/GH/NDZ/2017/1473 dated

08/06/2017 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2014/NDZ/595 dated 09/05/14 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation :- ADO (CC)