GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2017/ 402 /1063

Dated: 13/7/17

FIRE SAFETY CERTIFICATE

Certified that the Chanakya Guest House located at 2245-47, Rajguru Road, Chuna Mandi, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (03 guest rooms + Reception + lobby), 1st floor to 3rd floor (10 guest rooms at each floor), total 33 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2014/NDZ/904 dated 22/07/14. The premises was re-inspected by the officer concerned of this department on 21/06/17 in the presence of Mr. R.K Verma (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 33 rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -------at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 930/Addl.C.P./ Lic.(H) dated 22/05/17.
- 2. The Manager. Chanakya Guest House at 2245-47, Rajguru Road, Chuna Mandi, Pahar Ganj, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

Market .	INS	PECTION REP	ORT				
1.	Name & address of the building	Chanakya Guest House located at 2245-47, Rajguru Road, Chuna Mandi, Pahar Ganj, New Delhi					
2.	Type of occupancy:-	Residential, Sub Division-A-1 Gr. + 03 Upper floors (total 33 Guest rooms)					
		Ground flo	or (03 guest rooms -	- Reception +			
		Ground floor (03 guest rooms + Reception + lobby), 1 st floor to 3 rd floor (10 guest rooms at each floor).					
3.	Type of case:-	Renewal					
4.	Details of previous FSC:- No. F6/DFS/MS/GH/2014/NDZ/904 dated 22/07/14.						
5.	Fire safety directives No N/A						
	Date of inspection:- 21/03/17						
	Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)						
	Name & designation of officer		Rumar Sharma (A	ibo/cc)			
	he building side:-		Verma (Manager)				
	Year of construction:-	1985	(1.14114501)				
	Applicant's letter No:-		P./ Lic.(H) dated 2	22/05/17.			
				Old Case			
S.No.	Minimum Standards on fire	Requirement/	Provided at site				
	Prevention and fire safety	Existing fire		MR/NMR			
	U/R 33	safety arrangements					
1.	Access to Building	urungements		1 %			
	1) Road width	N/A	09 mtr.	N/A			
	2) Gate width	N/A	N/A	N/A			
	3) Width of internal road	N/A	N/A	N/A			
2.		The second secon		TWA			
	Number, Width Type & Arrangement of Exits A. Number of staircases						
	1. Upper floors	01 Nos.	02 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase			1771			
	1. Upper floors	0.90 mtr.	1.25 & 1.35 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits			11/22			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01	02	MR			
	staircase to terrace						
	E. Width of corridor	01 mtr.	01 mtr.	01 mtr.			
	F. Door size	01 mtr.	01 mtr.	01 mtr.			
3.	Compartmentation						
	1),Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
1	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
1.	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			

7 1 =				
5.	Fire Extinguishers			
	1) Total numbers	10 N.	1027	
	2) Types	10 Nos.	10 Nos.	MR
- T	3) ISI marking	ABC & CO2		MR
6.	First-Aid Hose Reel	Required	Provided	MR
	1) Total number of eachfloor	01	0.1	
	2) Length of hose reel hose		01	MR
	3) Nozzle diameter	30 mtr.	30 mtr.	MR
7.	Automatic Fire Detection &	U5 mm	05 mm	MR
	1) Type of detectors	Alarming Syst		
	2) Location of main panel	N/A N/A	N/A	N/A
	3) Location of repeater panel		N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.		N/A	N/A	N/A
9.	MOEFA	Required	Provided	MR
10.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
T'	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
11	ceiling			
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			
10	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
10	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
	1) Ground level ·	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	E		
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum	p N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outpu	t N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping		7	
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump		Provided	MR

N

14.	Captive Water Storage for Fire Fighting					
***	Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	Required	Provided	MR		
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection Syst Risk, if any: ABC & CO ²	tem for Protec	tion of special	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2014/NDZ/904 dated 22/07/2014 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Дуско (1202)

FTM.

miscell 6/7.