GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2017/ 99 8

Dated: /1/7/17

FIRE SAFETY CERTIFICATE

Certified that Hotel Kama Palace located at 9A/34, Channa Market, WEA, Karol Bagh,

Issued _____ at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. The CEO, Hotel Kama Falace, 9A/34, Channa Market, WEA, Karol Bagh, New Delhi- 05.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form ""F" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : M/s. Hotel Kama Palace, 9A/34, Channa Market, WEA,

Karol Bagh, New Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2014/SZ/1044 dated 21.08.2014

5. Fire Safety directives letter No : Nil

6. Date of inspection : 30-06-2017

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side : Dr. J.N.Chawla, Owner/Occupier

9. Year of Construction : 1996-97

10. Applicant's letter No. : 775/Addl. C.P./Lic. (H) dated New Delhi the 10.04.2017

The said guest house is comprised of basement (storage), ground floor (reception, office & 04 guest rooms), first floor (06 guest room) & second floor (06 guest rooms) and forth floor (01 staff room & staff pantry) (total 16 guest rooms).

Minimum Standards on fi prevention and fire safety U	requirements as	Provided at site	Remarks MR/NMR			
Access to building						
Road width	06 mts	Provided	MR			
Gate width	4.5 mts	Directly accessible	MR			
Width of internal road	N/A	N/A	N/A			
Number, Width, Type & Arra	angement of Exits					
a. Number of staircases	_					
Upper Floors	01	01	MR being old case			
	01	01	MR being old case			
	-					
	1.25 mts	1.25 mts	MR being old case			
	1.25 mts	1.30 mts	MR being old case			
		-				
	N/A	N/A	N/A			
Pressurization	N/A	N/A	N/A			
e. No. of continuous staircases to terr	ace 01	01	MR			
g. Width of Corridor	Old case	1.6 mts	MR			
h. Door Size	Old case	. 0.80 mts	MR being old case			
Compartmentation.						
Fire check door	N/A	N/A	N/A			
Sealing of electrical sha	fts N/A	N/A	N/A			
Fire Rating of shaft door	r N/A	N/A	N/A			
Water Curtain	N/A	N/A	N/A			
Fire Dampers	N/A	N/A	N/A			
	Access to building Road width Gate width Width of internal road Number, Width, Type & Arra a. Number of staircases Upper Floors Basements b. Width of staircases Upper Floors Basements c. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terring. Width of Corridor h. Door Size Compartmentation. Fire check door Sealing of electrical sha Fire Rating of shaft doo Water Curtain	Access to building Road width Gate width Width of internal road Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors Basements Upper Floors Basements Upper Floors Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door Size Compartmentation. Fire Check door Fire check door Sealing of electrical shafts Fire Rating of shaft door Width of Norman Norma	Access to building			

	Duscineits	is we per nour	provided	1	TVIIC .			
	Upper floors	12 a/c per hour	Natural Ventilation		MR 🦠			
5	Fire Extinguishers							
	Total numbers	20	Provided		MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided		MR			
	IS marking	ISI marked	Provided		MR			
6	First-Aid Hose Reels.							
	Total numbers on each floor	01	Provided		MR			
	 Length of hose reel hose 	30 m	Provided		MR			
	Nozzle diameter	5 mm	Provided		MR			
7	Automatic fire detection and alarming system.							
	Type of detectors	N/A	N/A		N/A			
	Location of Main Panel	N/A	N/A		N/A			
	Location of Repeater Panel	N/A	N/A		N/A			
	Alternate source of power	N/A	N/A		N/A			
	Hooters' Location	N/A	N/A		N/A			
8	MOEFA	Required	Provided		MR			
9	Public Address System.	Required	Provided		MR			
10	Automatic Sprinkler System.							
	Basement	Required	Provided		MR			
	Upper Floor	N/A	N/A		N/A			
	Sprinkler above false ceiling	N/A	N/A		N/A			
11	Internal Hydrants							
	Size of riser/down-comer	N/A	N/A		N/A			
	Number of hydrants per floor	N/A	N/A		N/A			
	Hose Box	N/A	N/A		N/A			
12	Yard Hydrants.							
	Total number of hydrants	N/A	N/A		N/A			
	Hose Box	N/A	N/A		N/A			
13	Pumping Arrangements.							
	Ground Level							
- 6	Discharge of main Pump	N/A	N/A		N/A			
	> Head of Main pump	N/A	N/A		N/A			
	> Number of main pumps	N/A	N/A		N/A			
Pic.	> Jockey Pump out put	N/A	N/A		N/A			
	Jockey pump head	N/A	N/A		N/A			
43	> Standby Pump out put	N/A	N/A		N/A			
		N/A	N/A		N/A			

	7		1125					
		Standby Pump Head	N/A	N/A	N/A			
		Auto Starting/ Manual stopping	N/A	N/A	N/A			
		Pump House Access						
		Terrace level	450 LPM	450 LPM	MR			
		Discharge of pump	30 mts	30 mts	MR			
		Head of the pump	Required	Provided	MR			
		Power Supply	Required	Provided	MR			
		> Auto Starting of pump						
14	Captive Water Storage for fire fighting.							
		 Underground tank capacity 	N/A	N/A	N/A			
		> Draw-off connection	N/A	N/A	N/A			
		Fire service inlet	N/A	Provided				
- 7 /		Access to tank Overhead Tark	N/A	N/A	N/A			
		Overhead Tank capacity	5,000 lts	5,000 lts	MR			
15	Ex	it Signage.	Required	Provided	MR			
16	Pro	ovision of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
- 3	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	N/A	N/A	N/A			
	Fireman's Grounding Switch		N/A	N/A	N/A			
	•	Lift Signage	N/A	N/A	N/A			
17	Star	ndby power supply	Required	Provided	MR			
18	Ref	uge Area.						
		Total Area	N/A	N/A	N/A			
)	Location	N/A	N/A	N/A			
19	Fire	Control Room						
		Detector System Panel	N/A	N/A	N/A			
		Flow Switch Panel	N/A	N/A	N/A			
		PA System Panel	N/A	N/A	N/A			
		Battery backup	Required	Provided	MR			
•		Building Floor Plans	N/A	N/A	N/A			
20		ial Fire Protection Systems for ction of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR			

The fire protection systems provided in the building were checked and found functional at the

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2014/SZ/1044 dated 21.08.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

CPO STI MISTELL FID.

F-T. letter is but up for Sign. please.

m-scell

