GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6 DFS (ans) 2017 / W2 / 1073 Dated: 21/7 /2017
FIRE SAFETY CERTIFICATE

Certified that Shopping Mall Plot NO 1-B/3, Twin District Centre, City Centre-Mall, Sector 10, Rohini, New Delhi comprised of Three Basement, Ground + four upper floors owned / occupied by Jackson's Developers Pvt. Ltd., was issued fire safety certificate by this department vide letter no. F.6/DFS/MS/2014/WZ/1016 dated 12/08/2014. The premises was re-inspected by the officers concerned of this department on 04/07/2017 in the presence of Sh. Amit Aggarwal (Mall Manager) and found that the building have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and premise is fit for class Mercantile building with effect from 2 1 / 7 /2017 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the condition under Rule 38 of Delhi Fire Service Rules 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

Issued on 2 / / 7 /2017 at New Delhi by

Chief Fire Officer Ph: 011-23414250

UL

Copy to:

1. Authorized Signatory, Shopping Mall Plot NO 1-B/3, Twin District Centre, City Centre-Mall, Sector 10, Rohini, New Delhi

INSPECTION REPORT

1. Name & address of the building : Shopping Mall Plot NO 1-B/3, Twin District Centre, City

Centre-Mall, Sector 10, Rohini, New Delhi

2. Type of Occupancy : Mall (Mercantile Building)

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/2014/WZ/1016 dated 12/08/2014

5. Fire Safety directives letter No : F6/DFS/MS/BP/2006/1129 dated 16/05/2006

6. Date of inspection : 04/07/2017

7. Name of the Inspecting Officers: DO (NW) & ADO (R)

8. Name and designation of officers

from the building side : Sh. Amit Aggarwal (Mall Manager)

9. Year of Construction : 2008

10. Applicant's letter No.: : Nil dated 15/06/2017

	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks/ NMR		
1	Access to building					
	Road width	9 mtr	9 mtr	M.R		
	Gate width	6 mtr	6 mtr	M.R		
	 Width of internal road 	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement (of Exits				
	a. Number of staircases					
	Upper Floors	04	O4	M.R		
	Basements	Required (10)	Provided (10)	M.R		
	b. Width of staircases					
	T. DI	1.5 mtr	1.5 mtr each	M.R		
	 Upper Floors Basements	1.5 mtr	1.5 mtr each	M.R		
	c. Protection of exits					
	Fire check door	Required	Provided	M.R		
	 Pressurization 	Required	Provided	M.R		
		N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	N/A	N/A	N/A		
	g. Width of Corridor	N/A	N/A	N/A		
	h. Door Size					

3	Con	partmentation.				
· ·	•	Fire check door	Required	Provided	M/R	
		Sealing of electrical shafts				
			Required	Provided	M/R	
		Fire Rating of shaft door	Required	Provided	M/R	
		Water Curtain	N/A	N/A	N/A	
	•	Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.					
	•	Basements	30 a/c per hour	Provided	M/R	
	•	Upper floors	* - * * * * * * * * * * * * * * * * * *	Provided	M.R	
5	Fire	Extinguishers	2 a/c per hour			
	•	Total numbers	One @ 300 m ²	Provided	M.R	
		Types		ABC-59, WCo2-78,	M.R	
		IS marking	144	CO2-25, AFFF-2	1,1,1(
		10 marking	ISI marked	YES	M.R	
)	First-	Aid Hose Reels.				
		Total numbers on each floor	07 @ each floor	Provided	M.R	
	•	Length of hoe reel hose		Provided	M.R	
		Nozzle diameter	30 m	* *** *** *** *** *** *** *** *** ***		
7		natic fire detection and alarming	5 mm	Provided	M.R	
		<u> </u>			×	
	•	Type of detectors	Smoke/Heat	Provided	M.R	
	•	Location of Main Panel	GF	Provided	M.R	
	•	Location of Repeater Panel	N/A	N/A	N/A	
	•	Alternate source of power	Required	Provided	M.R	
	•	Hooters' Location	At strategic locations	Provided	M.R	
	MOE	14 THE STATE OF THE PARTY AND THE PARTY OF T	Required	Provided		
		Address System.	Required	Provided	M.R M.R	
)	Auton	natic Sprinkler System.				
	•	Basement	Required	Provided	M.R	
	•	Upper Floor	Required	Provided	M.R	
	•	Sprinkler above false ceiling	Required	Provided	M.R	
	Intern	al Hydrants				
	•	Size of riser/down-comer	6','	Provided	M.R	
	•	Number of hydrants per floor	07	Provided	M.R	
	•	Hose Box	07	Provided	M.R	

 Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Tosable Provided Provided Provided Required Provided Provided Provided 	M.R
Provided Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Ground Level 2850LPM Provided Provided Provided 70 m Provided 70 m Provided Required Provided Required Provided	M.R M.R M.R M.R M.R M.R M.R
 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping 2 Provided 180 LPM Provided 2 Provided 2 Provided 2 Provided 70 m Provided Required Provided Required Provided Provided Required Provided	M.R M.R M.R M.R M.R M.R
 Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping 2 Provided 180 LPM Provided Provided 70 m Provided Required Provided Provided Required Provided Provided 	M.R M.R M.R M.R M.R M.R
 → Head of Main pump → Number of main pumps → Jockey Pump out put → Jockey pump head → Standby Pump out put → Standby Pump Head → Auto Starting/ Manual stopping 70 m Provided 70 m Provided Provided Required Provided Provided Provided 	M.R M.R M.R M.R M.R M.R
 Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Provided Required Provided Required Provided Provided Provided Provided 	M.R M.R M.R M.R M.R
 ▶ Jockey Pump out put ▶ Jockey pump head ▶ Standby Pump out put ▶ Standby Pump Head ▶ Auto Starting/ Manual stopping 180 LPM Provided 2850 LPM Provided Required Provided Provided 	M.R M.R M.R M.R
 Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping To m Provided Required Provided Provided 	M.R M.R M.R
➤ Standby Pump out put 2850 LPM Provided ➤ Standby Pump Head 70 m Provided ➤ Auto Starting/ Manual stopping Required Provided	M.R M.R
Standby Pump Head Standby Pump Head Auto Starting/ Manual stopping To m Required Provided Required Provided	M.R
Auto Starting/ Manual stopping Required Provided Required Provided	
Auto Starting/ Manual stopping Required Provided Provided Provided	M.R
Required Provided	
I	M.R
Terrace level	
➤ Discharge of pump N/A N/A	N/A
➤ Head of the pump N/A N/A	N/A
➤ Power Supply N/A N/A	N/A
➤ Auto Starting of pump N/A N/A	N/A
14 Captive Water Storage for fire fighting.	
Underground tank capacity 2,00,000 ltr Provided	M.R
> Draw-off connection Required Provided	M.R
Fire service inlet Required Provided	M.R
Access to tank Required Provided	M.R
Overhead Tank capacity 20,000 ltr Provided	M.R
15 Exit Signage. Required Provided	M.R
16 Provision of Lifts.	
Pressurization of Lift Shaft Required Provided	M.R
Pressurization of Lift lobby Required Provided	M.R
Communication In lift Car Required Provided	M.R
Fireman's Grounding Switch Required Provided	M.R
Lift Signage Required Provided	M.R

17	Standby power supply	Required	Provided	M.R		
18	Refuge Area.					
	Total Area	N.A	N.A	N.A		
	> Location	N.A	N.A	N.A		
19	Fire Control Room					
	Detector System Panel	Required	Provided	M.R		
	Flow Switch Panel	Required	Provided	M.R		
	PA System Panel	Required	Provided	M.R		
		Required	Provided	M.R		
	Batter backupBuilding Floor Plans	Required	Provided	M.R		
20	Special Fire Protection Systems for Protection of special Risks, if any:	N.A	N.A	N.A		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2014/WZ/1016 dated 12/08/2014 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

11/2/17/18

Name Suresh Singh.

Name Rojesh Kumar

Designation Dolcoc

Designation ADO | RN & Robe'N

Dy CFO (WE) Speak veg. 6 m Real.