## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2017/ / 0 9 5

Dated: 26/07/17

## FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Jagat Inn located at 6/87, WEA, Karol Bagh, New Delhi- 110005 comprised of basement (other's ownership), ground floor (reception & shops), first floor (08 guest room + offices), second floor (10 guest rooms) (total 18 guest rooms) and third floor (residence of owner), was granted FSC by this department vide letter No. F6/DFS/MS/GH/2014/NDZ/950 dated 30.07.2014. The premises was re-inspected by the officer concerned of this department on 07/07/2017 in presence of Mr. Abhimanyu Malhotra, owner of the guest house and found that deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 26/07/17 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 26/07/17 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- 1. The Manager, M/s. Hotel Jagat Inn, 6/87, WEA, Karol Bagh, New Delhi- 110005.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

## Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

1. Name & address of the building : M/s. Hotel Jagat Inn, 6/87, WEA, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2014/NDZ/950 dated 30.07.2014

5. Fire Safety directives letter No : Nil

6. Date of inspection : 07-07-2017

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

from the building side : Mr. Abhimanyu Malhotra (Owner / Occupier)

9. Year of Construction : 2000-2001

10. Applicant's letter No. : 1126/Addl. C.P./Lic. (H) dated New Delhi the 05.06.2017

The said guest house is comprised of basement (other's ownership), ground floor (reception & shops), first floor (08 guest room + offices), second floor (10 guest rooms) (total 18 guest rooms) and third floor (residence of owner)

S. No.		Minimum Standards on fire prevention and fire safety U/R 33	Existing fire safety arrangement as per letter No. letter dt. 30.07.2014	Provided at site	Remarks MR/NMR
1	A	ccess to building			
		Road width	06 mts	Provided	MR
		Gate width		Directly accessible	MR
		Width of internal road	N/A	N/A	N/A
2	Nı	umber, Width, Type & Arrangemen	t of Exits		a
	a.	Number of staircases	_		-
		Upper Floors	01	01	MR
		Basements	02	02	MR
	b.	Width of staircases	-	-	-
		Upper Floors	1.25 mts.	1.23 mts	MR being old case
		Basements	1.25 mts.	1.05, 0.95 mts.	MR being old case
	c.	Protection of exits	_	-	-
	×	Fire check door	N/A	N/A	N/A
		Pressurization	N/A	N/A	N/A
	e.	No. of continuous staircases to	01	01	MR
		Width of Corridor	Old case	0.95 mts.	MR being old case
	h.	Door Size	Old case	0.87 mts	MR being old case
3	Compartmentation.				
		Fire check door	N/A	N/A	N/A
		Sealing of electrical shafts	N/A	N/A	N/A
		Fire Rating of shaft door	N/A	N/A	N/A
		Water Curtain	N/A	N/A	N/A
		Fire Dampers	N/A	N/A	N/A

4	Smoke Management System.							
	Basements	30 a/c per hour	Exhaust fan provided	MR				
	Upper floors	12 a/c per hour	Natural Ventilation	MR				
5	Fire Extinguishers							
	Total numbers	18	Provided	MR				
	• Types	CO <sub>2</sub> , ABC, WCO <sub>2</sub>	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6	First-Aid Hose Reels.							
	Total numbers on each floor	01	Provided	MR				
	Length of hose reel hose	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7	Automatic fire detection and alarmin	g system.	,					
	Type of detectors	N/A	N/A	N/A				
	Location of Main Panel	N/A	N/A	N/A				
	Location of Repeater Panel	N/A	N/A	N/A				
	Alternate source of power	N/A	N/A	N/A				
	Hooters' Location	N/A	N/A	N/A				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	Required	Provided	MR				
10	Automatic Sprinkler System.							
	Basement	Required	Provided	MR				
	Upper Floor	N/A	N/A	N/A				
	Sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants							
	Size of riser/down-comer	N/A	N/A	N/A				
	Number of hydrants per floor	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
12	Yard Hydrants.							
	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.							
	Ground Level							
	> Discharge of main Pump	N/A	N/A	N/A				
par i	> Head of Main pump	N/A	N/A	N/A				
	> Number of main pumps	N/A	N/A	N/A				
	Jockey Pump out put	N/A	N/A	N/A				
	Jockey pump head	N/A	N/A	N/A				
	> Standby Pump out put	N/A	N/A	N/A				

Auto Starting/ Manual stopping  Pump House Access  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N		> Standby Pump Head	N/A	N/A	N/A
Pump House Access N/A  N/A  N/A  Terrace level  Discharge of pump Head of the pump Head of the pump  MR  Power Supply Required Provided MR  Provided MR  14 Captive Water Storage for fire fighting.  Underground tank capacity Pries ervice inlet Access to tank Overhead Tank capacity Standby power supply  Provided MR  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/		8	N/A		
Terrace level  Discharge of pump  Head of the pump  Head of the pump  MR  Power Supply  Auto Starting of pump  Underground tank capacity  Draw-off connection  Fire service inlet  Overhead Tank capacity  Provided  Provided  MR  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/			N/A	N/A	
Head of the pump Power Supply Auto Starting of pump  Captive Water Storage for fire fighting.  Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity  Provided MR  N/A N/A N/A N/A N/A N/A N/A N/A N/A N/		Terrace level			
Power Supply Auto Starting of pump  Required Required Provided MR  Required Provided MR  14 Captive Water Storage for fire fighting.  Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity  Sound Its  Exit Signage.  Provided MR  N/A N/A N/A N/A N/A N/A N/A N/A N/A N/		> Discharge of pump	450 LPM	450 LPM	MR
Auto Starting of pump  Required  Required  Provided  MR   14 Captive Water Storage for fire fighting.   • Underground tank capacity  > Draw-off connection  > Fire service inlet  > Access to tank  • Overhead Tank capacity   Thyla N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/A		> Head of the pump	40 mts	40 mts	MR
Captive Water Storage for fire fighting.		Power Supply	Required	Provided	MR
<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>N/A</li> <li>Provided</li> <li>MR</li> <li>MR being old cases</li> <li>Provided</li> <li>MR</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>N/A</li> <l< td=""><td></td><td>&gt; Auto Starting of pump</td><td>Required</td><td>Provided</td><td>MR</td></l<></ul>		> Auto Starting of pump	Required	Provided	MR
<ul> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>5,000 lts</li> <li>5,000 lts</li> <li>5,000 lts</li> <li>MR being old case</li> <li>Exit Signage.</li> <li>Required</li> <li>Provided</li> <li>MR</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift I lobby</li> <li>N/A</li> <li>N</li></ul>	14	Captive Water Storage for fire fightin	g.		
Fire service inlet  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/		Underground tank capacity	N/A	N/A	N/A
Access to tank Overhead Tank capacity  South Signage.  Required Provided  MR being old case of the special spe		> Draw-off connection	N/A	N/A	N/A
Overhead Tank capacity  5,000 lts  5,000 lts  5,000 lts  MR being old cas  15 Exit Signage.  Required Provided MR  Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/		> Fire service inlet	N/A	N/A	N/A
Some state   Som		> Access to tank	N/A	N/A	N/A
16 Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby N/A  Communication In lift Car Fireman's Grounding Switch Lift Signage N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/A		Overhead Tank capacity	5,000 lts	5,000 lts	MR being old case
<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>N/A</li> <l< td=""><td>15</td><td>Exit Signage.</td><td>Required</td><td>Provided</td><td>MR</td></l<></ul>	15	Exit Signage.	Required	Provided	MR
<ul> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>N/A</li> </ul>	16	Provision of Lifts.			
<ul> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>N/A</li> </ul>		Pressurization of Lift Shaft	N/A	N/A	N/A
• Fireman's Grounding Switch • Lift Signage  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/		Pressurization of Lift lobby	N/A	N/A	N/A
• Lift Signage  N/A  N/A  N/A  N/A  N/A  N/A  17  Standby power supply  Required  Provided (32 KVA)  MR		Communication In lift Car	N/A	N/A	N/A
17 Standby power supply Required Provided (32 KVA) MR		Fireman's Grounding Switch	N/A	N/A	N/A
1		Lift Signage	N/A	N/A	N/A
	17	Standby power supply	Required	Provided (32 KVA)	MR
18 Refuge Area.	18				
Total Area N/A N/A N/A		> Total Area	N/A	N/A	N/A
Location N/A N/A N/A		> Location	N/A	N/A	N/A
19 Fire Control Room	19	Fire Control Room			
Detector System Panel     N/A     N/A     N/A     N/A		Detector System Panel	N/A	N/A	N/A
• Flow Switch Panel N/A N/A N/A		Flow Switch Panel	N/A	N/A	N/A
PA System Panel Required Provided MR		PA System Panel	Required	Provided	MR
Batter backup     Required     Provided     MR		Batter backup	Required	Provided	MR
Building Floor Plans     N/A     N/A     N/A		Building Floor Plans	N/A	N/A	N/A
20 Special Fire Protection Systems for N/A N/A N/A	0.0	Special Fire Protection Systems for	N/A	N/A	N/A
Protection of special Risks, if any:	20				14/11

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2014/NDZ/950 dated 30.07.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended. DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Div. Officer (South West)

DCFO(SZ)

Mscell Will-F-T. letter is put up for Signi

481/00/8W