GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No.F6/DFS/MS/School/NDZ/2017/ 1110

Dated: 27/7/17

FIRE SAFETY CERTIFICATE

Certified that the Kerla Education Socitey Regd. Senior Secondary School located at Srimat MAdhav Rao Scindia Marg, (Canning Road), New Delhi comprises of Ground + 02 Upper floor was granted FSC by this department vide letter No. F6/DFS/MS/School/2013/885 dated 09/09/2013. The premises was re-inspected by the officer concerned of this department on 11-07-2017 in the presence of Sh. Hari Kumar. K.G (Prinacpal) and found that the said school building have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Group B "Educational Building" Sub-Div. B-I with effect from 27-1-2017 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 on the conditions printed below.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Of Mu

Copy to:-

1. The Principal, Kerla Education Socitey Regd. Senior Secondary School, Srimat MAdhav Rao Scindia Marg, (Canning Road), New Delhi

2. Director of Education, Old Secretariat, Govt. of NCT, Delhi - 54.

Condition for the validity of fire safety certificate

- 1. All the means of escape shall be kept free of all types of obstruction all the time.
- 2. All the fire safety arrangements provided there in shall be maintained in good working condition at all time.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Basement shall be used as per NBC/BBL 1983.
- 6. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 7. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 8. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

		INS	PECTION REPO	ĎΤ	
	1	Name & address of the building			C:
		addies of the building		tion Society Regd.	Andhar D
			Secolidary,	School at Srimat N	viadnav Kao
	2.	Type of occupancy:-	Educational	g, (Canning Road)	, New Delhi.
		Type of case:-		Building, Gr. + 2	Floor
		Details of previous FSC:-	Renewal	/C 1 1/2012/205	
		Details of previous FSC		School/2013/885	dated
	5	Fire safety directives No	09/09/13. N/A		
		Date of inspection:-	11/07/17		
		Name of the inspecting officer		· C1.	20/00
		Name & designation of office		lumar Sharma (AI	00/00)
1	7	From the building side:-		man V C (Duin si	1)
	9.	Year of construction:-	1997	mar. K.G. (Princi	pai)
		Applicant's letter No:-	Nil dated 20	0/06/2017	
	S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks
W		Prevention and fire safety	Exiting fire	1 Tovided at site	MR/NMR
		U/R 33	safety certificate		MINIMIK
-	1.		arrangements		
-	1.	Access to Building	8.4.7		
		1) Road width	Accessible	06 mtr.	MR
		2) Gate width	4.5 mtr.	4.5 mtr.	MR
- 0		3) Width of internal road	NA	NA	NA
-	2.	Number, Width Type & Arrar	igement of Exits		
×		A. Number of staircases			
		1. Upper floors	02	03	MR
		2. Basements	N/A	N/A	N/A
		B. Width of staircase	Y I Lay		
		1. Upper floors	1.5 mtr.	1.0 mtr., 1.30 mtr.	MR
		2. Basements	DI/A	& 1.50 mtr.	
		C. Protection of exits	N/A	N/A	N/A
		1. Fire check door	27/4		
			N/A	N/A	N/A
ŀ		2. Pressurization D. No. of continuous	N/A	N/A	N/A
		staircase to terrace	N/A	N/A	N/A
		E. Width of corridor	NI/A	DT/A	27/
-		F. Door size	N/A	N/A	N/A
-	3.	Compartmentation	1 mtr.	1 mtr	MR
-	7.	1) Fire check door	27/4	27/4	
		2) Sealing of electrical shafts	N/A	N/A	N/A
		3) Fire rating of shaft door	N/A	N/A	N/A
		4) Water curtain	N/A	N/A	N/A
		5) Fire Dampers		N/A	N/A
-	1.	Smoke Management System	N/A	N/A	N/A
-	т.	1) Basements	NI/A	127/4	
1		2) Upper floors	N/A	N/A	N/A
-	5.	Fire Extinguishers	12 ACPH	Natural	MR
-		1) Total numbers	14 Na -	1427	-
		2) Types	14 Nos.	14 Nos. ABC, CO2	MR
		3) ISI marking	ABC & CO2		MR
6	5.	First-Aid Hose Reel	Required	Provided	MR
			02	/ /	
	-	1) Total number of each floor 2) Length of hose real hose	03	03	MR
		2) Length of hose reel hose 3) Nozzle diameter	30 mtr.	30 mtr.	MR
		3) Nozzle diameter	05 mm	05 mm	MR

		8		
7.	Automatic Fire Detection & A	larming System		
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Siren	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	1200		
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	IN/A	IVA	IVA
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	100 mm	100 mm	MR
			03	
	2) Number of hydrants per	03	03	MR
	floor	02	02	MD
10	3) Hose box	03	03	MR
12.	Yard Hydrants	1227. 2		1271
N e i	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			0
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main	N/A	N/A	N/A
	pump	1 1/12		
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
		N/A	N/A	N/A
	, , , , ,	IN/A	, IVA	14/71
	output	N/A	N/A	N/A
	g) Stand by pump head	N/A N/A	N/A	N/A
	h) Auto starting/Manual	N/A	IN/A	IN/A
	stopping	-		
	2) Terrace level	000 7 77 7	000 7 77 5	1.00
	a) Discharge of pump	900 LPM	900 LPM	MR
134	b) Head of pump	40 mtr.	40 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of	Required	Provided	MR
	pump			
14.	Captive Water Storage for Fir			
	1) Under ground tank	N/A	N/A	N/A
	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	10,000 ltr.	10,000 ltr.	MR
	capacity	10,000 10.	, , , , , , ,	
15.	Exit Signage.	Required	Provided	MR
	Provision of Lifts.	Required	Tiovided	
16.				3-11
	a) Pressurization of lift	N/A	N/A	N/A
	shaft			
		1		
	b) Pressurization of lift	N/A	N/A	N/A

	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A

N/A

Special Fire Protection System for Protection of special Risk, if

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Building floor plan

any: Fire bucket with send

Shortcomings communicated vide letter No. F6/DFS/MS/2017/1278 dated 19/05/2017

have been rectified.

20.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/School/2013/885 dated 09/09/13 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

N/A

N/A

MR

Name: - M.K. Sharma 13/ 7/2. Designation: - A. D.O. (CC)

379/cf- NO2 17/2-/24/2 Do-MIR Defo/240

G.F.D. M. SCEN. 14/7.
F.S. letter is put up for sign.