GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2017/ 11 4 9

Dated :-- 1/8/1/7

FIRE SAFETY CERTIFICATE

Certified that the Aman Guest House located at 4/5, D.B. Gupta Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Commercial ply shops), 1st floor (07 guest rooms + reception + other property), 2nd floor to 3rd floor (07guest rooms at each floor), total 21 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2014/NDZ/681 dated 04/06/14. The premises was re-inspected by the officer concerned of this department on 27/06/17 in the presence of Sh. Mukesh Mahajan (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 1/8/17—at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- oy to:
 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Aman Guest House at 4/5, D.B. Gupta Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

Aman Guest House at 4/5, 1), 11. Gupta

1. Name & address of the building

Road, Pahar Ganj, New Delhi Residential, Sub Division-A

2. Type of occupancy:-

Gr. + 03 Upper floors (total 21 (nest rooms) Ground floor (Commercial ply shops), 1st floor (07 guest rooms + reception + other property),

2nd floor to 3rd floor (07 guest room) at each floor).

3. Type of case:-

No. F6/DFS/MS/GH/2014/NUS/681 dated 04/06/14.

4. Details of previous FSC:-

N/A

5. Fire safety directives No.-6. Date of inspection:-

30/06/17

7. Name of the inspecting officer:-8. Name & designation of officer

Sh. Manoj Kumar Sharma (ADO/CC)

From the building side:-

Sh. Mukesh Mahajan (Owner)

9. Year of construction:-

2008 Nil dated 16/06/2017.

10. Applicant's letter No:-

10.	Applicant's letter No:-	Nil dated 10/00	0/2017.	Old Case
, No.		Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			MR
,	1) Road width	N/A	12 mtr.	N/A
	2) Gate width	N/A	N/A	
	avvi the of internal road	N/A	N/A	N/A
-	Number, Width Type & Arra	angement of E	xits	
	A. Number of staircases			MR
	1. Upper floors	01 Nos.	01 Nos.	N/A
	2. Basements	N/A	N/A	14/14
	B. Width of staircase	-	1.25 mates	MR
	1. Upper floors	0.80 mtr.	1.25 mtr.	N/A
	2 Basements	N/A	N/A	1 (1 / 2
	C. Protection of exits		N/A	N/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	01	MR
	D. No. of continuous	01	01	
	staircase to terrace		1 mtr.	MR
	E. Width of corridor	1 mtr.	1 mtr.	MR
	F. Door size	1 mtr.		7
1.	Compartmentation	27/4	N/A	N/A
- 7	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
1	3) Fire rating of shaft door	IN/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	11/12	
1.	Smoke Management Syste	30 ACPH	N/A	N/A
-	1) Basements	12 a/c per	Natural	MR
	2) Upper floors	hour		
		Hour		

5.	Fire Extinguishers		10.21	MR
	1) Total numbers	10 Nos.	12 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	IVIK
6.	First-Aid Hose Reel		0.1	MR
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	IVIN
7.	Automatic Fire Detection &	N/A		
Andrew F. S	1) Type of detectors	N/A	N/A	N/A N/A
	2) Location of main panel	N/A	N/A	N/A N/A
	3) Location of repeater panel	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A N/A
	5) Hooter's Location	N/A	N/A	
8.	MOEFA	Required	Provided	MR
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System			
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
112	2) Number of hydrants per	N/A	N/A	N/A
	floor			
	3) Hose box	N/A	N/A	N/A
	Yard Hydrants	*		
12.	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
12	Pumping Arrangement	The Winds		
13.	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pun		N/A	N/A
	d) Jockey pump out put	1	N/A	N/A
1	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump outp		N/A	N/A
	g) Stand by pump head		N/A	N/A
	h) Auto starting/Manua		N/A	N/A
	stopping			
	2) Terrace level			
1	C	450 LPM	450 LPM	MR
2		30 mtr.	30 mtr.	MR
		Required	Provided	MR
			Provided	MR
1	d) Auto starting of pun	Troquitous.		

- 11-

	Captive Water Storage for F	ire Fighting		
4.	1) Under ground tank	N/A	N/A	N/A
	capacity	27/4	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	Provided	MR
	c) Access to tank	Required	2500 ltr.	MR
	d) Over head tank	2500 ltr.	2300 III.	TVIIC
	capacity	1	Provided	MR
5.	Éxit Signage.	Required	Provided	1711
6.	Provision of Lifts.		The second second	DI/A
	a) Pressurization of lift	N/A	N/A	N/A
	shaft		N/A	N/A
	b) Pressurization of lift	N/A	IN/A	1 1/1 2
	lobby	DI/A	N/A	N/A
	c) Communication in	N/A	INIX	
	lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A N/A	N/A	N/A
	e) Lift signage		Provided	MR
17.	Stand by Power Supply	Required	N/A	N/A
18.	Refuge Area	N/A		
-	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
17.	a) Detector system	N/A	N/A	N/A
	panel	27/4	N/A	N/A
	b) Flow switch panel	N/A	N/A N/A	N/A
	c) PA system panel	N/A		N/A
	d) Battery backup	N/A	N/A	11/11
	e) Building floor plan	N/A	N/A	N/A
500	Special Fire Protection Sy	stem for Prote	ection of special	MR
20.				

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/Ms/GH/2014/NDZ/681 dated 04/06/14 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DO-MIR DEFONDE

M 317

1/1