GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No.F.6/DFS/MS/ school/w2/1126

Dated: 28 1 07 12017

FIRE SAFETY CERTIFICATE

Certified that the Govt. Boys Sr. Sec. School, (New Building) located at Tikri Kalan, New Delhi-110041 comprised of Ground + Three upper floors only owned / occupied by Govt. Boys Sr. Sec. School, have complied with the fire prevention and fire safety requirements in accordance with Director Education Circular Dated 01/03/2011 / NBC (Part-IV) and verified by the officer concerned of Fire Service on 13.07.2017 in presence of Mr. Satnam Singh and that the building / premises is fit for occupancy class Educational (Group B) with effect from

| Service Rules, 2010. | Service Rules, 2010.

Issued on 28/07/17 at New Delhi by.

(ATUL GARG) CHIEF FIRE OFFICER.

Copy to :-

1. Assistant Engineer (E), Sub-div.-I, Edu. Maint., Div. M1-1, PWD, I T Campus Pusa, New Delhi-110012.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in

1. Name & address of the building: Govt. Boys Sr. Sec. School, (New Building),

Tikri Kalan, New Delhi-110041.

2. Type of Occupancy : Educational

3. Type of Case : New | Covered Area -1202 m²

4. Details of previous NOC : Nil

5. Fire Safety directives Letter No. : <u>DOE</u> Circular Dated 1/3/2011 / NBC (Part-IV)

6. Date of inspection : 13/07/2017

7. Name of the Inspecting Officer: A.D.O. (Jwala Puri)

8. Name and designation of Officer

from the building side : Mr. Satnam Singh

9. Year of Construction : 2016-17

10. Applicant's letter No. : 54(SPS School)/PWD EDU Sub Div. / M-1/2017-18/35 dated 05/06/2017

S	Minimum standards on fire	DOE Circ. Dt.	Provided at	Remarks		
No	prevention and fire safety	01/03/2011 / NBC	site	MR/NMR		
INO	U/R 33	Requirements	Site			
1.	Access of building					
	Road width	6 mtr	6 mtr	MR		
	Gate width	4.5 mtr	4.5 mtr	MR		
	Width of internal road	N/A	N/A	N/A		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases	5 .	2			
	Upper floors	3	5	MR		
*	Basements	N/A	N/A	N/A		
	b. Width of staircases					
	Upper floors	1.50 Mtr.	1.80 mtr x 5	MR		
	Basements	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	d. No of continuous	1	1	MR		
	staircase to terrace		e 9	2 8 2		
	e. Width Of Corridor	1.50 Mtr.	1.50 Mtr	MR		
	f. Door Size	1.00 Mtr.	1.00 Mtr	MR		
	8	1.50 Mtr (Hall)	2.00 Mtr (Hall)			
3.	Compartmentation					
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers					
4.	Smoke managements System			4		
	Basements	N/A	N/A	N/A		
	Upper floors	N/A	N/A	N/A		
5.	Fire Extinguishers	•		Ÿ.		
	Total numbers	12	15	M/R		
	• Types	ISI marked	Provided	MR		

6.	First – Aid Hose Reels		4	MR
	• Total numbers on	2	4	
	each floor		30 mtr	MR
	 Length of hose reel 	30 mtr	30 1110	
100	hose	F	5 mm	MR
	Nozzle diameter	5 mm		
144				
7.	Automatic fire detection and al	arming system	N/A	N/A
1.	 Type of detector 	N/A	N/A	N/A
	 Location of Main 	N/A	IN/A	
	Panel	21/2	N/A	N/A
	 Location of Repeater 	N/A	147.	
	Panel		21/0	N/A
	• Alternate source of	N/A	N/A	TO THE STATE OF TH
	power			
		N/A	N/A	N/A
	Hooters' Location		N/A	N/A
8.	MOEFA	N/A N/A	N/A	N/A
9.	Public Address System	IN/A	2	x
10		N/A	N/A	N/A
	Basements	N/A	N/A	N/A
	• Upper Floor	N/A	N/A	N/A
8.0	Sprinkler above false	Try .		×
- 1	ceiling			2
1	Internal Hydrants	•	21/0	N/A
1.	• Size of riser/down-	N/A	N/A	IN/A
	comer		N/A	N/A
	Number of hydrants	N/A	IV/A	
	per floor		N1/A	N/A
	Hose Box	N/A	N/A	147.1
1	2. Yard Hydrants		N/A	N/A
	• Total number of	N/A	IN/A	1.4
ite av	hydrants		N/A	N/A
	Hose Box	N/A	14/74	
	13. Pumping Arrangements	-		9
	Ground Level	D1/A	N/A	
	 Discharge of main pump 	N/A	N/A	N/A
	> Head of main pump	N/A N/A	N/A	N/A
	> Number of main pumps	N/A	N/A	N/A
	> Jockey pump out put	N/A	N/A	N/A
	> Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
-	Standby Pump HeadAuto Staring/Manual	N/A	N/A	N/A
	> Auto Staring/Manual stopping	(a)		N/A
	> Pump House Access	N/A	N/A	IN/ A
	Terrace level			2 MR
×	> Discharge of pump	450 LPM	450 LPM x	MR
	> Head of the pump	40 MH	40 MH	MR
	> Power supply	Required	Provided	MR
	Auto starting of pump	Required	Provided	IVIN
	Ctamaga for	fire fighting		N/A
	14. Captive water Storage 101 • Underground tank	N/A	N/A	IN/A
	capacity		21/4	N/A
	> Draw of connection	on N/A	N/A Provided	
	> Fire service inlet	NA	Flovided	NA

		Required	Provided	MR ors)
15	Exit Signage	Required		. 013)
16.	Provision of Lifts > Pressurization of Lift	N/A	N/A	N/A
	Shaft Pressurization of lift	N/A	N/A	N/A
	lobby Communication in lift	N/A	N/A	N/A
	Car Fireman's Grounding	N/A	N/A	N/A
	Switch > Lift Signage	N/A	N/A	N/A
	The same supply	Required	Provided	MR
17.	Standby power supply	N/A	N/A	
18.	Refuge Area	N/A	. N/A	N/A
	> Total area > Location	N/A	N/A	N/A
10	Fire control room			NI/A
19.	> Detector system panel	N/A	N/A	N/A
	> Flow Switch Panel	N/A	N/A	N/A
	PA Criston Panel	N/A	N/A	N/A
	> PA System Panel	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	> Building Floor Plans	N/A	N/A	N/A
20.	Special Fire Protection Systems for Protection of special Risks, if any;			

Note:-A) General requirements for schools as per Director of Education circular dated 01/03/2011.

- 1. Escape route- Clear
- 2. LPG cylinders in laboratories :- Nil
- 3. Electric wiring:- Conduit Wiring MCB and ELCB...... Electric circuit:- MCB Provided
- 4. Electric meter board / switch board panel .:- Not Under the staircase
- 5. Basement use as per BBL 1983 :- N/A
- 6. Emergency telephone no. board :- Displayed
- 7. Generator set: :- at the terrace
- Each class room is provided with 2 Doors. B)

There is a Multipurpose Hall measuring 28m x 17m (476 m²) equipped with Fire Extinguishers & Hose Reel Hose having sufficient exits. Stage is concreted made & there is no fixed seats.

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended

Signature of the Inspecting Officer : A.K. Jaiswal

Name Designation: A.D.O. (Jwala Puri)

tubolon eren-Al