GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE NEW DELHI- 110001

NO.F6/DFS/MS/School/2017/SZ/ 1143

Dated: 31/2/17

FIRE SAFETY CERTIFICATE

Certified that the Green View Public School, Dwarka Vihar, Kakrola Road, Najafgarh, New Delhi-110043, comprised of ground plus two upper floors was Issued Fire Safety Certificate vide this department letter no. F6/DFS/MS/School/2014/SZ/1040 dated 20.8.2014. The said school building was re-inspected by the officer concerned of this department on 22.6.2017 in presence of Sh. Mahavir Singh (Representative) and found that the Premises/Building have deemed complied with the fire prevention and fire safety requirements in accordance with Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by Directorate of Education, Govt. of NCT of Delhi, and that the building is fit for occupancy class B "Educational building" for ground plus two upper floors with effect from.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. Director (Education), Govt. of NCT of Delhi, old Secretariat, Delhi-110054.

2. Manager, Green View Public School, Dwarka Vihar, Kakrola Road, Najafgarh, New Delhi-110043.

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

ADO Quella

| | | | INSPECTION D | EDODT | | | |
|------------|------------------------|--|--|---|-----------------|----------|--|
| 1 | Name | & address of the building | INSPECTION REPORT | | | | |
| - | | | Green View Public School, Dwarka Vihar, Kakrola Road, Najafgarh, New Delhi-110043.(Near Sector-16B, Dwarka) | | | | |
| 2 | Type o | f Occupancy | Educational Building "B" | | | | |
| 3 | Type o | f case | Renewal (G+2) | | | | |
| 4 | Details | of previous NOC | F6/DFS/MS/School | F6/DFS/MS/School/2014/SZ/1040 dated 20.08.2014 | | | |
| 5 | Fire sa | fety directives letter No | Directorate of Educa | | | | |
| 6 | Date of | inspection | Dated 1.3.2011 22.06.2017 | Directorate of Education:F-16/Estate/CC/fire Safety/2011/3298-3398 Dated 1.3.2011 | | | |
| 7 | | of the inspecting Officers : | ADO S.P. Bhardwaj | | | | |
| 8 | Name a | and designation of officers | | | | | |
| | - | e building side construction | Sh. Mahavir Singh (Representative) | | | | |
| 9 | | o not dotton | 2003, 2009 | | | | |
| 10 | | nt's letter No. | GVPS/DFSH/2017/592 dated 26.5.2017 | | | | |
| S. NO. | Minimu | m Standards on fire prevention safety U/R 33 | | Provid | ed at site | Remarks | |
| | | outery on 33 | Requirement/DOE | | | MR / NMR | |
| 1 | Access | to building | | | | | |
| | 1) Road | | 6 Mtrs. | 9 Mtrs. | | LAD | |
| | 2) Gate | | 4.50 Mtrs. | | 20 Mtra (2 N | MR | |
| | 3) Width | of internal road | N/A | N/A | 20 Mtrs. (2 Nos | | |
| 2 | Number | , width Type & arrangement of | exits | IIVA | | N/A | |
| | a. Numb | er of staircases | | | | | |
| | 1. Upper | floors | 2 N | | | | |
| | 2. basen | | 3 Nos. | 3 Nos. | • | MR | |
| - 1 | - 4 | of staircase | N/A | N/A | | N/A | |
| | 1. Upper | | 1.5 Mtrs. | 1.5 Mtrs.each | | | |
| | 2. basem | ents | N/A | | | MR | |
| | | tion of exits | IN/A | N/A | | N/A | |
| | 1. Fire ch | eck door | N/A | NICA | | | |
| 2 | 2. Pressu | rization | N/A | N/A | | N/A | |
| | d. No. | of continuous staircase to | | N/A | | N/A | |
| t | terrace | | 3 Nos. | 3 Nos. | | MR | |
| | e. vvidth . Door si | | N/A | 1.50 to 2.35 | 1. | MR | |
| | | mentation. | 1 Mtr. | 1.05 to 1.10 Mtr | S. | MR | |
| | 1. Fire ch | | | | | | |
| | | | N/A | N/A | | N/A | |
| | | | N/A | N/A | | N/A | |
| | water c | | N/A | N/A | | N/A | |
| | . Fire da | | N/A | N/A | | N/A | |
| | | anagement system. | N/A | N/A | | N/A | |
| | and management system. | | | | | | |
| ba | asement | | | N/A | | N/A | |
| ur 5 Fi | pper floo | rs 1 | 2 a/c charge | Natural Vent. | | MR | |
| | tal numb | | | | | VII C | |
| | ypes | | One No. Co2 OR ABC | | IN | /IR | |
| | | TO | or every 300 Sq.Mtrs. | Co2 & ABC | ٨ | /IR | |
| IIS | SI markin | | SI Marked | Provided | IV. | /IIX | |

| | rst-Aid Hose Reels. | | | |
|--|---|------------|-------------|------------|
| | tal numbers on each floor | 3 Nos. | Provided | MR 🕠 |
| | ength of Hose reel hose | 30 m | Provided | MR |
| | ozzle Diameter | 5 mm | Provided | MR |
| | utomatic fire detection and alarming | | | |
| | ype of detectors | N/A | N/A | N/A |
| | cation of Main Panel | N/A | N/A | N/A |
| | cation of Repeater panel | N/A | N/A | N/A |
| | ternate source of power | N/A | N/A | N/A |
| | poter's location | N/A | N/A | N/A |
| | OEFA | N/A | N/A | N/A |
| | ublic Address System. | N/A | Provided | N/A |
| | utomatic Sprinkler System. | | | |
| | asement | N/A | N/A | N/A |
| | oper floors | N/A | N/A | N/A |
| | orinkler above false ceiling | N/A | N/A | N/A |
| | ternal Hydrants | NI/A | N/A | 1 |
| | ze of riser/down-corner | N/A | N/A | N/A |
| 1 1 | umber of Hydrants per floor | N/A | N/A | N/A |
| | ose Box | N/A | N/A | N/A |
| | ard Hydrants. | NI/A | INI/A | INUA. |
| | tal number of hydrants | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | umping arrangements Ground level | | | |
| | | NI/A | NUA | NI/A |
| | Discharge of main Pump | N/A | N/A | N/A |
| | Head of main pump | N/A | N/A | N/A |
| | Number of main pumps ockey pump out put | N/A N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | ockey pump head Standby Pump output | N/A | N/A N/A | N/A N/A |
| | Stanby Pump head | N/A | N/A N/A | |
| | Auto Starting/Manual stopping | N/A | N/A | N/A |
| | mp house access | N/A | N/A | N/A |
| | Terrace level | IN/A | IN/A | N/A |
| | Discharge of pump | 450 Lpm. | 450 LPM | MR |
| | head of the pump | 40 Mtrs. | 40 Mtrs. | MR |
| | Power supply | Required | Provided | MR |
| | Auto starting of pump | Required | Provided | MR |
| | | required | Tovided | IVIIX |
| | ptive water storage for fire fighting | | | |
| | Underground tank capacity | N/A | N/A | N/A |
| | Draw-off connection | N/A | N/A | N/A |
| | fire service inlet | N/A | N/A | MR |
| | Access to tank | N/A | N/A | N/A |
| | er head tank Capacity | 10000 Lts. | 10000 Ltrs. | MR |
| - | it Signage. | Required | Provided | MR |
| | ovision of lifts. | | | |
| | Pressurization of lift shaft | N/A | N/A | N/A |
| | pressurization of lift lobby | N/A | N/A | N/A |
| A CONTRACTOR OF THE PARTY OF TH | communication in lift car | N/A | N/A | N/A |
| | Fireman's grounding switch | N/A | N/A | N/A |
| e. | Lift signage | N/A | N/A | N/A |

MIII

| 17 | Standby power supply | N/A | N/A | N/A | | |
|----|--|-----------------------|---|----------------------------------|--|--|
| 18 | efuge Area. | | Not Required | | | |
| | total area | | | | | |
| | location | | | | | |
| 19 | Fire control room | | Marie Control of the | | | |
| | a. detector system Panel | N/A | N/A | N/A | | |
| | b. Flow switch Panel | N/A | N/A | N/A | | |
| | c. PA system Panel | N/A | N/A | N/A | | |
| | d. Batter backup | N/A | N/A | N/A | | |
| | e. Building floor plans | N/A | N/A | N/A | | |
| 20 | Special Fire Protection systems felectric meter. | for protection of spe | ecial risks, if any: CO2 Fire | extinguisher provided near MR | | |
| | | | | | | |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view deemed compliance of the minimum standards on fire prevention and fire safety requirements as per DOE CIR. dated 1.3.2011, renewal of FSC issued vided letter no F6/DFS/MS/School/2014/SZ/1040 dated 20.8.2014 for ground plus two upper floor is recommended under rule 37 of the Delhi Fire Service Rules 2010.

Accordingly DFA is put up for approval and signature please.

S.P. Bhardwaj ADO (Dwarka)

416/20/50 / XW

20/2/2012

DCF0(92)

starry self

20-7-17

anosp

m sceu Ft

21/7

a put up for Signat

Cho157

M. Scell 42777

W2/17.

Som"

78/7/17