GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/SZ/2017/ 1194

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya, Delhi Cantt, New Delhi-10, comprised of ground and first floor only, was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2014/1034 dated 14-08-2014. The premises was reinspected by the officer concerned of this department on 29-07-2017 in the presence of Mrs. Pratibha Mishra (Principal) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dated 01.03.2011 and that the premises is fit for Occupancy Class "B" Educational Building with effect from ... 1.5.1.5.2.1.02.1.2017 for period of three years.

(Vipin Kental)
Chief Fire Officer
T.No.011-23412225

OIC

Dated: /0/08/17

Copy To:- 1. The Principal, Sarvodaya Kanya Vidyalaya, Delhi Cantt, New Delhi-10.

2. The Director of Education, GNCTD, Old Secretariat, Delhi-54.

Conditions for the validity of fire safety certificate are as under:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

3. Type of Occupancy Education		2.	Building is comprised of : G+1		2 7 7		1011	VIIII 10.		
5. Details of Previous NOC Fire Safety direction letter No		3.	Type of Occupancy : Edu	cation						
1.			and the same of th							
1. Pate of Inspection 1. Pate of Inspection 2.9.07.17. 1. Pate of Inspecting Officers: 2.9.07.17. 1. Pate of Construction 1.958 1. Patibba Mishra (Principal) 1. Pate of Construction 1.958 1. Patibba Mishra (Principal) 1. Pate of Construction 1.958 1. Patibba Mishra (Principal)				: No.F6/DFS/MS/School/2014/1034, dated 14.08.2014.						
7. Date of Inspection : 29,071,7. 8. Name of the Inspecting Officers: : Vedpal (ADO) 9. Name and designation of Officer from the building side :Mrs. Pratibha Mishra (Principal) 10. Vear of Construction : 1958 11. Applicant's letter No :SKV/DC/2017/241, dated 10.7.17. S.No Minimum Standards on fre prevention and fire safety as per director no.3298-3398 Dated 01.03.11 Existing Fire Provided at Remarks Site MR/NMR 1. Access to building Required 6 m MR Road width Gate width Width Type and Arrangement of Exits. N.A. N.A. N.A. a Number of Starcases Upper Floor Basement Basement Signature Starcases Upper Floor Basement N.A. N.A. N.A. N.A. B. Width of Staircases Upper Floor Basement N.A. N.A. N.A. N.A. N.A. Upper Floor Basement N.A. N.A. N.A. N.A. N.A. N.A. By Width of Staircases Upper Floor Basement N.A. N.A. </td <td></td> <td>6. I</td> <td>site Salety direction letter No : F.16</td> <td colspan="6">: F.16/Estate/CC/Fire safety/2011/3298 to 3398</td>		6. I	site Salety direction letter No : F.16	: F.16/Estate/CC/Fire safety/2011/3298 to 3398						
8. Name of the Inspecting Officers: Vedpal (ADO) Name and designation of Officer from the building side		7 [Dated- 01.03.11						
9. Name and designation of Officer from the building side 10. Year of Construction		/. L	7							
From the building side 1.0 Year of Construction 1958 1.1 Applicant's letter No		0. I	Jame of the Inspecting Officers: : Vedp	oal (ADO)						
10. Year of Construction 1958		9. I		D (111) (11)						
11. Applicant's letter No				Pratibha Mishra (P	rincipal)				
S.No Minimum Standards on prevention and fire safety as per drivular no.3298-3398 Dated 01.03.11 State of Color					1107	1.77		*		
Prevention and fire safety as per circular no.3298-3398 Dated 01.03.11 Access to building Road width Width of internal road N.A. N			10.2	Poquiremental	ed 10.7.					
Access to building	1						at			
Access to building Required 6 m MR MR Midth of internal road N.A.						Site	8	WR/NWR		
Required	-	1		1 Totection System						
Gate width NA. N.A. N.				Poguirod			T			
Width of internal road										
Number, Width, Type and Arrangement of Exits.										
a Number of Staircases		2		1000 1000	N.A.		N.A.			
Upper Floor Basement N.A. N.A			a Number of Staircases	IL OI EXILS.		_				
Basement B. Width of Staircases Upper Floor 1.5 m 1.5 m each MR MA. N.A.				02700	0.0					
B Width of Staircases Upper Floor Basement C. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size 1.5 m 1.5 m MR N.A. N						10 400 /4				
Upper Floor Basement C. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size 1.5 m 1.5 m MR N.A.				IV.A.	N.A.		N.A.			
Basement N.A. N.A				1.5	1.5					
C. Protection of exits Fire check door Pressurization Pressuriza						n each				
Fire check door										
Pressurization			CONTROL CONTRO							
Post										
terrace g. Width of Corridor h. Door Size 1.5 m 1.5 m 1m MR			e. No. of continuous staircases to							
1.5 m				N.A.	N.A.		N.A.	_		
1 m			g. Width of Corridor	1 5 200	1.5					
Compartmentation			h. Door Size			<u> </u>				
Fire check door Sealing of electrical shafts N.A.	3	}	Compartmentation	1 111	1111		MR			
Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers N.A. Simple Basement Upper floor 12 a/c per hour N.A. N.A.				ΝΔ	NΙΛ		NI A			
Fire rating of shaft door Water curtain Fire Dampers N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.										
Water curtain Fire Dampers N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.										
Fire Dampers N.A. N.A.										
4 Smoke Management System. Basement Upper floor 30a/c per hour N.A. N.A. 5. Fire Extinguisher Total numbers types IS marking ISI marked ISI marked MR 6 First-aid-Hose Reels. Total numbers of each floor Length of hose reel hose Nozzle diameter N.A. N.A. N.A. N.A. 7 Automatic fire detection and alarming system. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters Smoke Management System 30a/c per hour N.A. N.A. N.A. N.A.			Fire Dampers							
Basement 12 a/c per hour N.A. N.A. N.A.	1		Smake Management Cont	N.A.	N.A.		N.A.			
Upper floor Total numbers types Start Fig. Start F	4			200/00/00/0	P1 2					
5. Fire Extinguisher Total numbers types 31 nos. 36 nos. MR										
Total numbers types 31 nos. 36 nos. MR CO ₂ & ABC ABC Type MR ISI marking ISI marked ISI marked MR MR MR MR MR MR MR M	5			12 a/c per hour	N.A.		N.A.			
types CO2 & ABC ABC Type MR	-			21 ncs	100		1.10			
IS marking ISI marked ISI marked ISI marked ISI marked ISI marked MR First-aid-Hose Reels. Total numbers of each floor Length of hose reel hose Nozzle diameter N.A. N.A. N.A. N.A. N.A. N.A. V.A. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters NA. ISI marked ISI marked INA. N.A.										
6 First-aid-Hose Reels. Total numbers of each floor Length of hose reel hose Nozzle diameter N.A. Automatic fire detection and alarming system. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters N.A.				The state of the s						
Total numbers of each floor Length of hose reel hose Nozzle diameter N.A.	6			151 marked	1SI ma	arked	MR			
Length of hose reel hose Nozzle diameter N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.	Q		The state of the s	NI A	NI C		11.			
Nozzle diameter N.A.							12			
7 Automatic fire detection and alarming system. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.				- Date of						
Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.	7				N.A.		N.A.			
Location of main panel Location of repeater panel Alternate source of power Hooters N.A.	/									
Location of repeater panel Alternate source of power Hooters N.A. N.A. N.A. N.A. N.A. N.A. N.A.										
Alternate source of power Hooters N.A. N.A. N.A. N.A. N.A.				N.A.	N.A.		N.A.			
Hooters N.A. N.A. N.A.				N.A.	N.A.		N.A.			
				N.A.	N.A.		N.A.			
			Tiooters	N.A.	NA		NA			

8	MOEFA	N.A.	N.A.	N. A
9	Public address System.	N.A.		N.A.
10	Automatic Sprinkler System.	14.73.	Provided	N.A.
	Basement	N.A.	N.A.	NI A
	upper floor	N.A.	N.A.	N.A.
	sprinkler above false ceiling	N.A.		N.A.
11	Internal Hydrants	IV.A.	N.A.	N.A.
	size of riser/down-comer	N.A.	NI A	
	Number of hydrants per floor	N.A.	N.A.	N.A.
	Hose Box	N.A.	N.A.	N.A.
12	Yard Hydrants.	IV.A.	N.A.	N.A.
	Total number of hydrants	N.A.	NI A	
	Hose Box	N.A.	N.A.	N.A.
13	Pumping Arrangements.	IV.A.	N.A.	N.A.
	F Ground Level	N.A.	, NI A	
	Discharge of main Pump	N.A.	N.A.	N.A.
	➤ Head of Main Pump	N.A.	N.A.	N.A.
	Number of main pumps		N.A.	N.A.
	Jockey pump out put	N.A.	N.A.	N.A.
	Jockey pump head	N.A.	N.A.	N.A.
	Standby pump out put	N.A.	N.A.	N.A.
	Standby pump Head	N.A.	N.A.	N.A.
	Auto Starting /Manual stopping	N.A.	N.A.	N.A.
	Pump House Access	N.A.	N.A.	N.A.
	> Terrace Level	N.A.	N.A.	N.A.
	Discharge of pump	N.A.	N.A.	N.A.
	Head of the Pump	N.A.	N.A.	N.A.
	Power supplyAuto Starting of nump	N.A.	N.A.	N.A.
	Auto Starting of pump		IN.A.	N.A.
14	Captive Water Storage for Fire Fighting			a 1
	Underground tank capacity		l Nu e	
	Draw-off connection	N.A.	N.A.	N.A.
	Fire service inlet	N.A.	N.A.	N.A.
	Access to tank	N.A.	N.A.	N.A.
	Overhead Tank capacity	N.A.	N.A.	N.A.
15		N.A.	N.A.	N.A.
16	Exit Signage. Provision of Lifts.	N.A.	N.A.	N.A.
10	Pressurization of Lift Shaft			
	Pressurization of Lift lobby	N.A.	N.A.	N.A.
	Communication in lift car	N.A.	N.A.	N.A.
	Firemen's grounding switch	N.A.	N.A.	N.A.
	Lift Signage	N.A.	N.A.	N.A.
4.7		N.A.	N.A.	N.A.
17	Standby power supply	N.A.	N.A.	N.A.
18	Refuge Area.			
	Total area	N.A.	N.A.	N.A.
15	Location	N.A.	N.A.	N.A.
19	Fire Control Room			
	Detector system panel	N.A.	N.A.	N.A.
	Flow switch panel	N.A.	N.A.	N.A.
	PA system panel	N.A.	N.A.	N.A.
	Building Floor Plans	N.A.	N.A.	N.A.
	Building Floor Plans	N.A.	N.A.	N.A.
			14./1.	14.74

^

NIB

Sarvodaya Kanya Vidyalaya, Delhi Cantt, New Delli 20 Special Fire Protection systems for protection of special Risks, if any: N.A.	N.A.	N.A.
	e test checke	
The fire protection systems provided in the building were found functional at the time of inspection. In view of the deeme standards on fire prevention and fire safety required as per Direct 01.03.2011, the FSC issued vide letter No: F6/DFS/MS/School renewal under rule 37 of the Delhi Fire Service Rule 2010 is recorned as per DFA is put up for kind constant.	etor of Education	on Circular dated dated 14.08.2014,
D.O.(S.A)		Name: Vedpal esignation: ADO
118/CFO SL DY CRO(SZ) 5/8/12/10-8013/ CFO (SZ) 1243 50 178 1243 50 178		
FT letter is put up for 80. CFO (52) M. SCELL MG	gn plea	18/18 18/18 18/18