GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/2017/ EH/W2/1223

Dated : 18/08/17

FIRE SAFETY CERTIFICATE

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

Issued on at New Delhi by

Chief Fire Officer Ph-011-23414250

Copy to:-

- 1. The Dy. Health Officer, North MCD, Civil Line Zone, Sec-5, Rohini, Delhi-110054.
- 2. The Manager, Bikanervala Foods Private Ltd, 103-105, Ist floor, Ring Road Mall, Sector-3 Rohini, Delhi -110085.

INSPECTION REPORT 1. Name & address of the building: M/s Bikanervala Foods Pvt. Ltd. at 103-105, Ist floor, Ring Road Mall, Sector-3, Rohini, Delhi-110085. 2. Type of Occupancy : Assembly 3. Type of Case : Renewal 4. Details of previous NOC : F.6/DFS/MS/EH/2014/WZ/989 dated: 07.08.2014 5. Fire Safety directives letter No : NBC Part-4 6. Date of inspection : 26/07/2017 7. Name of the Inspecting Officers: ADO/RN 8. Name and designation of officers from the building side : Sh Nikesh Sharma, Manager 9. Year of Construction :2007 10. Applicant's letter No. :Nil dated 04.07.2017 Minimum Standards on fire **NBC** Requirement Provided at site Remarks prevention and fire safety U/R 33 MR/NMR 1 Access to building Road width 09m 10m MR 4.5m 4.5m Gate width MR Width of internal road NA NA NA 2 Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors 04 common with mall 04 common with mall MR NA Basements NA NA b. Width of staircases 1.50m Upper Floors 1.50m x3 with Mall & 1.20m MR NA NA Basements NA c. Protection of exits Fire check door Required Provided with Mall MR Pressurization Required Provided with Mall MR d. No. of continuous staircases to terrace NA NA NA e. Width of Corridor NA NA NA f. Door Size 02 Exits 1.80m & 1.70m(Old case) MR 3 Compartmentation.

Required

Required

Required

Provided with Mall

Provided with Mall

Provided with Mall

MR

MR

MR

Fire check door

Sealing of electrical shafts

Fire Rating of shaft door

	Water Curtain	NA	NA	NA	
*		NA	NA	NA	
	Fire Dampers				
	Smoke Management System.	20 / 1	NA	NA	
	Basements	30 a/c per hour	Natural Ventilated	MR	
	• Upper floors	12 a/c per hour	Natural Ventuated		
	Fire Extinguishers	08nos	MR		
	Total numbers	06nos		MR	
	• Types	ABC/Co2	ABC-06 /Co2-02		
	IS marking	Yes	Yes	MR	
	First-Aid Hose Reels. (Common with) (D		
	Total numbers on each	04	04	MR	
	floor		20	MR	
	Length of hose reel hose	30 m	30m		
	Nozzle diameter	5mm	5mm	MR	
7	Automatic fire detection and alarm	n with mall)			
		Smoke/ Heat	Provided	MR	
	Type of detectors	NA	NA	NA	
	Location of Main Panel	NA	NA	NA	
	 Location of Repeater Panel 	NA	NA	NA	
	Alternate source of power		NA	NA	
	Hooters' Location	NA		MR	
8	MOEFA	Required	Provided with Mall		
9	Public Address System.	Required	Provided with Mall	MR	
10	Automatic Sprinkler System.				
	Basement	NA	NA	NA MR	
	Upper Floor	Required	Provided	MR	
	Sprinkler above false ceiling	Required	Provided	IVIK	
11	14 - 10				
		100mm	100 mm	MR	
	Size of riser/down-comer	4	4	MR	
	Number of hydrants per floor	or 4	4	MR	
	Hose Box				
12	Yard Hydrants. (with mall)				

			NTA	NA
	Total number of hydrants	NA	NA	
	Hose Box	NA	NA	NA
Pun	nping Arrangements. (Common	with Mall)		
		,		
	Ground Level	4500 lpm	4500 lpm	MR
	Discharge of main Pump	70m	70m	MR
	> Head of Main pump	02	02	MR
	> Number of main pumps	180 lpm	180lpm	MR
	> Jockey Pump out put	70m	70m	MR
	Jockey pump headStandby Pump out put	4500 lpm	4500 lpm	MR
	> Standby Pump Head	70m	70m	MR
	> Auto Starting/ Manual	Required	Provided	MR
	stopping > Pump House Access	Required	Provided	MR
	Terrace level			
	Discharge of pump	NA	NA	NA NA
	Head of the pump	NA	NA	NA
	> Power Supply	NA	NA	NA NA
	> Auto Starting of pump	NA	NA	INA
4 Ca	ptive Water Storage for fire figh	ting. common with ma	all	
			2,20,000 ltrs	MD
	 Underground tank capacity 	2,20,000 ltrs		
	Underground tank capacityDraw-off connection	2,20,000 ltrs Required	provided	
				MF
	> Draw-off connection	Required	provided	MF
	Draw-off connectionFire service inlet	Required Required	provided provided	MF MF
15 Ex	 Draw-off connection Fire service inlet Access to tank 	Required Required Required	provided provided provided	MF MF
	 Draw-off connection Fire service inlet Access to tank Overhead Tank capacity 	Required Required 30,000 ltrs Required	provided provided provided 30,000 ltrs	MF MF
	 Draw-off connection Fire service inlet Access to tank Overhead Tank capacity 	Required Required 30,000 ltrs Required	provided provided provided 30,000 ltrs	MF MF MF
	 Draw-off connection Fire service inlet Access to tank Overhead Tank capacity xit Signage. rovision of Lifts. (Common with	Required Required 30,000 ltrs Required Mall)	provided provided provided 30,000 ltrs Provided	MF MF MF MF
	> Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity xit Signage. rovision of Lifts. (Common with Pressurization of Lift Shaft	Required Required 30,000 ltrs Required Mall) Required	provided provided provided 30,000 ltrs Provided	MF MF MF MI MI
	> Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity xit Signage. rovision of Lifts. (Common with Pressurization of Lift Shaft Pressurization of Lift lobby	Required Required 30,000 ltrs Required Mall) Required NA	provided provided provided 30,000 ltrs Provided Provided NA	MF MF MF MI MI
	> Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity xit Signage. rovision of Lifts. (Common with Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car	Required Required 30,000 ltrs Required Mall) Required NA Required	provided provided provided 30,000 ltrs Provided NA Provided	MR MR MR MR MF MF MF MF MF MI MI

18	Refuge Area.				
	> Total Area	NA	NA	NA	
	> Location	NA	NA	NA	
19	Fire Control Room (Common with mall)				
	Detector System Panel	Required	Provided	MR	
	Flow Switch Panel	Required	Provided	MR	
	PA System Panel	Required	Provided	MR	
	Batter backup	Required	Provided	MR	
	Building Floor Plans	Required	Provided	MR	
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA	

The fire protection systems provided in the building were tested/ checked and found some in working order at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate issued vide this department letter of even no. 989 dated 07.08.2014 under rule 35 of the Delhi Fire Service Rules 2010.

DO NWO on MIR

DCFotWZ)

Signature of the Inspecting Officer
Name: - Rajesh Kumar

Designation:- ADO/RN