FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI

No. 66/08/01/2017/EH/W2/1236

Dated: 18/08/17

FIRE SAFETY CERTIFICATE

Certified that the M/s Eleven Course (A Unit of Eleven Course Hospitality Pvt. Ltd.), located at Unit No. 116 – 117, First Floor, NDM – II, Plot no. D – 1, 2, 3, Netaji Subhash Place, Pitampura, Delhi – 110034 was issued FSC vide Letter No. F6/DFS/MS/EH/2014/WZ/342 dated 11/03/2014. The NDM - II, Netaji Subhash Place has already issued FSC vide Letter No. F6/DFS/MS/2017/WZ/1012 dated 12/07/2017. The premises was re inspected by the officers concerned of this department on 01-08-2017 in the presence of Mr. Upander Kumar (Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D with effect from $\frac{18}{08}/17$ for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on at New Delhi by.

(Atul Garg)
Chief Fire Officer,
Pelhi Fire Service

Copy to:

The Authorized Signatory,
 Eleven Course Hospitality Pvt. Ltd.,
 Unit No. 116-117, First Floor, NDM – II, D – 1, 2, 3, Netaji Subhash Place,
 Pitampura, Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in..

1. Name & address of the building: Eleven Course, Unit No. 116 – 117, First Floor, NDM – II, Plot no. D – 1, 2, 3, Netaji Subhash Place, Pitampura, Delhi – 110034.

2. Type of Occupancy

: Assembly

3. Type of Case : Renewal (NDM-II already issued NOC vide F6/DFS/MS/2017/WZ/1012 dated 12/07/2017

4. Details of previous NOC: no. F6/DFS/ MS/EH/2014/WZ/342 dated 11/03/2014

5. Fire Safety directives Letter No.: FSC Issued to the building

6. Date of inspection

: 01-08-2017

7. Name of the Inspecting Officer: DO (West) & ADO (WP)

8. Name and designation of Officer

from the building side

: Sh. Upander Kumar (Manager)

9. Year of Construction

: 2010

10. Applicant's letter No.

: Nil Dated 13 Jul 2017

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Provided at site		Remarks MR/NMR				
1.	Access of building	×						
	 Road width 	6 m Prov		vided MR				
	Gate width	NA	NA	. v.	NA			
	Width of internal road	NA	NA		NA			
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases							
	 Upper floors 	2	04 Provided		MR			
	 Basements 	NA	NA		NA			
	b. Width of staircases							
	Upper floors	1.5m & 1.25m	Pro	ovided (old	case)	MR		
		NA	NA	1		NA		
	 Basements 							
	c. Protection of exits	 Fire check door Pressurization No of continuous staircase to terrace Width Of Corridor Door Size NA NA NA		Provided		NA		
				Provided		NA		
	The second state of the second			NA		NA		
	staircase to terrace			NA		NA		
				190cm & 120cm, 95cm (Old case)		MR		
	f. Door Size							
3.	Compartmentation				4			
	Fire check door	NA		NA		NA		
	Sealing of electrical shafts	NA		NA		NA		
	Fire Rating of shaft door	NA		NA		NA		
	Water Curtain	NA		NA		NA		
	Fire Dampers	NA		NA		NA		
4.	Smoke managements System							
	Basements	NA		NA		NA		
	Upper floors	12 a/c per hour		Provided		MR		
5.	Fire Extinguishers				(F. 18 %)			
	Total numbers	02 nos. each type		Provided		MR		
	• Types	DCP, CO2 & WCO2		Provided		MR		
	• IS marking	ICI morted		_				

					*				
(6. First – Aid Hose Reels	C	common with the						
-		m	mall						
	• Total numbers on each	1	1 Prov		Provide	ded MR			
	floor								
	 Length of hose reel hose 		30 m		Provided M		MR		
-	Nozzle diameter	5	5 mm Provi		Provide				
7	and the detection and a	larmii	ng system						
	 Type of detectors 	Sr	Smoke Provided		vided	MR			
	 Location of Main Panel 	Re	Required Provi		vided at C	t GF MR			
	 Location of Repeater 		NA NA		NA		A	-	
	Panel				vided MR				
	 Alternate source of power 	R	Required Provide		vided	ided MR			
	Hooters' Location								
8		Re	Required Provi		vided	M	R		
9	Jacobs By Stelli	NA	4	Provide		MR			
1	Sprinted System								
	 Basements 	N	Not Required	N	R	NR			
	 Upper Floor 	R	Required	Pr	Provided		MR		
	 Sprinkler above false 	R	Lequired	Pr	Provided		MR		
	ceiling								
11	The state of the s	h the	mall						
	 Size of riser/down- com 	er	150 mm	P	rovided	MR			
	 Number of hydrants per 		1		rovided	MR			
	floor		Required		rovided	MR			
	Hose Box			-					
12	. Yard Hydrants				Ž				
	 Total number of 	N4	2	NA		NA	7		
	hydrants	NA	NA NA			NA			
	 Hose Box 								
13	T 8 Bernents. Commi	on wi	th the mall						
	 Ground Level 								
	 Discharge of main pump 	NA	NA 28501		lpm	MR			
	> Head of main pump	NA			-				
	Number of main pumps	NA			ded				
,	Jockey pump out put	NA		180 1	om	MR			
	Jockey pump head	NA	A 110		1111			a to the Land	
	Standby Pump out putStandby Pump Head	NA	A 2850		lpm MR				
	Tamp Head	NA	A STATE OF THE PARTY OF THE PAR	110 m	m MR		45		
		NA	A Prov		ided MR				
	stopping Pump House Access								
	Terrace level	NA	VA Provided		ded	MR			
	Discharge of pump								
	Head of the pump	900	700 lpm The Mair		lain pum	oump is provided		MR	
			in pla		ace of terrace pump		np		
	Power supplyAuto starting of pump		10 m -do-					MR	
	Auto starting of pump		equired -do-					MR	
		Req	uired	-do-				MR	
14.	Cantive water Stance C. C. C.	1	0						
17.	Captive water Storage for fire fig	hting	: Common wi						
	• Under ground tank	NA			00 litrs	NA	405 N.		
	capacity Draw off connection	NA	110		-	NA			
	Fire service inlet		equired Provi			NA			
	Access to tank	NA 10	210110			NA			
	Overhead Tank	10, (000 litres	20, 00		MR			
	capacity			Provid	ed				
15	Exit Signage	Pos	irad	D	1	1.00			
16.	Provision of Lifts	Requ	irred	Provid	ed	MR			
- ~.	- 20 (1010H OI LIH)								

17.	Standby power supply	Required	Provided	MR			
18.	Refuge Area						
	> Total area	NA	NA	NA			
	> Location	NA	NA	NA			
19.	Fire control room						
	Detector system panel	NA	NA	NA			
	Flow Switch Panel	NA	NA	NA			
	PA System Panel	NA	NA	NA			
	Battery backup	NA	NA	NA			
	Building Floor Plans	NA	NA	NA			
20.	Special Fire Protection	NA	NA	NA			
	Systems for Protection of			***************************************			
	special Risks, if any;						

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/EH/2014/WZ/342 dated 11/03/2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Mukesh Verma

Designation DO (West)

Signature of the Inspecting Officer

Name Udai Vir Singh

Designation ADO (WP)