## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No.F.6/DFS/MS/ School/w2/2017/ 1241 Dated: 2/ 108 /2017
FIRE SAFETY CERTIFICATE

Certified that the Govt. Co. Ed. Sr. Sec. School, (New Building) located at B-3, Paschim Vihar, New Delhi-110063 comprised of 2 Blocks of Ground + Three upper floors only owned / occupied by Govt. Co. Ed. Sr. Sec. School, have complied with the fire prevention and fire safety requirements in accordance with Director of Education Circular Dated 01/03/2011 / NBC (Part-IV) and verified by the officer concerned of Fire Service on 28.07.2017 in presence of Mr. Naresh Kumar (Civil Eng.) and that the building / premises is fit for occupancy class Educational (Group B) with effect from for a period of 3 (Three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 21/08/17 at New Delhi by.

(ATUL GARG) CHIEF FIRE OFFICER.

Copy to :-

1. Assistant Engineer (E), Sub-div.-I, Edu. Maint., Div. M1-1, PWD, ITI Campus Pusa, New Delhi-110012.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in

1. Name & address of the building: Govt. Co. Ed. Sr. Sec. School, (New Building), B-3, Paschim Vihar, New Delhi-110063.

2. Type of Occupancy

: Educational (2 Blocks)

3. Type of Case

: New

Covered Area 1<sup>st</sup> Block-539m<sup>2</sup> 2<sup>nd</sup> Block-475m<sup>2</sup>

4. Details of previous NOC

: Nil

MR

Provided

5. Fire Safety directives Letter No.: <u>DOE</u> Circular Dated 1/3/2011 / NBC (Part-IV)

6. Date of inspection :

: 28/07/2017

7. Name of the Inspecting Officer: A.D.O. (Jwala Puri)

8. Name and designation of Officer

from the building side

: Mr. Naresh Kumar (Civil Eng.)

9. Year of Construction

: 2016-17

10. Applicant's letter No. : 54(SPS School)/PWD EDU. Maint. Div. / M-1/2017-18/30 dated 29/05/2017

S No	Minimum standards on fire prevention and fire safety U/R 33	DOE Circ. Dt. 01/03/2011 / NBC Requirements		Provided at site		marks R/NMR
1.	Access of building				1.0	
	Road width	6 mtr		6 mtr MR		-
	Gate width	4.5 mtr		4.5 mtr	MF	
	Width of internal road	N/A		N/A	N/	A
2.	Number, width, Type & Arran	gements of exits	S			
	a. Number of staircases		19		12.60	
	Upper floors	1 in each block 2 in		n each block	MR	
	Basements	N/A		N/A	N/	A
	b. Width of staircases			2		
	Upper floors			ntr x 2 (in I-B <mark>loc</mark> k) ntr x 2 (in II-B <mark>loc</mark> k	(1)	MR
	Basements	N/A		N/A	N/	A
	c. Protection of exits					
	Fire check door	N/A		N/A	N/A	
	Pressurization	N/A		N/A	N/A	
	d. No of continuous	1		1	M	R
	staircase to terrace			:		9
	e. Width Of Corridor	1.50 Mtr.		1.50 Mtr	M	R
	f. Door Size	1.00 Mtr. (Class I 1.50 Mtr (Hall)		1.00 Mtr (Class 2.00 Mtr (Hal		MR
3.	Compartmentation		to to	8		
	Fire check door	N/A		N/A	N/	'A
	Sealing of electrical shafts	N/A		N/A	N/A	
	Fire Rating of shaft door	N/A		N/A	N/A	
	Water Curtain	N/A		N/A	N,	/A
	Fire Dampers		e e			
4.	Smoke managements System		×		141	
	Basements	N/A		N/A		/A
	Upper floors	N/A		N/A	N,	/A
5.	Fire Extinguishers				4	
	Total numbers	12 in each blo	ock	15	M	/R
(						Carried Co.

ISI marked

Types

	each floor	2	2	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 mtr	30 mtr	MR
	Nozzle diameter	5 mm	5 mm	MR
7.	Automatic fire detection and	alarming system		9
	Type of detector	N/A	N/A	N/A
1 20	Location of Main	N/A	N/A	N/A
	Panel		10/74	IN/A
	<ul> <li>Location of Repeater</li> <li>Panel</li> </ul>	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System			
	Basements	N/A	N/A	N/A
	Upper Floor	N/A	N/A	N/A
1X	<ul> <li>Sprinkler above false ceiling</li> </ul>	N/A	N/A	N/A
11.	Internal Hydrants			
	• Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants     per floor	N/A	N/A	N/A
	• Hose Box	N/A	N/A	N/A
12.	Yard Hydrants		14/7	IV/A
	Total number of hydrants	N/A	N/A	N/A
	<ul> <li>Hose Box</li> </ul>	N/A	N/A	N/A
13.	Pumping Arrangements	1	,	11/7
•				
·	Discharge of main pump	N/A	N/A	
-	Danie	N/A	N/A	N/A
- >	The state of main pumps	N/A	N/A	N/A
-	J Paris Par	N/A	N/A	N/A
. >	pump nead	N/A	N/A	N/A
-		N/A	N/A	N/A
	The state of the s	N/A	N/A	N/A
	- Triditadi	N/A	N/A	N/A
	stopping	* v v	2	
>	z minp frouse riccess	N/A	N/A	N/A
•	Terrace level	,		
>	Discharge of pump	450 LPM in each	450 LPM x 2 in	MR
	Hood of the	block	each block	
>	Head of the pump Power supply	40 MH	40 MH	MR
· >	The state of the s	Required	Provided	MR
	Auto starting of pump	Required	Provided	MR
14.	Captive water Storage for fire f			11
	<ul> <li>Underground tank</li> <li>capacity</li> </ul>	N/A	N/A	N/A
	> Draw of connection	N/A	N/A	N/A
	> Fire service inlet	NA	Provided	NA

N REPORT (Ground +Three Upper Floors)

15 16.	Exit Signage	Required	ORT   (Ground +	11
10.	Provision of Lifts	6	Provided	MR
	<ul><li>Pressurization of L</li><li>Shaft</li></ul>	ift N/A	N/A	
	Pressurization of lit	t N/A	N/A	N/A
	lobby  Communication in 1		N/A	N/A
	Car	A	N/A	N/A
	<ul><li>Fireman's Groundin Switch</li></ul>	g N/A	N/A	8 - 2
	Lift Signage	N/A		N/A
7.   8.   1	Standby power supply	Required	N/A	N/A
0. 1	Refuge Area	N/A	Provided	MR
	> Total area	N/A	N/A	
). F	Location	N/A	N/A	N/A
· F	Fire control room		N/A	N/A
	Detector system panel	N/A		
	Flow Switch Panel	N/A	N/A	N/A
	I Dyslem Panal	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
C	Building Floor Di	N/A	N/A	N/A
Sp	culai Fire Protection	N/A	N/A	N/A
Sy	stems for Protection of ecial Risks, if any;		N/A	N/A
	ono, if ally,			

Note:-A) General requirements for schools as per Director of Education circular

- 1. Escape route .....- Clear
- 2. LPG cylinders in laboratories :- Nil
- 3. Electric wiring .....- Conduit Wiring MCB and ELCB... Electric circuit .....- MCB Provided
- 4. Electric meter board / switch board panel.:-Not Under the staircase 5. Basement use as per BBL 1983 :- N/A
- 6. Emergency telephone no. board :- Displayed
- 7. Generator set .....: :- NA
- B)Each class room is provided with 2 Doors.
- **C**) There is a Multipurpose Hall measuring 28m x 17m (476 m²) equipped with Fire Extinguishers & Hose Reel Hose having sufficient exits. Stage is concreted made & there is no fixed seats.

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended

Signature of the Inspecting Officer Name

: A.K. Jaiswal Designation: A.D.O. (Jwala Puri)