## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2017/ 1224

Dated: 18/68/17

## FIRE SAFETY CERTIFICATE

Certified that M/s Hotel City International Deluxe located at 8/22, WEA, Karol Bagh, New Delhi- 110005 comprised of basement (Storage), ground floor (reception, shop & office), first floor (08 guest rooms) & second floor (08 guest rooms) (Total 16 guest rooms) and a pantry for staff on terrace was granted FSC by this department vide letter no. F.6/DFS/MS/GH/2014/SZ/912 dated 22.07.2014. The building was re-inspected by the officer concerned of this department on 07-08-2017 in presence of Mr. Lovleen Anand, proprietor of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class residential (Guest house) with effect from 18/68/17 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 18/58/19 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to: -

1. The Joint C.P..C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The Manager, M/s Hotel City International Deluxe, 8/22, WEA, Karol Bagh, New Delhi- 110005.

## Conditions for the Validity of Fire Safety Certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

1. Name & address of the building : M/s Hotel City International Deluxe, 8/22, WEA, Karol Bagh, New Delhi- 110005

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2014/SZ/912 dated 22.07.2014

5. Fire Safety directives letter No : Nil

6. Date of inspection : 07-08-2017

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers from the building side

: Mr. Lovleen Anand, proprietor

9. Year of Construction : 2000-2001

10. Applicant's letter No. : 1837/Addl. C.P/Lic. (H)/dated New Delhi the 06.07.2017

The said guest house is comprised of basement (Storage), ground floor (reception, shop & office), first floor (08 guest rooms), second floor (08 guest rooms) and one pantry on the terrace.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire Safety Requirements as per letter dt. 22.07.2014	Provided at site	Remarks MR/NMR				
1	Access to building							
	Road width	06 mts	Provided	MR				
	Gate width		Directly accessible	MR				
	Width of internal road	N/A	N/A	N/A				
2	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases	-		-				
	Upper Floors	01	01	MR being old case				
	Basements	01	01	MR being old case				
	b. Width of staircases			-				
	Upper Floors	1.25 Mts.	Provided	MR being old case				
	Basements	1.25 Mts.	Provided	MR being old case				
	c. Protection of exits	-						
W	Fire check door	N/A	N/A	N/A				
	Pressurization	N/A	N/A	N/A				
	e. No. of continuous staircases to terrace	01	01	MR				
	g. Width of Corridor	N/A	N/A	N/A				
	h. Door Size	Old case	Provided (0.78 mt.)	MR being old case				
}	Compartmentation.							
	Fire check door	N/A	N/A	N/A				
	Sealing of electrical shafts	N/A	N/A	N/A				
	Fire Rating of shaft door	N/A	N/A	N/A				
	Water Curtain	N/A	N/A	N/A				
	Fire Dampers	N/A	N/A	N/A				



4	Smoke Management System.			1000			
	• Basements	30 a/c per hour	Exhaust fan provided		MR		
	Upper floors	12 a/c per hour	Natural Ventilation	a	MR		
5	Fire Extinguishers						
	Total numbers	12	Provided		MR		
	• Types	ABC type	Provided		MR		
	IS marking	ISI marked	Provided		MR		
6	First-Aid Hose Reels.						
	<ul> <li>Total numbers on each floor</li> </ul>	01	Provided		MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided		MR		
	Nozzle diameter	5 mm	Provided	- Control of the Cont	MR		
7	Automatic fire detection and alarming						
	Type of detectors	N/A	N/A		N/A		
	Location of Main Panel	N/A	N/A		N/A		
	• Location of Repeater Panel	N/A	N/A		N/A		
	Alternate source of power	Required	Provided		MR		
	Hooters' Location	N/A	N/A		N/A		
8	MOEFA	Required	Provided		MR		
9	Public Address System.	Required	Provided		MR		
10	Automatic Sprinkler System.						
	• Basement	Required	Provided		MR		
	Upper Floor	N/A	N/A		N/A		
*	Sprinkler above false ceiling	N/A	N/A		N/A		
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A		N/A		
	Number of hydrants per floor	N/A	N/A		N/A		
	Hose Box	N/A	N/A		N/A		
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A		N/A		
	Hose Box	N/A	N/A		N/A		
13	Pumping Arrangements.	4	8				
	Ground Level						
	Discharge of main Pump	N/A	N/A		N/A		
	Head of Main pump	N/A	N/A		N/A		
	Number of main pumps	N/A	N/A		N/A		
	> Jockey Pump out put	N/A	N/A		N/A		
	Jockey pump head	N/A	N/A		N/A		
		N/A	N/A		N/A		

	> Standby Pump out put	14/22		
	Standby Pump Head	N/A	N/A	N/A
	> Auto Starting/ Manual stopping	N/A	N/A	N/A
	> Pump House Access			
	Terrace level	450 LPM	Provided	MR
	Discharge of pump	40 mts	Provided	MR
	Head of the pump	Required	Provided	MR
	> Power Supply	Required	Provided	MR
	> Auto Starting of pump			
14 Ca	ptive Water Storage for fire fighting.			
14 Ca	TI I would tonk canacity	N/A	N/A	N/A
	- cction	N/A	N/A	N/A
	<ul><li>Draw-off connection</li><li>Fire service inlet</li></ul>	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
6-1	Overhead Tank capacity	5,000 lts	Provided	MR being old case
		Required	Provided	MR
	xit Signage.	1414	X2343 - 1	
16 P	rovision of Lifts.	N/A	N/A	N/A
	• Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car		N/A	N/A
	Fireman's Grounding Switch	N/A		N/A
	• Lift Signage	N/A	N/A	IN/A
17	Standby power supply	Required	Provided (125 KVA	MR MR
	Refuge Area.		The state of the s	
10	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
10	Fire Control Room			
19	D. J. Jan Cristom Panel	N/A	N/A	N/A
=	Detector System Fance     Flow Switch Panel	N/A	N/A	N/A
		N/A	N/A	N/A
	PA System Panel  Parker backup	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans      Building Floor Plans      Systems for	Required	One ABC type fire extinguisher found	MR
20	Special Fire Protection Systems for Protection of special Risks, if any:	1	provided near elect. p	anel
	1 Totalion of Special 2-2-2		ware checked and four	1 functional at 1

The fire protection systems provided in the building were checked and found functional at the

1,

finenection

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/SZ/912 datable 22.07.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer
Name M.K.CHATTOPADHYAY
Div. Officer (South West)

Fig. 12

Fig. 12

Signature of the Inspecting Officer
Name M.K.CHATTOPADHYAY
Div. Officer (South West)

CFO (South)

Miscell Vetts

565/20/500

11-8-13

blease