GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/GH/SZ/2017/ 1234

Dated:

18/08/17

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Ivory Palace located at 14A/27, WEA, Karol Bagh, New Delhi110005 comprised of basement (storage), ground floor (reception, office & 02 guest rooms), first floor (07 guest room), second floor (07 guest rooms) and third floor (03 guest rooms) (total 19 guest rooms) was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2014/NDZ/934 dated 28.07.2014. The premises was re-inspected by the officer concerned of this department on 07/08/2017 in presence of Sh. Sanjay Kapoor, owner of the guest house and found that deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class group-A, residential (guest house) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 18/08/17 at New Delhi by.

18)8 (VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. The Manager, M/s. Hotel Ivory Palace, 14A/27, WEA, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : M/s Hotel Ivory Palace located at 14A/27, WEA, Karol

Bagh, New Delhi- 110005

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2014/NDZ/934 dated 28.07.2014

5. Fire Safety directives letter No : N/A.

6. Date of inspection : 07.08.2017

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

from the building side : Sh. Sanjay Kapoor, Owner

9. Year of Construction : 1999-2000 10. Applicant's letter No. : nil dated nil

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per letter No28.07.2014	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
-	Gate width	05 mts	Directly accessible	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangeme	nt of Exits				
A	a. Number of staircases	_	-	<u> </u>		
	Upper Floors	01	Provided	MR being old case		
	Basements b. Width of staircases	01	Provided	MR being old case		
			-	-		
		1.25 mts.	1.28 mts	MR being old case		
	Upper Floors	1.25 mts.	1.20 mts	MR being old case		
	Basements		-	_		
	 c. Protection of exits Fire check door Pressurization No. of continuous staircases to terrace 	N/A	N/A	N/A		
		N/A	N/A	N/A		
		0.1	01	MR		
	g. Width of Corridor	1.25 mts	1.50 mts	MR		
	h. Door Size	Old case	Provided (0.78 mt.)	MR being old case		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts		Sealed			
	 Fire Rating of shaft door 	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					

5	Fire Extinguishers						
	Total numbers	14	Provided	MR A			
	• Types	CO ₂ , ABC type	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming system.						
	• Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby Pump out putStandby Pump Head	N/A	N/A	N/A			
	Standby Pump HeadAuto Starting/ Manual stopping	N/A	N/A	N/A			
	> Pump House Access	N/A N/A	N/A N/A	N/A N/A			
	Terrace level	17/74		IN/A			

	> Discharge of pump	450 LPM	Provided	MR		
1	> Head of the pump	30 mts	Provided	MR		
	> Power Supply	Required	Provided	MR		
	> Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for fire fighting.					
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	> Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	10,000 lts	Provided (4000 lts)	MR being old case		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.	ovision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	N/A	N/A	N/A		
	Fireman's Grounding Switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
		N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backupBuilding Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. pane	MR 1		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/NDZ/934 dated 28.07.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

355 DU 80

Land

