GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/GH/SZ/2017/ 1254

Dated: 22/08/17

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Indraprastha located at 17A/54, WEA, Karol Bagh, New Delhi- 110005 comprised of basement (storage), ground floor (reception & 03 guest rooms), first floor (06 guest room), second floor (06 guest rooms) and third floor (03 guest rooms) and a pantry for staff (total rooms) was granted FSC by this department vide F.6/DFS/MS/GH/2014/SZ/1043 dated 21.08.2014. The premises was re-inspected by the officer concerned of this department on 14/08/2017 in presence of Sh. Rakesh Sharma, manager of the guest house and found that deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class group-A, residential (guest house) with effect from 22/12/17 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 22/58/17 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. The Manager, M/s. Hotel Indraprastha, 17A/54, WEA, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building: M/s Hotel Indraprastha located at 17A/54, WEA, Karol

Bagh, New Delhi- 110005

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2014/SZ/1043 dated 21.08.2014

5. Fire Safety directives letter No : N/A.

6. Date of inspection : 14.08.2017

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

from the building side : Sh. Rakesh Sharma, Manager

9. Year of Construction : 2000-01

10. Applicant's letter No. : HI/DCP/2017/ dated nil

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per letter No 21.08.2014	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
	Gate width	05 mts	Directly accessible	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-	<u>-</u> .	_		
	Upper Floors	01	Provided	MR being old case		
	Basements	01	Provided	MR being old case		
	b. Width of staircases	<u> </u>	-	_		
	Upper Floors	Old case	1.18 mts	MR being old case		
	Basements	Old case	1.25 mts	MR being old case		
	c. Protection of exits		-	<u>-</u>		
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	01	01	MR		
	g. Width of Corridor	1.25 mts	2.30 mts	MR		
	h. Door Size	Old case	Provided (0.88 mt.)	MR being old case		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	4	Sealed			
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	Exhaust fan provided MR			
	Upper floors	12 a/c per hour	Natural ventilation	n MR		
	- 11					

	Total numbers	14	Provided	MR
	• Types	CO ₂ , ABC type	Provided	MR
	IS marking	ISI marked	Provided	MR
6	First-Aid Hose Reels.			
	Total numbers on each floor	01	Provided	MR
	 Length of hose reel hose 	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarmin			
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	• Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.	•		
	Basement	Required	Provided	MR
2	• Upper Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			1771
	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A		
12	Vond II. 1	IN/A	N/A	N/A
12	Yard Hydrants.			
	Total number of hydrants Hose Box	N/A	N/A	N/A
13	Tiose Box	N/A	N/A	N/A
13	• Ground Level			
		NI/A		
	Discharge of main Pump	N/A N/A	N/A	N/A
	Head of Main pump	*	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head Standby Pump out put	N/A	N/A	N/A .
	Standby Pump out putStandby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
Fèd.	Terrace level	N/A	N/A	N/A
Allva	1000 20 20			

1.7	Discharge of pump	450 LPM	Provided	MR			
A	► Head of the pump	30 mts	Provided	MR			
	Power Supply	Required	Provided	MR			
	➤ Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	5,000 lts	Provided (5000 lts)	MR being old case			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
	Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided (D.G. set 82.5 KVA)	MR			
18							
	> Total Area	N/A	N/A	N/A			
	> Location	. N/A	N/A	N/A			
19	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
		N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Batter backupBuilding Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/SZ/1043 dated 21.08.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

16 8 17 GRE SERV

FILE