GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/GH/SZ/2017/ 12-55

Dated: 22/08/17

FIRE SAFETY CERTIFICATE

Certified that Hotel Swati Deluxe located at 17A/32, WEA, Karol Bagh, New Delhi110005 comprised of basement (storage), ground floor (reception, office, restaurant), first floor (11 guest room), second floor (11 guest rooms), third floor (11 guest rooms) and fourth floor (11 guest rooms) (total 44 guest rooms) was granted FSC by this department vide letter No.
F.6/DFS/MS/GH/2014/NDZ/1230 dated 22.09.2014. The premises was re-inspected by the officer concerned of this department on 14/08/2017 in presence of Sh. Kamlesh Parekh, owner of the guest house and found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class group-A, residential (guest house) with effect from 22/108/117 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 22/08/17 at New Delhi by.

W21/8

(VIPEN KENTAL) CHIEF FIRE OFFIÇER

Copy to:-

1. The Manager, Hotel Swati Deluxe, 17A/32, WEA, Karol Bagh, New Delhi- 110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building: M/s Hotel Swati Deluxe, 17A/32, WEA, Karol Bagh, New

Delhi- 110005

: Lodging House 2. Type of Occupancy

: Renewal 3. Type of Case

: F.6/DFS/MS/GH/2014/NDZ/1230 dated 22.09.2014 4. Details of previous NOC

5. Fire Safety directives letter No : N/A.

: 14.08.2017 6. Date of inspection

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

: Sh. Kamlesh Parekh, owner from the building side

: 2001 9. Year of Construction

: 2001/Addl. C.P/Lic (H) dated New Delhi the 19.07.2017 10. Applicant's letter No.

A	pre Acc	Minimum Standards on fire evention and fire safety U/R 33 ess to building Road width Gate width Width of internal road mber, Width, Type & Arrangemen Number of staircases	06 mts 05 mts N/A	Provided Directly accessible N/A	MR MR
	Nu	 Road width Gate width Width of internal road mber, Width, Type & Arrangemen 	05 mts N/A	Directly accessible	MR
	Nu	 Road width Gate width Width of internal road mber, Width, Type & Arrangemen 	05 mts N/A		
		 Width of internal road mber, Width, Type & Arrangemen 	N/A		DI/A
		mber, Width, Type & Arrangemen		11122	N/A
			t of Exits	· L	
					_
		1 dillo	-	Provided	MR being old case
		• Upper Floors	01	Provided	MR being old case
		Basements	01	-	
	b.	Width of staircases	Old case	1.12 mts	MR being old case
		• Upper Floors	Old case	1.12 mts	MR being old case
		Basements	_		-
	c.	Protection of exits	N/A	N/A	N/A
		• Fire check door	N/A	N/A	N/A
	e	PressurizationNo. of continuous staircases t	0.1	01	MR
		terrace	1.25 mts	1.0 mt.	MR being old case
		. Width of Corridor	Old case	Provided (1.0 mt.)	MR being old cas
		n. Door Size			
3		Compartmentation.	N/A	N/A	N/A
		• Fire check door		Sealed	
		Sealing of electrical shafts Sealing of electrical shafts	NI/A	N/A	N/A
		• Fire Rating of shaft door	N/A N/A	N/A	N/A
		Water Curtain Fire Dampers	N/A	N/A	N/A
		Fire Dampers	1012	so A. esmost ordering in a	
4		Smoke Management System.	30 a/c per ho	ur Exhaust fan prov	ided MR
		BasementsUpper floors	12 a/c per ho	Natural ventilal	ion MR

5	Fire Extinguishers	,		
	Total numbers	20	Provided	MR
	• Types	CO ₂ , ABC type	Provided	MR
	IS marking	ISI marked	Provided	MR
6	First-Aid Hose Reels.			
	Total numbers on each floor	01	Provided	MR
	 Length of hose reel hose 	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarming	g system.		27//
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	 Location of Repeater Panel 	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	Basement	Required	Provided	MR
	Upper Floor	Required	Provided	MR
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
12	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	> Head of Main pump	N/A	N/A	N/A
	> Number of main pumps	N/A	N/A	N/A
	> Jockey Pump out put	N/A	N/A	N/A
	> Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	> Standby Pump Head	N/A	N/A	N/A
	> Auto Starting/ Manual stopping	N/A	N/A	N/A
	> Pump House Access	N/A	N/A	N/A
	Terrace level			

	> Discharge of pump	.450 LPM	Provided	MR			
	Head of the pump	30 mts	Provided	MR			
	Power Supply	Required	Provided	MR			
		Required	Provided	MR			
1	Auto Starting of pump Captive Water Storage for fire fightin	g.		and the second has second			
4		N/A	N/A	N/A			
	Underground tank capacityDraw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	5,000 lts	Provided (5000 lts)	MR being old case			
15	Evit Signage	Required	Provided	MR			
16	Provision of Lifts.	Exit Signage.					
10	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
	Fireman's Grounding Switch	N/A	N/A	N/A			
	• Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
10	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19	Fire Control Room						
12	Detector System Panel	N/A	N/A	N/A			
		N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Batter backup	N/A	N/A	N/A			
20	 Building Floor Plans Special Fire Protection Systems for Protection of special Risks, if any: 	Required	Two ABC type finextinguisher foun provided near elect.	d			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/NDZ/1230 dated 22.09.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

582/20/80 16/8/20/7

red (S). In 1

M.K. CHATTOPADHYAY