GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No.F6/DFS/MS/2017/NDZ/ 1282

Dated:- 28/08/17

FIRE SAFETY CERTIFICATE

Certified that the Multilevel Car Parking cum Commercial Complex at Baba Kharak Singh Marg, New Delhi comprised of B + Gr. + first floor for commercial purposes and eight floors for car parking was granted FSC by this department vide letter No. F6/DFS/MS/2014/NDZ/1179 dated 12/09/2014. The premise was re-inspected by the officer concerned of this department on 03/08/17 in the presence of Mr. Sandeep Kumar (Manager) and found that the said Business have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class parking with effect from --28/11-7------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 28 8 17 ---- at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. Authorized Signatory, Cushman & WAKEFIELD, 14th floor, Building 8 Tower C, DLF Cyber City, Guugram.

 The Manager, Multilevel Car Parking cum Commercial Complex at Baba Kharak Singh Marg, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

17/10

INSPECTION REPORT

1. Name & address of the building : Multilevel Car Parking cum Commercial

Complex at Baba Kharak Singh Marg,

New Delhi

: Car Parking (B + Gr9Upper floor) 2. Type of occupancy

3. Type of case:-: Renewal

: F6/DFS/MS/2014/NDZ/1179 dated 12/07/14 4. Details of previous FSC

5. Fire safety directives No. : N/A 6. Date of inspection:-03/08/17

7. Name of the inspecting officer : Sh. Gurmukh Singh DO/CD,

Sh. M.K. Sharma ADO/CC

8. Name & designation of officer From the building side

: Mr. Sandeep Kumar (Manager)

: 2011 9. Year of construction

10. Applicant's letter No : Nil Dated 20/07/17

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building		e di	^		
	1) Road width	13 mtr.	30 Mtr.	MR		
	2) Gate width	06 mtr.	06 mtr.	MR		
	3)Width of internal road	06 mtr.	06 mtr.	MR		
2.	Number, Width Type & Arran	gement of Exits	3° v - ,	8		
۷.	A. Number of staircases					
	1. Upper floors	03 No	03 No.	MR		
	2. Basements	03 No	03 No.	MR		
	B. Width of staircase			N H		
	1. Upper floors	1.25 mtr. & 1.0 mtr.	01 Nos. 1.25 mtr. & 02 Nos. 1.0 mtr.	MR		
	2. Basements	1.5 mtr. each	1.5 mtr. each	MR		
	C. Protection of exits		A	17		
	1. Fire check door	Required	Provided	MR		
	2. Pressurization	Required	Provided	MR		
	D. No. of continuous	02 No	02 No	MR		
	staircase to terrace			д.		
	E. Width of corridor	1.0 mtr.	1.20 mtr.	MR		
	F. Door size	1.0 mtr.	1.0 mtr.	MR		
3.	Compartmentation		AS A			
	1) Fire check door	Required	Provided	MR		
	2) Sealing of electrical shafts	Required	Provided	MR		
	3) Fire rating of shaft door	Required	Provided	MR		
	4) Water curtain	Required	Provided	MR		
	5) Fire Dampers	Required	Provided	MR		
4.	Smoke Management System	e e e e e e e e e e e e e e e e e e e	* * * * * * * * * * * * * * * * * * *			
	1) Basements	30 ACPH	Mechenical	MR		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers			1.00		
	1) Total numbers	140 Nos.	150 Nos.	MR		
	2) Types	ABC & CO2, foam type	M. ABC, CO2 & W.CO2, M. Foam type	MR		
	3) ISI marking	Required	Provided	MR		

N/119

6.	First-Aid Hose Reel						
	1)Total number	03 each floor	03 each floor	MR			
	2) Length of hose reel hose	30 m	30 m	MR			
_	3) Nozzle diameter	5 mm	5 mm.	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	Required	Provided	MR			
	2) Location of main panel	Gr. Floor	Provided	MR			
	3) Location of repeater panel	Floor wise	Floor wise	MR			
	4) Alternate source of power	Required	Provided	MR			
0	5) Hooter's Location	All floor	All floor	MR			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System						
	1) Basement	Required	Provided	MR			
	2) Upper floors	Required	Provided	MR			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants						
	1) Size of riser/down-comer	150 MM	150 MM	MR			
	2) Number of hydrants per	03	03	MR			
	floor	x=, -x, -					
	3) Hose box each floor	03	03	MR			
12.	Yard Hydrants						
	1) Total number of hydrants	06	06	MR			
12 V	2) Hose box	06	06	MR			
3.	Pumping Arrangement						
	1) Ground level						
	a) Discharge of main	2850 LPM	2850 LPM	MR			
	pump			17110			
	b) Head of main pump	85 mtr.	85 mtr.	MR			
	c) Number of main pump		02	MR			
	d) Jockey pump out put	180 LPM	180 LPM	MR			
	e) Jockey pump head	85 mtr.	85 mtr.	MR			
	f) Stand by pump output	2850 LPM	2850 LPM	MR			
	g) Stand by pump head	85 mtr.	85 mtr.	MR			
	h) Auto starting/Manual	Required	Provided Provided	MR			
	stopping	rioquirou	Trovided	IVIIC			
	2) Terrace level		B ₁				
	a) Discharge of pump	900 LPM	900 LPM	MR			
	b) Head of pump	35 mtr.	35 mtr.				
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump	Required	Provided	MR			
4.	Captive Water Storage for Fire		TIOVIUEU	MR			
	1) Under ground tank	1,50,000 ltr.	1,50,000 ltr.	MD			
	capacity	1,50,000 111.	1,50,000 Itr.	MR			
	a) Draw-off connection	Required -	Provided	MD			
	b) Fire service inlet	Required	Provided	MR			
	c) Access to tank	Required		MR			
	d) Over head tank	25,000 Ltrs.	Provided 25,000 Ltm	MR			
	capacity	23,000 Lus.	25,000 Ltr.	MR			
5.	Exit Signage.	Doguinad	D	1.00			
5.	Provision of Lifts.	Required	Provided	MR			
,							
	a) Pressurization of lift	N/A	N/A	N/A			

	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
* 1	Total area location	N/A	N/A	N/A
19.	Fire Control Room	Required	Provided	MR
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection System for Protection of special Risk, if any: Total flooding			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/2014/NDZ/1179 dated 12/09/2014 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- G.S Chauhan 878

Designation: - DO (CD)

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

P.T. letter is part up of

CFO(ND4)

M.SCOU VETELS