GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2017/ 1356

Dated: 12/09/17

FIRE SAFETY CERTIFICATE

Certified that M/s Hotel Durga Deluxe located at 05/40, WEA, Karol Bagh, New Delhi- 110005 comprised of ground floor (reception, office, pantry & 06 guest rooms), first floor (06 guest rooms), second floor (08 guest rooms) and third floor (03 guest rooms) (total 23 guest rooms) was granted FSC by this department vide letter no. F.6/DFS/MS/GH/2014/NDZ/936 dated 28.07.2014. The premise was re-inspected by the officers concerned of this department on 06-09-2017 in presence of Mr. H.K. Saluja, owner of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class residential (Guest house) with effect from the formula of the prevention of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on 12/08/17 at New Delhi by.

11/9

(VIPEN KENTAL) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

- 1. The Joint C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.
- 2. The Manager, M/s Hotel Durga Deluxe, 05/40, WEA, Karol Bagh, New Delhi-110005.

Conditions for the Validity of Fire Safety Certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION RELOW!

: M/s Hotel Durga Deluxe, 5/40, WEA, Karol Bagh, New 1. Name & address of the building

Delhi.

: Lodging House 2. Type of Occupancy

: Renewal 3. Type of Case

: F.6/DFS/MS/GH/2014/NDZ/936 dated 28.07.2014 4. Details of previous NOC

5. Fire Safety directives letter No : Nil

: 06-09-2017 6. Date of inspection

: M.K. Chattopadhyay, DO(South West) 7. Name of the Inspecting Officers

8. Name and designation of officers

: Mr. H.K. Saluja (Owner) from the building side

: 1992-93 9. Year of Construction

10. Applicant's letter No. : nil dated nil

The said guest house is comprised of ground plus three upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire Safety requirements as per letter dt. 28.07.2014	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	06 mts	Provided	MR
	• Gate width		Directly accessible	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangemen	nt of Exits		11
2		-	_	a -
	a. Number of staircases	02	02	MR
	• Upper Floors	N/A	N/A	N/A
	Basements	_	-	-
	b. Width of staircases	1.25	1.25 mts, 0.98mts	MR being old case
	Upper Floors	1.25 mts. N/A	N/A	N/A
	• Basements	-	-	-
	c. Protection of exits	N/A	N/A	N/A
	Fire check door	11/11		27/4
	 Pressurization 	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	Old case	1.05 mts	MR being old case
	h. Door Size	Old case	0.75 mts	MR being old case
3	Compartmentation.	1	**	-
	Fire check door	N/A	N/A	N/A
	 Sealing of electrical shafts 	N/A	N/A	N/A
	 Fire Rating of shaft door 	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	Fire Dampers	N/A	N/A	N/A
4	Crooks Managament System			
4	Smoke Management System. Basements	30 a/c per hour	r N/A	N/A
	Dascincitis	7		

	• Upper floors	12 a/c per hour	Natural Ventilation	MR		
5	Fire Extinguishers		* ×	-		
	• Total numbers	18	Provided	MR		
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR		
-	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	- MR		
10	Automatic Sprinkler System.	5				
	Basement	N/A	N/A	N/A		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Vand III. day					
12	Yard Hydrants.Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.	IN/A	N/A	11/21		
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A N/A	N/A N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	> Standby Pump Head	N/A	N/A	N/A		
	Auto Starting/ Manual stopping	N/A	N/A			

	Terrace level			14/21		
	Discharge of pump					
	Head of the pump	450 LPM	Provided	MR		
	Power Supply	40 mts	40 mts	MR		
	Auto Starting of pump	Required	Provided	MR		
***************************************		Required	Provided	MR		
14	Captive Water Storage for fire fighting.					
	Underground tank capacity	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	5,000 lts	5,000 lts	MR		
15	Exit Signage.	Required	Provided	MR		
16		,				
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	N/A	N/A	N/A		
	Fireman's Grounding Switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
ı	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	Required	Provided	MR		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Two ABC type fire extinguishers found provided near elect. panel.	N/A		

The fire protection systems provided in the building were checked and found non functional at the time of inspection.

All the shortcomings issued by this department vide letter No. F.6/DFS/MS/GH/SZ/2017/1920 dated 28.07.2017 have been complied with.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/NDZ/936 dated 28.07.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended. DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

Dy. C.F.O. (SZ) - on leave

F. T. letter is put up for Sign