## FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35]

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001**

No.F6/DFS/MS/WZ/2017/ \389

Dated: 20/09/2017

FIRE SAFETY CERTIFICATE

Certified that the Kamal Pharmacy (Ayurvedic) pvt. Ltd located at 14, Industrial Area, Shivaji Marg, (Najafgarh Road), New Delhi-110015, comprised of Ground Floor, Mezzanine and First Floor was granted NOC / FSC by this department vide letter F-6/DFS/MS/2012/2799 dated 27/07/2012. The premises was re-inspected by the officer concerned of this department on 04/09/2009 in the presence of Mr. Rochak Arora and observed that Fire prevention and Fire safety arrangements provided in the premises, found in good working condition. The premises have therefore, deemed complied with the fire prevention and fire safety requirements in accordance with requirement under rule 33 of the Delhi Fire Service Rule 2010 and that the building / premises is fit for occupancy class Industrial Group-G (G-1) with effect from .20.0.9.1.7... for a period of 3 (three) years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS Rules, 2010 Issued on.....at New Delhi.

> (ATUL GARC CHIEF FIRE OFFICER.

Copy to:

1. Authorized Signatory, Kamal Pharmacy (Ayurvedic) pvt. Ltd, 14, Industrial Area, Shivaji Marg, (Najafgarh Road), New Delhi-110015.

## Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipment's shall be maintained in perfect working conditions all the time and any lapse rendering non functional of fire safety measures, management shall be responsible.
- 4. Any deviation with regards to construction, electrical installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularization of unauthorized construction,
- 6. The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt..nic.in.
- 7. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

INSPECTION REPORT

1. Name &address of the building: Kamal Pharmacy (Ayurvedic) pvt. Ltd located at 14, Industrial

Area, Shivaji Marg, (Najafgarh Road), New Delhi-110015.

Floor & 1<sup>st</sup> Floor

2. Type of Occupancy : Class-G (G1) Industrial

3. Type of Case : Renewal

4. Details of previous NOC : F-6/DFS/MS/2012/2799 dated 27-07-2012

5. Fire Safety directives letter No. : N.A. Ground Floor, Mezzanine

6. Date of inspection : 04-09-2017

7. Name of the Inspecting Officers : A.K. JAISWAL ADO (JWP) Total Plot Area-275 m<sup>2</sup>

8. Name and designation of officers

From the building side : Mr. Rochak Arora

9. Year of Construction : 2005-06

10. Applicant's letter No. : KPPL/35/17 dated 09-06-17

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL/BBL Requirement	Provided at site	Remarks MR/NMR		
	Access to building					
	Road width	6 mtr	12 mtr	M.R		
	1000	4.5 mtr	5 mtr	M.R		
	• Gate width					
		N.R.	N.R.	N.R.		
	<ul> <li>Width of internal road</li> </ul>					
2.	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	1 2	2	M.R.		
	a. Number of stancases					
	<ul> <li>Upper Floors</li> </ul>	··· NR	NR	M.R.		
	• Basement	N.A	N.A	N.A		
		3		=		
	b. Width of staircases	× ×				
		1.50 mtr	A) Ground to Mezzanine Floor-I mtr & 1x 0.70 mtr.			
	Upper Floors	, ,	B) Ground Floor to 2 <sup>nd</sup> Floor-1x1	1x1.30 mtr (Being Old Case)		
	Сррегионз	N.A	N.A	N.A		
	Basement	IV.A	N.A	14.71		
		NID	N.R	N.R		
	c. Protection of exits	N.R	17.17	TV.IX		
	Fire check door					
	Pressurization	N.R	N.R	N.R.		
	1.2500.1200.1	1	1	MR		
	d. No. of continuous staircases					
	to terrace	1.0				
		Halls only	Halls only	M.R.		
	e. Width of Corridor	1 mtr	1 mtr	M.R.		
	f. Door size					
3.	Compartmentation.					
	Fire check door	N.R	N.R	N.R.		
				N.R.		
	Sealing of electrical shafts	N.R	N.R	IN.IX.		
	Fire Rating of shaft door	N.R	N.R	N.R.		
		IV.IX	11.10			
	Water Curtain	N.R	N.R	N.R.		
	Fire Dampers	N.R	N.R	N.R.		

		N.A	N.A	N.A	
	Basements		1 W 1		
	The State of the S		F-1	n.	
	Upper floors	required	Exhaust fans are provided	M.R	
5.	Fire Extinguishers				
	Total numbers	10	13	M.R	
	• Types	ABC type	provided	M.R	
	ISI marking	ISI marked required	provided	M.R	
6.	First-Aid Hose Rees.				
	Total numbers on each floor	1	1	M.R	
	Length of hose reel hose	30 m	30 mtr	M.R	
	Nozzle diameter	5 mm	5 mm	M.R	
7.	Automatic fire detection and alar	ming system.			
				- NA	
17-10-	Type of detectors	N.R	N.R	N.A	
	<ul> <li>Location of Main Panel</li> </ul>	N.R	N.R	N.A	
			A	NI A	
	• Location of Repeater Panel	N.R	N.R	N.A	
	Alternate source of power	N.R	N.R	N.A	
	Hooter's Location	N.R	N.R	N.A	
8.	MOEFA	N.R	N.R.	M.R.	
9.	Public Address System	N.R.	N.R.	N.A	
10.	Automatic Sprinkler system				
	Basement	N.R.	N.R.	N.R.	
	Upper Floor	N.R.	N.R.	N.R.	
		N.R.	N.R.	N.R.	
	Sprinkler above false ceiling	TV.IX.	11.10.	14.16.	
78			,		
11.	Internal Hydrants		<u> </u>		
	Size of riser/down-comer	150 mm	150 mm	M.R.	
	Number of hydrants per floor	1-	1	M.R.	
	Hose Box				
) j.		1	1	M.R.	
12.	Yard Hydrants.				
	Total number of hydrants	N.R.	ND	Not applicable.	
	I of all number of hydrants	T.A.C.	N.R.	Hot applicable.	
1					

			11 9	
	Ground Level			
	Discharge of main pump	N.R.	Ń.R.	N.R
	➤ Head of Main pump	N.R.	N.R.	N.R
	Number of main pumps	N.R.	N.R.	N.R
	> Jockey Pump out put	N.R.	N.R.	N.R
	> Jockey pump head	N.R.	N.R.	N.R
	> Standby pump out put	N.R.	N.R.	N.R
	> Standby pump Head	N.R.	N.R.	N.R
	Auto Starting/Manual stopping	N.R.	N.R.	N.R
	➤ Pump Hose Access	N.R.	N.R.	N.R
	Terrace level	*		
	➤ Discharge of pump	450 LPM	450 LPM	M.R
0	➤ Head of the pump	40 mtr	40 mtr	M.R
	Power supply	Required	provided	M.R
	> Auto Starting of pump	Manual	Provided	M.R
14.	Captive Water Storage for fire fig	ghting.		
	Underground tank capacity	N.R.	N.R.	N.R
	Draw -off connection	N.R.	N.R.	N.R
	Fire service inlet	N.R.	N.R.	N.R
	<ul><li>Access to tank</li><li>Overhead Tank Capacity</li></ul>	N.R.	N.R.	N.R
	,	10,000 ltr	12,000 ltr	M.R
15	Exit Signage.	N.R.	N.R.	N.A
16.	Provision of Lifts		*	4/2/2/
	• Pressurization of Lift Shaft	N.A.	N.R.	N.R.
	Pressurization of Lift lobby	N.A.	N.R.	N.R.
	Communication In lift Car	N.A.	N.R.	N.R.
	<ul> <li>Fireman's Grounding</li> <li>Switch</li> </ul>	N.A.	N.R.	N.R.
	Lift Signage	N.A.	N.R.	N.R.
17.	Standby power supply	Required	Provided	MR

18.	Refuge Area	N.R.	N.R	N.A.
	> Total Area	N.R.	N.R.	N.A.
	> Location	N.R.	N.R.	N.A.
19.	Fire Control Room			
	> Detector System Panel	N.R.	N.R.	Not applicable
	> Flow Switch Panel	N.R.	N.R.	Not applicable
	> PA system Panel	N.R.	N.R.	Not applicable.
	> Batter backup	N.R.	N.R.	Not applicable.
	Building Floor plans	N.R.	N.R.	Not applicable
20.	Special Fire Protection Systems for	N.R.	N.R.	Not applicable
	Protection of special Risks, if any:			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F-6/DFS/MS/2012/2799 dated 27-07-2012 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

D. p. (Co)

Micher : 11/8/12

Signature of the Inspecting Officer

Name

: Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)

cfolo /3 alr

ATT

f. T. is added for sign. fl.