GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2017/ ND2 /1457

Dated : 66 10 17

FIRE SAFETY CERTIFICATE

Certified that the Hotel Florence located at 2719, Bank Street, Karol Bagh, New Delhi comprised of Basement + Ground + 03 Upper floors, Basement (hall), Ground floor (Reception + shops), 1st floor to 3rd floor (08 guest rooms at each floor), total 24 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2014/NDZ/895 dated 21/07/14. The premises was re-inspected by the officer concerned of this department on 15/09/17 in the presence of Mr. Jitender (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 24 guest rooms only with effect from -- 6-4-17 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 1-6-10-11-7--at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- by to:1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 1865/Addl. C.P./ Lic.(H) dated 07/07/17.
- 2. The Manager, Hotel Florence at 2719, Bank Street, Karol Bagh, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSP	ECTION REPO	ORT			
1.	Name & address of the building	Hotel Flore	ence at 2719, Bank	Street, Karol		
	,	Bagh, Nev				
2.	Type of occupancy:- Residential, Sub Division-A-1					
	B + Gr. + 03 Upper floors (total 24 Guest rooms)					
	Basement (Hall), Ground floor (Reception +					
	Shops), 1 st floor to 3 rd floor					
	(08 guest rooms at each floor).					
	Type of case:- Renewal					
4.	Details of previous FSC:-	No. F6/DFS/MS/GH/2014/NDZ/895 dated 21/07/14.				
5.	Fire safety directives No N/A					
	Date of inspection:-	15/09/17				
	Name of the inspecting officer:					
8.	Name & designation of officer					
-	from the building side:-	Mr. Jitende	er (Manager)			
9.	Year of construction:-					
10.	Applicant's letter No:-	1865/Addl.	C.P./ Lic.(H) dated	07/07/17.		
				Old Case		
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
	Prevention and fire safety	Existing fire		MR/NMR		
	U/R 33	safety arrangements				
1.	Access to Building	arrangements				
	1) Road width	N/A	12 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr			14/14		
<u> </u>	A. Number of staircases	dingement of E2				
	1. Upper floors	01 Nos.	01 Nos.	MR, Old case		
	2. Basements	01 Nos.	01 Nos.	MR, Old case		
	B. Width of staircase	01 1403.	011103,	11111, 314 4434		
	1. Upper floors	1.25 mtr.	1.17 mtr.	MR, Old case		
	2. Basements	1.25 mtr.	1.0 mtr.	MR, Old case		
	C. Protection of exits	1.23 11111.	1.0 11111.	Witt, Old case		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace	01	01	IVIK		
	E. Width of corridor	N/A	115 cm, 150 cm	N/A		
	F. Door size	N/A	85 cm x 205cm	N/A		
3.	Compartmentation	IVA	65 CHI X 205CHI	IVA		
-	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	sealed	N/A		
1	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A				
			N/A	N/A		
4	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System 1) Basements	20 A CDII	Evhaust for	MD		
		30 ACPH	Exhaust fan	MR		
	2) Upper floors	12 ACPH	Natural	MR		

5.	Fire Extinguishers	5		1.00			
	1) Total numbers	10 Nos.	10 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR			
	3) ISI marking	Required	Provided	MR			
6.	First-Aid Hose Reel						
	1) Total number of eachfloor	01	01	MR			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	05 mm	05 mm	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	Required	D.G. set 120 KVA	MR			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System	_					
10.	1) Basement	Required	Provided	MR			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling	100					
11.	Internal Hydrants	-		\$			
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor						
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump						
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pur		N/A	N/A			
	d) Jockey pump out pu	t N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump outp	ut N/A	N/A	N/A			
	g) Stand by pump head		N/A	N/A			
	h) Auto starting/Manua		N/A	N/A			
	stopping		, ,				
	2) Terrace level	- x 1/2		2			
	a) Discharge of pump	450 LPM		MR			
	b) Head of pump	30 mtr.	30 mtr.	MR			
				N/D			
	c) Power supply	Required	Provided Provided	MR MR			

14.	Captive Water Storage for	Fire Field		
	Under ground tank capacity			
	a) Draw-off connection		N/A	N/A
	b) Fire service inlet	N/A N/A	N/A	N/A
	c) Access to tank	N/A N/A	N/A	N/A
a =	d) Over head tank		N/A	N/A
1.7	capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	1.00
16.	Provision of Lifts.		Tiovided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
17.	e) Lift signage	Required	Provided	MR
18.	Stand by Power Supply	Required	Provided	MR
10.	Refuge Area	N/A	N/A	NI/A
	Total area location	N/A	N/A	N/A N/A
9.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A N/A
	b) Flow switch panel	N/A	N/A	NI/A
	c) PA system panel	N/A	N/A	N/A
	d) Datt 1 1	Required	Provided	N/A
	-	- toquitou	riovided	MR
		N/A	N/A	N/A
).	Special Fire Protection System Risk, if any:	for Protecti	on of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2014/NDZ/895 dated 21/07/2014 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

423/ch102 Doles) (18/1/4)/17 Doles)

Dy CRO (MDZ)

M 2119

F1101