## GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F.6/DFS/MS/EH/2017/SZ/ 15D 4

Dated: .(8./.1.0./.17

## FIRE SAFETY CERTIFICATE

Certified that M/s Haldiram Restaurant located at Ground, First & Second floor of B-1/H-8, M.C.I.E., Main Mathura Road, New Delhi-110044, building comprised of Basement, Ground plus two upper floors (Main building has already been issued FSC vide letter dated 18/11/2015) Owned/Occupied by M/s Haldiram Marketing Pvt. Ltd. was granted Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/EH/2014/SZ/1316 dated 21/10/2014. The restaurant premises was re-inspected by the officer concerned of this department on 07/09/2017 in the presence of Mr. SK Jain (Manager) and found that the said restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class-D "Assembly" (restaurant) as above with effect from the date of issue of this certificate for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on \_\_\_\_\_\_at New Delhi by

(Vipin Kental) Chief Fire Officer Ph. 011-23412225

Copy to: -

- 1. The Additional C.P. (Lic.) 1st floor, Police Station Defence Colony, New Delhi-110049
- 2. The Manager, M/s Haldiram Restt., B-1/H-8, M.C.I.E, Mathura Road, New Delhi-110044
- 3. M/s Haldiram Marketing Pvt. Ltd., B-1/H-8/1, M.C.I.E, Main Mathura Road, N Delhi-44

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.
- 7. This FSC will become null & void, if the FSC of the main premise is not renewed under rule 37 of DFS Rules-2010
- 8. The capacity of O.H. tank should be made from 10,000 ltrs to 20,000 ltrs before next renewal.

		ON REPORT			
- 1	Name & Address of the Building	HALDIRAM REST	AURANT, located at Pl	ot No. B-1/	
2 2 2		H-8, M.C.I.E., Mathura Road, New Delhi-110044			
2	Type of Occupancy	Assembly buildings 'Group-D'			
3	Building comprised of	Basement, Ground plus two upper floors.			
. 4	Type of Case	Renewal			
5	Details of Previous NOC	F.6/DFS/MS/EH/2	2014/SZ/1316 Dated 2	1-10-2014	
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	07-09-2017			
8	Name of the Inspecting Officers	ADO R.N. Singh			
9	Name & Designation of Officers from the building side	Mr. SK Jain (Manager)			
10	Year of construction	2011 Restt at ground, 1st & 2nd floor of the bldg			
11	Applicant letter No.	Nil dated 08.08.2017			
S. No	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks	
	and Fire Safety U/R 33	requirement		MR/NMF	
1	Access to Building.				
	Road width	Approachable	6 mtr	MR	
	Gate width	N/A	N/A	N/A	
	Width of internal road	N/A	N/A	N/A	
2	Number, width, type & arrangement of exits				
	a. Number of Staircase		14		
	Upper floors	Required	Two	MR	
	Basement floor	N/A	N/A	N/A	
	b. Width of Staircase			1 30	
-	Upper floors	1.50m + 1.25m	1.5m & 1.25m	MR	
	Basement floor	N/A	N/A	N/A	
	c. Protection of exits		y		
1	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
	d. No. of continuous staircase to terrace	Required	One	MR	
	e. Width of corridor	N/A	N/A	N/A	
	f. Door size	N/A	1.5 mtr	N/A	
3	Compartmentation.				
	Fire check door.	N/A	N/A	N/A	
	Sealing of electrical shafts.	N/A	N/A	N/A	
	• Fire rating of shaft door.	N/A	N/A	N/A	
	Water curtain	N/A	N/A	N/A	
	• Fire dampers.	N/A	N/A	N/A	
1	Smoke Management system.	1777		1 11/1	
4.	Basement	N/A	N/A	N/A	
. , .		Required in Kitchen	Provided	MR	
E	Upper floors  Fire Extinguishors	Kitchell	7		
5.	Fire Extinguishers.	6 No's	10 Na2a	MD	
	Total numbers		10 No's	MR	
	• Types	ABC / Co2	ABC-06, Co2-04	MR	
	ISI Marking	ISI marked	Provided	MR	
6.	First Aid Hose Reels.		A LOS CONTRACTOR		
	<ul> <li>Total numbers on each floor.</li> </ul>	One	One	MR	
	<ul> <li>Length of hose-reel hose.</li> </ul>	30 m 5 mm	30 m 5 mm	MR	

7	Automatic fire detection & alarming system.		Not required	
	Type of detectors	N/A	Smoke type	N/A
	Location of Main Panel	N/A	Ground floor	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	Provided	N/A
	Hooter's location	N/A Required	Each floor Provided	N/A MR
8.	MOEFA			
9.	Public Address System	N/A	N/A	N/A
0.	Automatic Sprinkler System			
	Basement	N/A	N/A	N/A
	Upper floors	Required	Provided	MR
	Sprinkler above false ceiling	N/A	N/A	N/A
1.	Internal Hydrants.			
	Size of Riser/Down-comer	Required	100 mm	MR
	Number of Hydrant per floor	Required	One	MR
	Hose box.	Required	One	MR
2.	Yard Hydrants.			
	Total number of hydrants.	Required	Two	MR
	Hose box.	Required	Two	MR
3.	Pumping arrangements.			
	Ground Level		Not required	
	Discharge of main pump.	N/A	N/A	N/A
	Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	> Jockey Pump output.	N/A	N/A	N/A
	> Jockey Pump head.	N/A	N/A	N/A
	> Standby Pump output.	N/A	N/A	N/A
	> Standby Pump head.	N/A	N/A	N/A
	Auto Starting / Manual Stopping.	N/A	N/A	N/A
	Terrace Level			
	Discharge of pump.	900 LPM	900 & 180 LPM	MR
	> Head of pump.	Required	40 mtr each	MR
	Power supply.	Required	Provided	MR
	> Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for Fire Fighting.	15,0volla		
	Underground tank capacity.	(1,50,000 ltrs	75,000 ltrs	MR
	Draw-off connection.	N/A	N/A	N/A
	➤ Fire Service Inlet.	N/A	N/A	N/A
	Access to tank.	N/A	N/A	N/A
	Overhead tank capacity.	10,000 ltrs	10,000 ltrs	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft.	N/A	N/A	N/A
	<ul> <li>Pressurization of lift lobby.</li> </ul>	N/A	N/A	N/A
	Communication in lift car.	N/A	· N/A	N/A
	• Fireman's switch.	N/A	N/A	N/A
	Lift signage.	N/A	N/A	N/A
17	Standby Power Supply	Required	Provided	MR
18.	Refuge Area	Not required		
	Total area	N/A	N/A	N/A
		N/A	N/A	N/A

19.	Fire Control Room.	Not required		
	Detector System Panel.	N/A	Provided	N/A
	Flow Switch Panel.	N/A	N/A	N/A
	PA system Panel.	N/A	N/A	N/A
	Battery backup	N/A	Provided	N/A
	Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for the	Required	ABC type fire extinguishers	MR
	Protection of special Risk, if any:		provided near electrical panel	

The Fire protection systems provided in the building were checked / operated and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/GH2014/SZ/1316 dated 21.10.2014, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

: R.N. Singh

Designation: ADO

Renewal

M/s Haldiram Restt., B-1, H-8, M.C.I.E., Main Mathura Road, New Delhi

Name

flease clearify here the Ula water storage is meeting the sequisemental sor, als. 14 of your inspection note.