GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No.F.6/DFS/MS/School/2017/SZ/ / 58/

Dated: 7/11/

FIRE SAFETY CERTIFICATE

Certified that the **St. Thomas' School,** Goyala Vihar, Near Sector-19, Dwarka, New Delhi-110074 comprised of basement, ground floor plus three upper floors, owned/occupied by St. Thomas' School was issued Fire Safety Certificate by this department vide letter no. F.6/DFS/MS/School/2014/SZ/772 dated 23.06.2014. The School building was re-inspected by the officer concerned of this department on 07.10.2017 in the presence of Sh. Dharam Veer Sharma (Care Taker) and found that the St. Thomas' School have deemed complied the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class "Educational" for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

(VIPIN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- The Principal,
 St. Thomas' School, Goyala Vihar,
 Near Sector-19, Dwarka, New Delhi-110074
 - Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	1. Name & address of the building: St. Thomas' School, Goyala Vihar, Near Sector-19, Dwarka, New						
	1. Name & address of the building: St. Thomas Delhi-1100		mai, Near Sector-	19, Dwarka, New			
	2. Type of Occupancy : Education	al					
	3. Type of Case : Renewal 4. Details of Previous NOC : F.6/DFS/N	40/0-11/2014/07	1772 1-4-122 06	2014			
	 4. Details of Previous NOC : F.6/DFS/N 5. Fire Safety directives letter No : N/A 	/IS/School/2014/SZ	7772 dated 23.06.	2014			
	6. Date of inspection : 07.10.2017	7					
		ndeep Duggal					
	8. Name and designation of officers From the building side : Sh. Dharam Veer Sharma (Care Taker) 9. Year of Construction : 2005						
	10. Applicant's letter No. : Nil dated	15.06.2017					
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per FSC dt. 23.06.2014	Provided at site	Remarks MR/NMR			
1.	Access to building						
	Road width	Accessible 6 mtrs	15 mtrs	MR			
	Gate width	4.5 mtrs	5.9 mtrs	MR			
	Width of internal road	N/A	N/A	N/A			
2.	Number, Width, Type & Arrangement of Exits			1			
	a. Number of staircases						
	• Upper Floors	03 No's	04 No's	MR			
	Basements	03 No's	04 No's	MR			
	b. Width of staircases		170 170 170 0	. 0			
	Upper Floor	150 cms	150, 150, 150 & 150 cms	MR			
	Basements	150 cms	150, 150, 150 &	MR			
	c. Protection of exits		150 cms				
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	d. No. of continuous staircases to						
	terrace	Required	Two	MR			
	e. Width of Corridor	150 cms	200 cms	MR			
	f. Door Size	100 cms	110 cms (Single)	MR			
3.	Compartmentation	, , , , , , , , , , , , , , , , , , , ,	(Single)				
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	Basements	Required	Exhaust fans are provided	MR			
	• Upper floors	Required	Natural ventilation	MR			
5.	Fire Extinguishers						
	Total numbers	30 no.'s	Provided	MR			
	Types	ABC/CO ₂ type	Provided	MR			
	IS marking	ISI marked	ISI marked	MR			
6.	First-Aid Hose Reels						
	Total numbers on each floor	02 no.'s	Provided	MR			
TANK T	Length of hose reel hose	30 mtrs	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			

	 Type of detectors Location of Main Panel 	N/A	N/A	N/A
	Location of Main Fanel Location of Repeater Panel	N/A N/A	N/A	N/A
	Alternate source of power	N/A N/A	N/A N/A	N/A
	Hooters' Location	N/A	N/A	N/A
		N/A	Provided	N/A
8.	MOEFA Public Address System	N/A	Provided	N/A
9.	Automatic Sprinkler System			
10.	Basement	Required	Provided	MR
	Ground Floor	N/A	N/A	N/A
L'artin	Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants			
	Size of riser/down-comer	N/A	100 mm	N/A
	Number of hydrants per floor	N/A	Two	N/A
	Hose Box	N/A	Two	N/A
12.	Yard Hydrants			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13.	Pumping Arrangements			
	Ground Level	1 1 2-1-1		
	Discharge of main Pump	N/A	N/A	N/A
	> Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out putJockey pump head	N/A	N/A	N/A
	> Standby Pump out put	N/A	N/A	N/A
	> Standby Pump Head	N/A	N/A	N/A
	> Auto Starting/Manual Stopping	N/A	N/A	N/A
				N/A
4		N/A N/A	N/A N/A	N/A N/A
	> Pump House Access	IN/A	IV/A	14/11
417	Terrace level	450 1 70 6	D 11.1	MR
	> Discharge of pump	450 LPM & 180 LPM	Provided	IVIK
	> Head of the pump	40 mtrs	Provided	MR
	> Power Supply	Required	Provided	MR
	> Auto Starting of pump	Required	Provided	MR
14.	Captive Water Storage for fire fighting			A SHOW
	Underground tank capacity	50,000 ltrs	Provided	MR
	> Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	Provided	N/A
The state of	> Access to tank	N/A	N/A	N/A
The same	Overhead Tank capacity		Provided	MR
		15,000 ltrs Required	Provided	MR
15.	Exit Signage.	Required	Trovided	IVIIX
		STEEL HAN		
16.	Provision of Lifts.			27/4
	 Pressurization of Lift Shaft 	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
a 4 5	Communication In lift Car	N/A	N/A	N/A
	Fireman's Grounding Switch	Required	Provided	MR
1-1-24	Lift Signage	Required	Provided	MR
4-	Charles across and the	N/A	Provided	N/A
17.	Standby power supply	IVII	1101144	
18.	Refuge Area.		Visite and All	
10.	Morago Alloni			
	> Total Area	N/A	N/A	N/A
- Assista	> Location	N/A	N/A	N/A
1000	ning 200	1771	ar disk of your Marin	

19.	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested, checked and found

functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number F.6/DFS/MS/School/2014/SZ/772 dated 23.06.2014 renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note: - As per the letter submitted by the Manager (placed at C-23) there are less than 45 students in each classroom and the lift does not go in the basement and it is used for upper floors only.

Signature of Inspecting Officer

Name: - Sandeep Duggal

Designation:- Asstt. Divisional Officer

D.O. (South West)

Go Cs2)