GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/SCHOOL/2017/ W2/1678

Dated: 20/11/17

FIRE SAFETY CERTIFICATE

Certified that the Bhatnagar International School(without Auditorium) located at Bhera Enclave, Paschim Vihar, NewDelhi-110087 comprised of Basement, Ground & Four Upper Floors only owned / occupied by Bhatnagar International School, have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 13.09.2017 in presence of Mr. Ranjeet Chaudhary (Civil Eng.) and that the building / premises is fit for occupancy class Educational (Group-B) with effect from _______ for a period of 3 (Three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

Issued on _____at New Delhi by.

CHIEF FIRE OFFICER

Copy to:-

1. Authorized Signatory, Bhatnagar International School, Bhera Enclave, Paschim Vihar, NewDelhi-110087.

Following Fire Safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of fire equipment's and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipment's shall be maintained in perfect working conditions all the time and any lapse rendering non functional of fire safety measures, management shall be responsible.
- 4. Any deviation with regards to construction, electrical installation etc. may be got verified from the concerned authorities.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This NOC may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt..nic.in.
- 8. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 9. Auditorium/Multipurpose Hall shall obtain separate FSC.

INSPECTION REPORT

1. Name & address of the building:

Bhatnagar International School,

Bhera Enclave, Paschim Vihar, NewDelhi-110087.

2. Type of Occupancy

: Educational

Basement, Ground & 4

Upper Floors

3. Type of Case

: New

4. Details of previous NOC : Letter No. : Nil

5. Fire Safety directives Letter No.

: NBC (Part-IV)

6. Date of inspection

: 13/09/2017

7. Name of the Inspecting Officer

: A.K. Jaiswal (ADO JWP)

8. Name and designation of Officer

from the building side

: Mr. Ranjeet Chaudhary (Civil Eng.)

9. Year of Construction

: 2015-16

10 Applicant's letter No.

· Bis/PV/2017/2299 dated 27/07/2017

G	Minimum standards on fire		NIDC (Part IV)		Provided at		Remarks	
S		A CONTROL OF CONTROL O	1,20 (site	a at	MR/NMR	
No		tion and fire safety	Requirements		Site		5	
1.	U/R 33							
1.	Access of building • Road width		6 mtr		60 mtr		MR	
	Gate width		4.5 mtr		4.5 mtr		MR	
	-	Width of internal road	6 mtr		6 mtr		MR	
2.	Number, width, Type & Arrangements of exits							
۷٠	a. Number of staircases							
	Upper floors		4		4		MR	
		Basements	4		4 & 2 Ramp		MR	
	Width	Width of staircases						
	•	Upper floors	1.50 mtr				s scarting <mark>has</mark> emoved)	
	•	Basements	1.50 mtr		.50 mtr x 4, 2 ramps of		MR	
	Protection of exits							
	•	Fire check door	Required	Required		ed	MR	
	•	Pressurization	Required	Required		Provided		
	b.	No of continuous	2		2		MR	
		staircase to terrace				J.	MR	
	c.	Width Of Corridor	1.50 mtr	1.50 mtr		2.00 mtr		
	d.	Door Size	1.00 mtr		1.00 m	tr x 2	MR	
3.	Comp	partmentation	*				NAD.	
4.	•	Fire check door	Required		Provided		MR	
	•	Sealing of electrical shafts	Required		Provided		MR	
	•	Fire Rating of shaft door	NR		NR		NR	
		Water Curtain	NR		NR		NR	
	-	Fire Dampers	NR		NR		NR	
	Smoke managements System							
7.	Basements		30 a/c per hour		Provided		MR	
1		Upper floors	12 a/c per hour		Provid	ed	MR	
5.	Fire I	Extinguishers	· · · ·				2	
J.	1 110 1	JAMIE GIOTIOTO			26		NAD	

	I otal numbers on each floor	4	4			
	Length of hose reel	30 Mtr.	30 Mtr.	2→IR		
	hoseNozzle diameter	5 mm	5 mm	MR		
7.	Automatic fire detection and a					
	Type of detector	NR	Provided	NR		
	 Location of Main Panel 	NR	GF	NR		
	 Location of Repeater 	NR	NR	NR		
	• Panel	NR	NR	NR		
	Alternate source of power	NR	NR	NR		
	Hooters' Location	NR	NR	NR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System					
10	Basements	Required	Provided	MR		
	Upper Floor	NR	NR	NR		
	Sprinkler above false ceiling	NR	NR	NR		
11.	Internal Hydrants					
11.	Size of riser/down-comer	100 mm	100 mm	MR		
	Number of hydrants per floor	4	4	MR		
	Hose Box	4	4	MR		
12		`		2 2 4 7		
12	Total number of hydrants	Required	Provided	MR		
	Hose Box	Required	Provided	MR		
13						
	Ground Level					
	Discharge of main pump	2280 LPM	2280 LPM	MR		
	> Head of main pump	60 MH	60 MH	MR		
	> Number of main pumps	1	1	MR		
	> Jockey pump out put	180 LPM	180 LPM	MR		
	Jockey pump head	60 MH	60 MH	MR		
	Standby Pump out put	2280 LPM	2280 LPM	MR		
	> Standby Pump Head	60 MH	60 MH	MR		
	> Auto Staring/Manual	Required	Provided	MR		
	stopping > Pump House Access	NR	NR	NR		
	Terrace level	IVIX				
	> Discharge of pump	900 LPM	900 LPM	MR		
		40 MH	40 MH	MR		
	Head of the pumpPower supply	Required	Provided	MR		
	> Auto starting of pump	Required	Provided	MR		
			11001000			
14	1					
	 Under ground tank capacity 	1,00,000 ltr	1,00,000 ltr	MR		
	> Draw of connection	Required	Provided	MR		
1	> Fire service inlet	Required	Provided	MR		
	> Access to tank	Required	Provided 25,000 Ltr.	MR		
1	Overhead Tank	25,000 Ltr.	DE 000 11.	1 0 /111		

		(1/6)				
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	Pressurization of Lift Shaft	Required	Provided	MR		
	Pressurization of lift lobby	Required	Provided	MR		
	Communication in lift	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	> Lift Signage	Required	Provided	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area		-			
	> Total area	NR	NR	NR		
	> Location	NR	NR .	NR		
19.	Fire control room					
	Detector system panel	NR	NR	NR		
	> Flow Switch Panel	NR	NR	NR		
	> PA System Panel	NR	NR	NR		
	> Battery backup	NR	NR	NR		
	Building Floor Plans	NR	NR	NR		
20.	Special Fire Protection	NR	NR	NR		
	Systems for Protection of					
	special Risks, if any;			1		

Note:- General requirements for schools as per NBC (Part-IV) / Director of Education circular dated 01/03/2011.

- 1. Escape route:- Clear
- 2. LPG cylinders in laboratories :- Nil
- 3. Electric wiring:- Conduit Wiring MCB and ELCB.....

 Electric circuit:- MCB Provided
- 4. Electric meter board / switch board panel.:-Not Under the staircase
- 5. Basement use as per BBL 1983 :- N/A
- 6. Emergency telephone no. board :- Displayed
- 7. Generator set: :- NA

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

D.0/(W)

Signature of the Inspecting Officer Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)

Dy. Cho Wig

ill the

aldful g