GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/2017/SZ/ 1693

FIRE SAFETY CERTIFICATE

Certified that the R.K. Residency, BE-404, Hari Nagar, New Delhi110064 comprised of Stilt plus four upper floors, having parking & in house kitchen at the Stilt Floor, 06 Guest rooms on First Floor, 06 Guest Rooms on Second Floor & 03 Guest Rooms on Third Floor and Half Portion of Third Floor & Fourth Floor are used by owner as residence, owned/occupied by M/s R.K Residency was issued FSC by this department vide letter no. F.6/DFS/MS/GH/2014/SZ/1626 dated 23.12.2014. The guest house building was re-inspected by the officer concerned of this department on 03.11.2017 in presence of Sh. Anshu Bharti (Proprietor) and found that Guest House R.K Residency have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building/premises (15 Guest rooms on First, Second and Partial Third floor) is fit for occupancy class "Residential" (Guest house) w.e.f the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on ______at New Delhi.

CHIEF FIRE OFFICER

Dated: 20.11.17

Copy to: -

The Joint C.P (Lic.), Police Station,
 Defence Colony, 1st floor, New Delhi,

Sh. Anshu Bharti (Proprietor),
 R.K. Residency, BE-404,
 Hari Nagar, New Delhi110064

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

Building is comprised of Stilt plus Four upper floors but Guest House is at First, Second and half Third Floor INSPECTION REPORT 1. Name & address of the building: R.K. Residency, BE-404, Hari Nagar, New Delhil 10064 2. Type of Occupancy Residential 3. Type of Case Renewal 4. Details of Previous NOC F.6/DFS/MS/GH/2014/SZ/1626 dated 23.12.2014 5. Fire Safety directives letter No Nil 6. Date of inspection 03.11.2017 7. Name of Inspecting Officer A.D.O. Sandeep Duggal 8. Name and designation of officers From the building side Sh. Anshu Bharti (Proprietor) 9. Year of Construction 2006 10. Applicant's letter No. Nil dated 18.09.2017 Stilt floor (parking & in house kitchen), 06 Guest rooms on First Floor, 06 Guest Rooms on Second Floor & 03 Guest Rooms on Third Floor and Half Portion of Third Floor & Fourth Floor are used by owner as residence. S. Minimum Standards on fire prevention and fire Requirements Provided at Remarks No. safety U/R 33 as per FSC dt. site MR/NMR 23.12.2014 1. Access to building Road width 06 mtrs. 06 mtrs M/R Gate width N/A N/A N/A Width of internal road N/A N/A N/A 2. Number, Width, Type & Arrangement of Exits Number of staircases Upper Floors 01 No. 01 No. M/R Basements N/A N/A N/A Width of staircases 90 cms 92 cms M/R Upper Floor N/A N/A N/A Basements c. Protection of exits N/A N/A N/A Fire check door N/A N/A N/A Pressurization d. No. of continuous staircases to Required One M/R terrace 1.5 mtrs 03 mtrs M/R Width of Corridor 87cms M/R, being Old Door Size 100 cms case 3. Compartmentation Fire check door N/A N/A N/A Sealing of electrical shafts N/A N/A N/A Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A 4. Smoke Management System N/A N/A N/A Basements Upper floors Required Natural M/R Ventilation 5. Fire Extinguishers Total numbers Eight no's Provided M/R ABC/CO₂ Types Provided M/R IS marking ISI marked M/R ISI marked First-Aid Hose Reels 6.

	nilding is comprised of Stilt plus Four upper floors but	Guest House is at Fi	rst, Second and n	all Third Floor
7.	Automatic fire detection and alarming system			27/4
	> Type of detectors	N/A	N/A	N/A
	> Location of Main Panel	N/A	N/A	N/A
	> Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of powerHooters' Location	N/A	N/A	N/A
	P Hootels Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System			
*	> Basement	N/A	N/A	N/A
A. A.	➢ Ground Floor	N/A	N/A	N/A
River	> Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants			
11.	> Size of riser/down-comer	N/A	N/A	N/A
	> Number of hydrants per floor	N/A	N/A	N/A
	➤ Hose Box	N/A	N/A	N/A
12.	Yard Hydrants	1471	11/11	
12.	> Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	The contract of the contract o	11//1	TV/A	IVIX
13.	Pumping Arrangements	F.		
1 7	Ground LevelDischarge of main Pump	NT/A	N/A	N/A
	Head of Main pump	N/A		
	> Number of main pumps	N/A	N/A	N/A
	> Jockey Pump out put	N/A	N/A	N/A
- 1-	> Jockey pump head	N/A	N/A	N/A
×=		N/A	N/A	N/A
1.5	> Standby Pump out put	N/A	N/A	N/A
	> Standby Pump Head	N/A	N/A	N/A
	> Auto Starting/Manual Stopping	N/A	N/A	N/A
			N/A	N/A
	> Pump House Access	N/A	IN/A	IVA
	Pump House AccessTerrace level			1.6/10
	> Discharge of pump	450 LPM	Provided	M/R
	> Head of the pump	40 mtrs	Provided	M/R
	> Power Supply	Required	Provided	M/R
	> Auto Starting of pump	Required	Provided	M/R
14.	Captive Water Storage for fire fighting			
	Underground tank capacity	N/A	N/A	N/A
	> Draw-off connection	N/A	N/A	N/A
	> Fire service inlet	N/A	N/A	N/A
	Access to tank Overhead Tank capacity	N/A	N/A	N/A
	Overhead Tank capacity	5000 ltrs	Provided	M/R
		Required	Provided	M/R
15.	Exit Signage.			
16.	Provision of Lifts.	TO BE THE TANK OF	I The second	
	25(1) 200 201 1 Len Office			27/4
	> Pressurization of Lift Shaft	N/A	N/A	N/A
	> Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A
	Fireman's Grounding SwitchLift Signage	Required	Provided	M/R
H I I I	Ditt bigliage	Required	Provided	M/R
17.	Standby power supply	Required	Provided	M/R
-	The state of the s			
18.	Refuge Area.			
16.	> Total Area	N/A	N/A	N/A
W. Park	1 Own I area			

2/10

Building is comprised of Stilt plus Four upper floors but Guest House is at First, Second and half Third Floor

19.	Fire Co	ntrol Room Detector System Panel	N/A	N/A	N/A
	>	Flow Switch Panel	N/A	N/A	N/A
	> PA System Panel	N/A	N/A	N/A	
	>	Battery backup	N/A	N/A	N/A
		Building Floor Plans	N/A	N/A	N/A
20.		Fire Protection System for Protection of Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested, checked and found functional at

the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number F.6/DFS/MS/GH/2014/SZ/1626 dated 23.12.2014 renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended

Sandaling

Signature of Inspecting Officer

Name: - Sandeep Duggal

Designation:- Asstt. Divisional Officer

D.O. (South West) - on leave

1270 cfo 52

12/11.17/11

FIRE SERVE

Clo St)

M.S CEU

13/11

FT Letter in put up for higharway plean.

Cfo CS2) — Combac.

Cfo | the Alaysia and the standard plane.