FORM 'H'
FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No: FB DFS MS 2017 1700

Dated: 23.11.17

FIRE SAFETY CERTIFICATE

Certified that the building of **Bharati Vidyapeeth's Institute of Management & Research** located at **A – 4, Paschim Vihar, Rohtak Road, New Delhi – 110063** comprised of Basement + **Ground + Three Upper floors** has already issued fire safety certificate vide letter no. F.6/MS/DFS/2014WZ/1437 dated 21-11-2014. The premises was re – inspected by the officers from this department on dated 14-11-2017 in the presence of Sh. Pramod Patil (Estate Manager) and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition and that the building/premises is fit for occupancy class **Educational Building Group B Sub Division B - 2,** with effect from <u>23/11/2017</u> in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 23.11.17... at New Delhi.

Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Director,

Bharati Vidyapeeth's Institute of Management & Research,

A - 4, Paschim Vihar, New Delhi – 110063.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. The basement shall be used strictly as per the provision of building by laws.

- 6. The shed on terrace of 4th floor shall not be used for any purpose of teaching & storage.
- 7. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 9. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

comprising 4 no. class rooms & 2 Office vide letter no. 02/CC/B/WZ/09/I dated 14-01-2009 from MCD. Now, a certificate dated 14/11/2017 submitted by Dr. Vikas Nath, Director, BVIMR indicating that the rainy shed will be not used for any official and residential purpose and no toilet is built in 4th floor. The rainy shed will not be used for any other purpose in future. The same was found sealed during inspection.

INSPECTION REPORT

1. Name & address of the building: Bharati Vidyapeeth's Institute of Management & Research, A – 4, Paschim Vihar, New Delhi – 110063.

2. Type of Occupancy : Educational (Basement + Ground + 3 Upper Floors)

3. Type of Case : Renewal

4. Details of previous NOC : F.6/MS/DFS/2014WZ/1437 dated 21-11-2014

5. Fire Safety directives Letter No.: F.6/DFS/MS/BP/95/131 dated 06-02-1995

6. Date of inspection : 14-11-2017

7. Name of the Inspecting Officer: Mukesh Verma, DO (West)

8. Name and designation of Officer

from the building side : Sh. Pramod Patil (Estate Manager)

9. Year of Construction : 1999

10. Applicant's letter No. : BVIMR/ND/719/2017-18 dated 18-09-2017

S. No	Minimum standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR			
1		- I a qui e me m	Site				
1.							
	 Road width 	60 m	Provided	MR			
	• Gate width	5 m	Provided	MR			
	Width of internal road	NA	NA	NA			
2.	Number, width, Type & Arrangem	ents of exits					
	a. Number of staircases						
	 Upper floors 	2	Provided	MR			
	 Basements 	2 stair &4 ramps	Provided	NA			
	b. Width of staircases						
	 Upper floors 	1.2 mtr	167 cm, 170cm	n MR			
	 Basements 	1.2 mtr	2X1.5 mtr, 4X				
			280 cm ramp				
	c. Protection of exits		Provided				
	 Fire check door 						
		Required in	Provided	MR			
	 Pressurization 	basement	-				
	d. No of continuous staircase	NA	NA	NA			
	to terrace e. Width Of Corridor	1	Provided	MR			
	f. Door Size	1.2 m	Provided	MR			
2		1 mtr	1 mtr Provided	MR			
3.	Compartmentation						
	Fire check door	NA	NA	NA			
	 Sealing of electrical shafts Fire Rating of shaft door 	NA	NA	NA			
	• Water Curtain	NA	NA	NA			
		NA	NA	NA			
	• Fire Dampers	NA	NA	NA			

 Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Required Provided MI Provided MI Provided MI Provided MI Provided MI MI First – Aid Hose Reels Provided MI Provided MI MI First – Aid Hose Reels Provided MI Provided MI MI Eight – Aid Hose Reels Provided MI Provided MI MI Eight – Aid Hose Reels Provided MI Provided Provided<th>R R R</th>	R R R				
5. Fire Extinguishers • Total numbers • Types • IS marking 6. First – Aid Hose Reels • Total numbers • ABC & CO ₂ • ISI marked Provided Provided Provided MI Provided MI	R R R				
• Types • IS marking 6. First – Aid Hose Reels ABC & CO ₂ ISI marked Provided Provided MI Provided	R R				
Types IS marking ISI marked First – Aid Hose Reels ABC & CO ₂ ISI marked Provided MI Provided MI	R R				
IS marking ISI marked Provided MI First – Aid Hose Reels	R				
6. First – Aid Hose Reels	R				
• Total numbers on each floor 2 Provided MI					
• Length of hose reel hose 30m Provided MI					
Nozzle diameter 5mm Provided MI					
7. Automatic fire detection and alarming system					
 Type of detectors NA NA NA 					
 Location of Main Panel NA NA NA 					
 Location of Repeater Panel NA NA NA 					
 Alternate source of power NA NA NA 					
 Hooters' Location NA NA NA 					
8. MOEFA NA Provided MR	2				
9. Public Address System NA NA NA					
10. Automatic Sprinkler System					
Basements Required Provided	MR				
• Upper Floor NA NA	NA				
Sprinkler above false ceiling NA NA	NA				
11. Internal Hydrants:					
Size of riser/down- comer NA 100 mm Provided	MR				
Number of hydrants per floor	MR				
Hose Box NA Provided	MR				
12. Yard Hydrants					
TT D	NA				
Hose Box NA NA NA NA NA NA NA NA	NA				
13. Pumping Arrangements: • Ground Level					
D Head of main					
Number of main numes					
lockey numn out nut					
lockey nump head					
Standby Pump out put					
Standby Pump Head NA NA NA					
Auto Staring/Manual NA NA NA					
stopping					
Pump House Access NA NA NA NA NA					
• Terrace level					
Discharge of pump Head of the pump 2X450 lpm Provided MR					
Power supply 40Mtr Provided MR					
Auto starting of pump Required Provided MR					
Required Provided MP					
The storage for the righting.					
 Under ground tank capacity 1,00,000 litres Provided MR 					
Draw off connection NA NA NA					
Fire service inlet Required Provided MR					
Access to tank Required Provided MR					
Overhead Tank capacity 30,000Ltr Provided MR					
15 Exit Signage Required Provided MR					
16. Provision of Lifts					
 ▶ Pressurization of Lift Shaft ▶ Pressurization of lift lobby NA NA NA NA 					
Pressurization of lift lobby NA NA NA	Achi				

110	
M 7	
	DIA
	NA

▶ Lift Signage	NA	NA	NA
	NA	NA	NA
18. Refuge Area ➤ Total area	NA NA	NA NA	NA NA
➤ Location19. Fire control room➤ Detector system panel	NA	NA	NA NA
Flow Switch Panel PA System Panel	NA NA	NA NA	NA NA
Battery backupBuilding Floor Plans	NA NA	NA NA	NA NA
20. Special Fire Protection Systems for Protection of special Risks, if	NA	NA	NA ·
any;			

The fire protection systems provided in the building were test checked and found functional at

the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F.6/MS/DFS/2014WZ/1437 dated 21-11-2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name Mukesh Verma

Designation DO (West)

CTP15

(Ro (West) Lillo

noreth