GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO.DFS/MS/2017/Cos/1735

Dated: 01 / 12 /2017

FIRE SAFETY CERTIFICATE

Certified that the M/s Kwality Color Cosmatics, Plot No.142, Pocket-O, Sector-2, DSIIDC, Bawana, Delhi- 39 comprised of Basement + ground + two upper floors owned/occupied by that M/s Kwality Color Cosmatics have complied with the fire prevention and fire safety requirement in accordance with rule 33 of the Delhi Fire Service Rules, 2010, and verified by the officer concerned of Fire Service on 13/11/2017 in the presence of Smt. Devi Aneja and that the building /premises is fit for occupancy Industrial G-2(ii) building with effect from 01/12/2017 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by guests in an event of emergency.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments.
- 3. The fire suppression / protection arrangements provided in the guest house are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the licensee.
- 5. This report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The use of basement shall be in accordance with building bye laws
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

Issued on 01/12/17 at New Delhi.

Chief Fire Officer Ph: 011-23414250

Copy to:

- 1. M/s Kwality Color Cosmatics, Plot No.142, Pocket-O, Sector-2, DSIIDC, Bawana, Delhi-39.
- 2. K.C.Aggarwal, DY. Drugs Controller & Licensing Authority, Govt. of National Capital Territory of Delhi, F-17, Karkardooma, New Delhi-110032

M/s Kwality Color Cosmatics, Plot No.142, Pocket-O, Sector-2, DSIIDC, Bawana, Delhi- 39

INSPECTION REPORT

B+Gr.+1+2nd floors two rooms

1. Name & address of the building: M/s Kwality Color Cosmatics, Plot No.142, Pocket-O

Sector-2, DSIIDC, Bawana, Delhi-39

2. Type of Occupancy : Industrial G-2(ii)

3. Type of Case : New Case

4. Details of previous NOC : Letter No. Nil Dated: Nil

5. Fire Safety directives letter No : DFS Act 2007 & Rule 2010/ NCB Part IV

6. Date of inspection : 13/11/2017

7. Name of the Inspecting Officers : ADO (BW)

8. Name and designation of officers

from the building side : Smt. Devi Aneja

9. Year of Construction : 2010

10. Applicant's letter No. : Nil dated 30/10/2017

Plot Area: 150 sq m Covered Area: B-150 sq m, Gr-150 sq m, FF-150 sq m, SF-15 sq m Total-465 Sq m2

6		Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Ac	cess to building			
		Road width	9.00 mtr	Provided	MR
		• Gate width	N/A	N/A	N/A
		Width of internal road	N/A	N/A	N/A
2	Nu	mber, Width, Type & Arrangement of	of Exits		
	a.	Number of staircases	N/A	N/A	N/A
		Upper Floors	02	02	MR .
		Basements	02	02	MR
	b.	Width of staircases	N/A	N/A	N/A
		Upper Floors	1.25 & 0.75 mtr	1.25 & 0.80 mtr	MR
		Basements	1.25 & 0.75 mt	1.25 & 0.80 mtr	MR
	c.	Protection of exits	N/A	N/A	N/A
		Fire check door	N/A	N/A	N/A
		Pressurization	N/A	N/A	N/A
	e	No. of continuous staircases to terrace	N/A	N/A	N/A
		Width of Corridor	N/A	N/A	N/A
		Door Size	1.00 mtr	1.00 mtr	MR

Musey

3	Compartmentation.	N/A	N/A	N/A	
	Fire check door	Required Lift lobby	Provided	MR	
	Sealing of electrical shafts	N/A	N/A	N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.				
	Basements	30 a/c per hour	Exhaust fan & natural		
	Upper floors	12 a/c per hour	ventilation		
5	Fire Extinguishers				
	Total numbers	07 ABC	07	M/R	
	• Types		ABC	M/R	
	• IS marking	ISI marked	Yes	M/R	
6	First-Aid Hose Reels.				
	Total numbers on each floor	One	Provided	MR	
	 Length of hose reel hose 		Provided	MR	
	Nozzle diameter	30 m 5 mm	Provided	MR	
7	The second secon		Provided	IVIK	
	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A	N/A	
	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	N/A	N/A	N/A	
9	Public Address System.	N/A	N/A	N/A	
10	Automatic Sprinkler System.				
	Basement	Required	Provided	MR	
	• Upper Floor	Required	Provided	MR	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
	- A	N/A	N/A	N/A	
	Size of riser/down-comer	IN/A	11//		
	Size of riser/down-comerNumber of hydrants per floor	N/A N/A	N/A	N/A	

Mahm

12	Yar	d Hydrants.			
		Total number of hydrants	N/A	N/A	N/A
		Hose Box	N/A	N/A	N/A
13	Pun	ping Arrangements.		1,1/1	IN/A
	-	Ground Level	N. C.		
,			N/A	N/A	N/A
		Discharge of main Pump	N/A	N/A	N/A
-		Head of Main pump	N/A	N/A	N/A
		Number of main pumps	N/A	N/A	N/A
		> Jockey Pump out put	N/A	N/A	N/A
		> Jockey pump head	N/A	N/A	N/A
		Standby Pump out put	N/A	N/A	N/A
		> Standby Pump Head	N/A	N/A	N/A
		Auto Starting/ Manual stopping	N/A	N/A	N/A
		Pump House Access	N/A	N/A	N/A
	•	Terrace level	N/A	N/A	N/A
		Discharge of pump	900 LMP	900 LMP Provided	MR
		➤ Head of the pump	40 m	40 m Provided	MR
		Power Supply	N/A	N/A	N/A
		> Auto Starting of pump	N/A	N/A	N/A
14	Capti	ve Water Storage for fire fighting			
	•	Underground tank capacity	N/A	N/A	N/A
	>	Draw-off connection	N/A	N/A	N/A
	>	Fire service inlet	N/A	N/A	N/A
	~ ~	Access to tank	N/A	N/A	N/A
	•	Overhead Tank capacity	10,000 ltr	10,000 ltr Provided	MR
15	Exit S	ignage.	Required	Provided	MR
6	Provis	sion of Lifts.			
	•	Pressurization of Lift Shaft	N/A	N/A	N/A
	•	Pressurization of Lift lobby	N/A	N/A	N/A
	•	Communication In lift Car	N/A	N/A	N/A
	•	Fireman's Grounding Switch	N/A	N/A	N/A
	•	Lift Signage	N/A	N/A	N/A
7	Standb	y power supply	N/A	N/A	N/A

Mhilan

18	Refuge Area.				
	> Total Area	N/A	N/A	N/A	
	> Location	N/A	N/A	N/A	
19	Fire Control Room				
	Detector System Panel	N/A	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	Batter backup	N/A	N/A	N/A	
	Building Floor Plans	N/A	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A	

The fire protection systems provided in the building were test checked and found at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....Nil...

Signature of the Inspecting Officer

October

Signature of the Inspecting Officer

Name

Name

Designation

Designation

400(Ba)