GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2017/19 45

Dated: 06/12/17

FIRE SAFETY CERTIFICATE

Certified that the **Delhi Darbar Guest House**, 15A/26, W.E.A, Karol Bagh, New Delhi-110005 comprised of basement, ground floor plus four upper floors, using basement as hall/storage, ground floor as reception & shops, first floor having 07 guest rooms, second floor having 09 guest rooms, third floor having 08 guest rooms, fourth floor having 04 guest rooms (total 28 guest rooms), water storage tanks & generator on terrace was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2012/3357 dated 13.09.2012 owned/occupied by Mr. Inderdeep Singh. The premises was re-inspected by the officer concerned of this department on 27/11/2017 in presence of Mr. Inderdeep Singh (Owner) and found that the owner/occupier have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class residential (guest house) with effect from 6 Group for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 6 6 12 17 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Mr. Inderdeep Singh (Owner), Hotel Delhi Darbar, 15A/26, W.E.A, Karol Bagh, New Delbi-05.

2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building: Hotel Delhi Darbar, 15A/26, W.E.A, Karol Bagh, New

Delhi-110005

2. Type of Occupancy : Residential (Guest House)

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2012/3357 dated 13.09.2012

5. Fire Safety directives letter No : N/A

6. Date of inspection : 27-11-2017

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

from the building side : Mr. Inderdeep Singh (Owner)

9. Year of Construction : 2000-01

10. Applicant's letter No. : Nil dated Nil

S. No.	M	est house is comprised of baseme inimum Standards on fire ention and fire safety U/R 33	Requirement as per letter No13.09.2012	Provided at site	Remarks MR/NMR	
1	Acces	s to building				
	•	Road width	06 mts	Provided	MR	
	•	Gate width	05 mts	Directly accessible	MR	
	•	Width of internal road	N/A	N/A	N/A	
2	Numb	er, Width, Type & Arrangeme	nt of Exits	A		
		nber of staircases	_			
	•	Upper Floors	01	Provided(01)	MR being old case	
	•	Basements	01	Provided(01)	MR being old case	
	b. Wid	th of staircases	_	- 1	_	
	•	Upper Floors	125 cms	125 cms	MR	
	•	Basements	125 cms	150 cms	MR	
	c. Prote	ection of exits	- '	-,	-	
	•	Fire check door	N/A	N/A	N/A	
		Pressurization	N/A	N/A	N/A	
	e. No.	of continuous staircases to	01	01	MR	
	g. Widt	h of Corridor	1.25 mts	1.60 & 2.30 mts	MR	
	h. Door	Size	Old case	Provided (0.88 mt.)	MR being old case	
	Compa	rtmentation.	-	(The being old case	
		Fire check door	N/A	N/A	N/A	
		Sealing of electrical shafts	N/A	N/A	N/A	
		Fire Rating of shaft door	N/A	N/A	N/A	
		Water Curtain	N/A	N/A	N/A	
	• H	Fire Dampers	N/A	N/A	N/A	
	Smoke Management System.					
	• I	Basements	30 a/c per hour	Exhaust fan provided	MR	
	• [Jpper floors	12 a/c per hour	Natural ventilation	MR	

	Total numbers	04 no.'s/floor	Provided	MR
	• Types	CO ₂ , ABC type	Provided	MR
	IS marking	ISI marked	Provided	MR
6	First-Aid Hose Reels.			
	Total numbers on each floor	01	Provided	MR
	• Length of hose reel hose	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarming			
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	Basement	Required	Provided	MR
	• Upper Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.		5	
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	> Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual stopping	N/A	N/A	N/A
	Pump House AccessTerrace level	N/A	N/A	N/A
,	1 errace level			

	<u></u>	Discharge of pump	450 LPM	Provided	MR	
7	>	Head of the pump	30 mts	Provided	MR	
	>	Power Supply	Required	Provided	MR	
			Required	Provided	MR	
4	-	e Water Storage for fire fightin	g.			
	•	Underground tank capacity	N/A	N/A	N/A	
	>	Draw-off connection	N/A	N/A	N/A	
	>	Fire service inlet	N/A	N/A	N/A	
	>	Access to tank	N/A	N/A	N/A	
	•	Overhead Tank capacity	5,000 lts	Provided	MR	
5	Exit Si	gnage.	Required	Provided	MR	
6	Provision of Lifts.					
	•	Pressurization of Lift Shaft	N/A	N/A	N/A	
	•	Pressurization of Lift lobby	N/A	N/A	N/A	
		Communication In lift Car	Required	Provided	MR	
	•	Fireman's Grounding Switch	Required	Provided	MR	
	•	Lift Signage	Required	Provided	MR	
17	Stand	by power supply	Required	Provided	MR	
18	Refuge Area.					
	>	Total Area	N/A	N/A	N/A	
	>	Location	N/A	N/A	N/A	
19	Fire C	ontrol Room				
RE	RVIO	Detector System Panel	N/A	N/A	N/A	
23	Wall State	Flow Switch Panel	N/A	N/A	N/A	
ABBrooks AB	Mat	PA System Panel	N/A	N/A	N/A	
of F	re Office	Batter backup	N/A	N/A	N/A	
		Building Floor Plans	N/A	N/A	N/A	
20	_	al Fire Protection Systems for tion of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR	

The fire protection systems provided in the building were checked and found functional at the time of inspection. The shortcomings issued vide letter no. F.6/DFS/MS/GH/2015/2151 dated 18.09.15 has been complied.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/GH/2012/3357 dated 13.09.2012, renewal under rule 37 of the Delhi Fire Service rules 2010 is recommended.

87/100/3W 28/11/20/7 DFA is put up for approval & signature please.

28/11/17 M.K. CHATTOPADH