GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHTPLACE NEW DELHI- 110001

No.F6/DFS/MS/School/NDZ/2017/ 1832

Dated: |9.12.17

FIRE SAFETY CERTIFICATE

Certified that the Shri S.R. Capital School H-27, Ganga Vihar, Delhi, owned/occupied by Shri S.R.Capital School, comprising of ground plus two upper floors was granted FSC vide letter no. No. F F.6/DFS/MS/School/2012/4217 dated 09/11/12. The school building was inspected by the officer concerned of this department on 30/11/17 in the presence of Principal of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular no.262-362 Dated 17.01.2005 issued by the Director of Education and found that the building is fit for occupancy class B "Educational Building" with effect from 17.12.17 for a period of three years, subject to conditions printed overleaf.

Issued on 19.12.17 at New Delhi by

(Vipin Kental)

Chief Fire Officer

To,

The Principal Shri S.R. Capital School H-27, Ganga Vihar, Delhi,

Copy to:-

The Director of Education GNCT of Delhi, Old secretariat Delhi -54.

- Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided inthe first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

N18

1. Name & address of the building: Shri S.R.Capital School H-27, Ganga Vihar, Delhi .

2. Building is comprised of : Ground +2 upper floors

3. Type of Occupancy : Educational 4. Type of Case : Renewal

5. Details of Previous NOC letter : F.6/DFS/MS/School/2012/4217 dated 09/11/12 6. Fire Safety direction letter No : Circular No.262-362 Dated 17.01.2005 Director of

Education : 30/11/17

7. Date of Inspection

8. Name of the Inspecting officers: ADO R.K. Yadav

9. Name and designation of Officer

from the building side : Principal

10. Year of Construction : 1996

11. Applicant's letter No : SSRCS/2017/02 Dated 16/10/17

NO.	Minimum Standards on fire prevention		Provided at	Remark			
	and fire safety U/R33	Requirement	Site				
1`	Access to building						
	Road width	06 Mtrs.	Provided	MR			
	Gate width	N/A	Directly accessible	MR			
	Width of internal road	N/A	On road	MR			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases		10.00				
	Upper Floor	02 Nos	02 Nos.	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases						
	Upper Floor	Existing	.90 M & .89 M	MR old			
	Basement			accepted			
	c. Protection of exits	N/A	N/A	N/A			
	Fire check door						
	Pressurization	N/A	N/A	N/A			
		N/A	N/A	N/A			
	e. No. of continuous staircases to	1 nos.	1 Nos.	MR			
	terrace	.90 M	.90 M	MR			
	g. Width of Corridor	.90 M	.90 M	MR			
3	h. Door Size			TE FLORE			
3	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
	Fire failing of shall door	IV/A					
	- Motor curtain	NI/A	NI/A	NI/A			
	Water curtain	N/A	N/A	N/A			
4	Fire Dampers	N/A N/A	N/A N/A	N/A N/A			
4	Fire Dampers Smoke Management System.	N/A	N/A	N/A			
4	Fire Dampers Smoke Management System. Basement						
4	Fire Dampers Smoke Management System.	N/A	N/A	N/A			
5.	Fire Dampers Smoke Management System. Basement	N/A	N/A	N/A N/A			
	 Fire Dampers Smoke Management System. Basement Upper floor 	N/A	N/A	N/A N/A			
	 Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers 	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A			
	 Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers 	N/A N/A N/A Oß Nos.	N/A N/A N/A 0-6 Nos.	N/A N/A N/A			
5.	 Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers Types 	N/A N/A N/A OS Nos. ABC & Co2	N/A N/A N/A 0-6 Nos. ABC & Co2	N/A N/A N/A MR MR			
	 Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers Types IS marking First-aid-Hose Reels. 	N/A N/A N/A OS Nos. ABC & Co2 ISI marked	N/A N/A N/A O-6Nos. ABC & Co2 ISI marked	N/A N/A N/A MR MR			
5.	 Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers Types IS marking 	N/A N/A N/A OS Nos. ABC & Co2	N/A N/A N/A 0-6 Nos. ABC & Co2	N/A N/A N/A MR MR			

Automatic fire detection and alarming syste			
Type of detectors	N/A	N/A	N/A
Location of main panel	N/A	N/A	N/A
Location of repeater panel	N/A	N/A	N/A
Alternate source of power	N/A	N/A	N/A
Hooter's location	N/A	N/A	N/A
MOEFA	N/A	N/A	N/A
Public address System.	N/A	N/A	N/A
Automatic Sprinkler System.			
Basement	N/A	N/A	N/A
upper floor	N/A	N/A	N/A
sprinkler above false ceiling	N/A	N/A	N/A
Internal Hydrants			
size of riser/down-comer	100 MM	100 MM	MR
 Number of hydrants per floor 	1 No.	1 No.	MR
Hose Box	1 No.	1 No.	MR
Yard Hydrants.	1		
Total number of hydrants	N/A	N/A	N/A
Hose Box	N/A	N/A	N/A
Pumping Arrangements.			
Ground Level	N/A	N/A	N/A
Discharge of main Pump	N/A	N/A	N/A
➢ Head of Main Pump	N/A	N/A	N/A
Number of main pumps	N/A	N/A	N/A
Jockey pump out put	N/A	N/A	N/A
> Jockey pump head	N/A	N/A	N/A
> Standby pump out put	N/A	N/A	N/A
Standby pump Head	N/A	N/A	N/A
> Auto Starting /Manual stopping	N/A	N/A	N/A
> Pump House Access	N/A	N/A	N/A
Terrace Level			14//
Discharge of pump	450 LPM	450 LPM	MR
➢ Head of the Pump	40 M	40 M	MR
> Power supply	Required	Provided	MR
> Auto Starting of pump	Required	Provided	MR
Captive Water Storage for Fire Fighting.	required	TTOVIGEG	IVIIX
Underground tank capacity	N/A	N/A	N/A
> Draw-off connection	N/A	N/A	N/A
Fire service inlet	N/A	N/A	N/A
> Access to tank	N/A	N/A	N/A
Overhead Tank capacity	5000 Ltrs.	10000 Ltrs.	MR
Exit Signage.	N/A		-
Provision of Lifts.	IN/A	N/A	N/A
Pressurization of Lift Shaft	N/A	N/A	N/A
Pressurization of Lift Shall Pressurization of Lift lobby	N/A	N/A N/A	N/A N/A
Communication in lift car	N/A N/A		-
		N/A	N/A
Standby power supply	Required	Provided	MR
Refuge Area.	N/A	N/A	N/A
Total area	N/A	N/A	N/A
Location Fire Control Booms	N/A	N/A	N/A
Fire Control Room	N/A	N/A	N/A
Detector system panel	N/A	N/A	N/A
Flow switch panel	N/A	N/A	N/A
PA system panel	N/A	N/A	N/A
- Dottom bookun	N/A	N/A	N/A
Battery backup	IN/A	I IV/A	IN/A

,	20	protection	e Protection sy of special Risk	s. if anv:	N/A	N/A	N/A	2
T fu	inctional	protection s	systems provided from the provided of the prov	ded in the bu				
	In	view of the	deemed comp	oliance of the i	minimum star	ndards of fire	prevention	and
fi	re safe	ty measure	s as required	under the	rules. The r	dor the circu	ular no 260	2-369
			2012/4217 dat ecommended.	ed 09/11/12	renewar un	der the choc	iiai 110.202	_ 002
						Cect		
						T	12/00/)
				Sign		Inspecting C		
	. /	•		Nam		. K. Yadav		
•	DOLE	<u>)</u> ,			_	DO (Laxmi N	lagar)	- 77
-	Sul	mettod	for cepps	ovel Dlu.				1
	344)iii) (lee-)	b. copi		1			
		1	,		Jun cy			
7	DYLFO	MDZ,			Jus ch	1511		
-	/	A.			, 4			
		5)	17					
		. //						
		8 F	-p - m.		FIM.	. 110		
		e e	/ M.	scell				
					Uz.			
0		77.6			6/12	7		
81	in, f	-Th	eller is	, put	if fe	n sign	alue	ks
						RIG	cct	
C	to/	NDZ)				12	112/201	12
			m-scell	157	12			
				P				

307/cfoMn 0/12/19/12