## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2018/01

Dated : 01.01.2018

## FIRE SAFETY CERTIFICATE

Certified that the KFC Restaurant located at A-12, Cannaught Place, New Delhi comprises of Basement, Ground + Mezzanine + 03 Upper floor, Restaurant is running at ground & mezzanine floor only was granted FSC by this department vide letter No.F6/DFS/MS/EH/2013/274 dated 08/05/13. The premises was re-inspected by the officer concerned of this department on 02/12/17 in the presence of Mr. Ayan (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D, Restaurant at Ground & Mezzanine floor only with effect from Object 14.—for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued \_\_\_\_\_\_\_at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, NDMC, Palika Kendre, New Delhi.

2. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

3. The Manager, KFC Restaurant, A-12, Cannaught Place, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

## **INSPECTION REPORT**

1. Name & address of the building KFC Restaurant, A-12, Cannaught Place, New

Delhi.

2. Type of occupancy:-Assembly Building Group-D

Basement, Gr. + Mezzanine + 03 Upper floors, Restaurant is running at Ground & Mezzanine floor

3. Type of case:-Renewal

4. Details of previous FSC:-F6/DFS/MS/EH/2013/274 dated

08/05/13

5. Fire safety directives No.-

N/A

6. Date of inspection:-

02/12/17

7. Name of the inspecting officer:-8. Name & designation of officer

Sh. Manoj Kumar Sharma (ADO/CC)

From the building side:-

Sh. Ayan (Manager) 2005

9. Year of construction:-

10. Applicant's letter No:-Nil dated 22/03/2017

S.No.	Minimum Standards C	D.		Old Cas
5.110.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety	Provided at site	Remarks MR/NMR
1.	Access to Building	arrangements		
	1) Road width	Accessible	06 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3) Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Ar		Exits	IN/A
	A. Number of staircases			
	1. Upper floors	02	02	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			1071
	1. Upper floors	1.25 mtr.	0.80 mtr. & 1.25 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01	01	01
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	N/A	N/A	N/A
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
	Smoke Management System			
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 a/c per hour	Exhaust fan	MR
	Fire Extinguishers			

	1) Total numbers	05 Nos.	05 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	<b>Automatic Fire Detection &amp;</b>				
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
-	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	N/A	N/A	N/A	
10.	<b>Automatic Sprinkler System</b>				
	1) Basement	N/A	N/A	N/A	
	2) Upper floors (Mezzanine floor)	Required	Provided	MR	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling				
11.	Internal Hydrants	*			
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	N/A	
	floor				
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement		a		
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main pump	N/A	N/A	N/A	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual stopping	N/A	N/A	N/A	
	2) Terrace level				
	a) Discharge of pump	450 LPM &	450 LPM & 180	MR	
	a) Disting of pump	180 LPM	LPM	IVIIC	
		40 mtr.	40 mtr.	MR	
	b) Head of pump	40 mir.		ATAAN	
				MR	
	c) Power supply	Required	Provided	MR MR	
14.	c) Power supply d) Auto starting of pump	Required Required		MR MR	
14.	c) Power supply	Required Required	Provided		



	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
101	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	stem for Prote	ction of special	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/EH/2016/593 dated 04/03/2016

have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2013/274 dated 08/05/2013 renewal under rule 35 of the Delhi Fire Service

rules 2010, is recommended.

Signature of the Inspecting Officer

Messen Name :- M.K. Sharma Designation :- ADO (CC)

7/12/28/12