GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001**

No. F6/DFS/MS/GH/SZ/2017/ 17 4 4

Dated: 06/12/17

FIRE SAFETY CERTIFICATE

Certified that the Guest House Apra International, 15A/57, W.E.A, Karol Bagh, New Delhi-110005 comprised of basement, ground floor plus four upper floors, using basement as hall/storage, ground floor as reception, office and 04 guest rooms, first floor, second floor & third floor each having 08 guest rooms respectively, fourth floor having three rooms for staff with pantry (total 28 guest rooms), was granted FSC by this department vide letter F.6/DFS/MS/GH/2014/SZ/368 dated 31.03.2014. The premises was re-inspected by the officer concerned of this department on 27/11/2017 in presence of Sh. S.L. Chouhan, Manager and found that the owner/occupier have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class residential (guest house) with effect from _____________________ for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued <u>o 6 /12/17</u> at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

9 c they 1. Sh. Kamal Kishore Arora (Owner), Guest House Apra International, 15A/57, W.E.A, Karol Bagh, New Delhi-110005.

2. The Addl. C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : M/s Apra International, 15A/57, W.E.A, Karol Bagh, New

Delhi-110005

: Lodging House Type of Occupancy

3. Type of Case : Renewal

: F.6/DFS/MS/GH/2014/SZ/368 dated 31.03.2014 4. Details of previous NOC

5. Fire Safety directives letter No : N/A

: 27-11-2017 6. Date of inspection

7. Name of the Inspecting Officers: M.K. Chattopadhyay, Divisional Officer (South West)

8. Name and designation of officers

Upper floors

: Sh. S.L. Chouhan (Manager) from the building side

: 2000 9. Year of Construction

: Nil dated Nil 10 Applicant's letter No.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per letter No31.03.2014	Provided at site	Remarks MR/NMR		
1	Access to building			,		
	Road width	06 mts	Provided	MR		
	Gate width	05 mts	Directly accessible	MR		
	• Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-	· -	-		
	• Upper Floors	01	Provided(01)	MR being old case		
	Basements	01	Provided(01)	MR being old case		
	b. Width of staircases	_	-	-		
	• Upper Floors	old case	1.19 mts.	MR being old case		
	Basements	old case	1.19 mts.	MR being old case		
	c. Protection of exits	-	- N	-		
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace		01	MR		
	g. Width of Corridor	1.25 mts	1.48 mts	MR		
	h. Door Size	Old case	Provided (0.87 mt.)	MR being old case		
3	Compartmentation.		•			
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.	-				
	Basements	30 a/c per hour				
	Unper floors	12 a/c per hour	Natural ventilation	n MR		

	Total numbers	22	Provided	MR		
	• Types	CO ₂ , ABC type	Provided	MR		
3	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.			1		
	Total numbers on each floor	01	Provided	MR		
	• Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	• Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.			0		
	Basement		Provided	Area of basement is less than 200 mt ²		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants			50%		
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.		1,11	17/11		
12	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.	IV/A	IN/A	IVA		
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	➤ Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	➤ Jockey Pump out put	N/A	N/A	N/A		
	➤ Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
i i i	Standby Pump Head	N/A	N/A	N/A		
	Auto Starting/ Manual stopping	N/A	N/A	N/A		
254	Pump House Access	N/A	N/A	N/A		
1919	Terrace level	304-F				

100	> Discharge of pump	450 LPM	Provided	MR			
	➤ Head of the pump	30 mts	Provided	MR			
	> Power Supply	Required	Provided	MR			
	➤ Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for fire fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	5,000 lts	Provided	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	> Total Area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room	1	T				
	Detector System Panel	N/A	N/A	N/A			
SE SER	Flow Switch Panel	N/A	N/A	N/A			
anla	PA System Panel	N/A	N/A	N/A			
ate IV.S.	Batter backup	Required	Provided	MR			
er Fire	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR			

The fire protection systems provided in the building were checked and found functional at the time of inspection. The shortcomings issued vide letter no. F.6/DFS/MS/GH/SZ/2017/1441 dated 02.06.17 has been complied.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/GH/2014/SZ/368 dated 31.03.2014, renewal under rule 37 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

875/20/2W 28/11/20/7

Land

M.K. CHATTOPADHYAY
Divisional Officer (South West)