## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110001

No. F6/DFS/MS/NDZ/2018/ (MOT) 56

Dated: 08/01/18

## FIRE SAFETY CERTIFICATE

Colony, Delhi, comprised of ground plus one upper floor owned/occupied by Royal Banquet Hall, have complied with the fire prevention and fire safety requirement in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 21/12/2017 in the presence of Sh. Dheeraj Bindra and found that the **Assembly building** is fit for occupancy class "D" 'Assembly (Banquet Hall)' with effect from ... Sh. ... for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on.....at New Delhi by

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

## Copy to:-

 The Dy. Health Officer, East Delhi Municipal Corporation, Health Department, Shahdara (South) Zone, Karkardooma, Shahdara, Delhi.

2. St. Ohcesa, Bindrer, fogal Baronet mall, 162/22, Theol Churring Geeta Colons, Polis.

## **INSPECTION REPORT**

1. Name & address of the building : Royal Banquet Hall at 162/22, Jheel Khuranja, Pelli.

2. Building is comprised of : Ground plus one upper floor

3. Type of Occupancy : Assembly (Banquet Hall)

4. Type of Case : Renewal

5. Details of Previous FSC : F6/DFS/MS/BNQT/2014/NDZ/1377 Dated 07/11/14.

6. Fire Safety direction letter No : NBC Part IV
7. Date of Inspection : 21/12/17
8. Name of the Inspecting Officers : DO. F. Brown

9. Name of the designation of Officer

from the building side : Sh.Dheeraj Bindra

10. Year of Construction : 1991

	oplicant's letter No : Nil Dated 2						
S.No	Minimum Standards on fire prevention	Requirement	Provided at	Remarks			
and the second	and fire safety U/R 33	Directive	Site	MR/NMF			
1	Access to building						
	Road width	6 m	30 m	MR			
	Gate width	N/A	N/A	N/A			
	Width of internal road	N/A	I/A N/A				
2	Number, Width, Type and Arrangement of Exits.						
	a. Number of Staircases		*				
	Upper Floor	02 Nos.	02 Nos.	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases			-			
	Upper Floor	1.5 m	1.5 m	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to terrace	2 nos.	2 nos.	MR			
	g. Width of Corridor	N/A	N/A	N/A			
	h. Door Size	2.0 m	2.0 m	MR			
3	Compartmentation.						
-	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A 🧋	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basement	N/A	N/A	N/A			
CANCEL COMPANY	Upper floor	Required	Ventilated	HEAMIR			
5.	Fire Extinguisher						
	Total numbers	06 no.	08 no.	MR			
	types	Co2 & ABC	Co2 & ABC	MR			
	IS marking	ISI marked	ISI marked	MR			

5	First-aid-Hose Reels.  Total numbers of each floor	s 1r	nos.	1 nos.	MR	
	Length of hose reel hose		) m	30 m	MR	
	Nozzle diameter	2	mm	5 mm	MR	
	Automatic fire detection and alarming system.					
7	0.00			N/A	N/A	
	Type of detectors  Location of main panel	N/A		N/A	N/A	
	Location of repeater panel	N/A		N/A	N/A	
	Alternate source of power	N/A		N/A	N/A	
	Hooters	N/A		N/A	N/A	
		1.50	quired	Provided	MR	
8	MOEFA	N/		N/A	N/A	
9	Public address System.	14/71				
10	Automatic Sprinkler System		/A	N/A	N/A	
	Basement		-	N/A	N/A	
	Upper floor		/A	N/A	N/A	
	sprinkler above false ceilin	g N	/A	IV/A	14/74	
11	Internal Hydrants	1	00	100 mm	MR	
	size of riser/down-comer		00 mm	01 nos.	MR	
•	Number of hydrants each	0	1 nos.	OT HOS.		
	floor			01 nos.	MR	
	TIOSC DOX COOK INC.		1 nos.	011103.	10111	
12	Yard Hydrants.		NI / A	N/A	N/A	
	Total number of hydrants		N/A	N/A	N/A	
	7,000		N/A	IN/A	14/74	
13	Pumping Arrangements.			NI/A	N/A	
	<ul> <li>Ground Level</li> </ul>		N/A	N/A	N/A	
	Discharge of mair		N/A	N/A	N/A	
	Head of Main Pur		N/A	N/A	N/A	
	> Number of main		N/A N/A	N/A	N/A	
				N/A	N/A	
	Jockey pump hea		N/A	N/A	N/A	
	> Standby pump ou		N/A	N/A		
	> Standby pump Ho		N/A	N/A	N/A N/A	
	> Auto Starting /M	alludi	N/A	N/A	IN/A	
	stopping	000	N/A	N/A	N/A	
	<ul><li>Pump House Acc</li><li>Terrace Level</li></ul>	C22				
	Terrace Level     Discharge of pun	าท	450 LPM	450 LPM	MR	
	> Head of the Pum		40 m	40 m	MR	
	> Power supply	۲	Required	Provided	MR	
	> Auto Starting of	numn	Required	Auto	MR	

14	Captive Water Storage for Fire Fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	10,000 ltrs.	10,000 ltrs.	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	Total area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector system panel	N/A	N/A	N/A N/A			
	Flow switch panel	N/A	N/A N/A				
	PA system panel	N/A	N/A	N/A			
	Batter backup	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			

The Fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping In view of deemed compliance of the minimum standards of Fire prevention and Fire Safety measured as required under the rules. The Fire Safety issued vide latter no. F6/DFS/MS/BNQT/2014/NDZ/1377 Dated Certificate 07/11/14.

The Fire safety certificate renewed under rule 37, of the Delhi Fire Service Rules 2010 is recommended. 27/12/13

Signature of the Inspecting Officer

Name

: F. BROWN

Designation

: DO

Dy. CFO (NDZ)

A 1/19 1/18

CF. P. m. Scott 1/19