GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2018/122

Dated: 22/01/12

FIRE SAFETY CERTIFICATE

Certified that the St. Eknath Sarvodaya Kanya Vidyalaya located at J & K-Block, Delhi-110095, comprised of ground plus three upper floors (New Building, One Block only), owned/occupied by St. Eknath Sarvodaya Kanya Vidyalaya was inspected by the officer concerned of this department on 12/01/18 in the presence of Mr. Ashwani, Contractor and found that the school building have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the school building is fit for occupancy class "B" 'Educational Building' with effect from the school building is fit for occupancy class "B" 'Educational Building' with effect from the school building is fit for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

This Fire Safety Certificate does not cover the old building blocks for which shortcomings were issued vide letter No. F6/DFS/MS/School/2017/157 dated 18/01/17.

Issued on 22 01/12 at New Delhi by

(Vipin Kental) Chief Fire Officer

BL

To,

The Assistant Engineer (E) PWD Edu. M1 Sub Div. IV, ITI Campus Pusa New Delhi 110012

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

1. Name & address of the building : St. Eknath Sarvodaya Kanya Vidya laya

J&K Block, Dilshad Garden, Delhi-110095

2. Building is comprised of : G+3 (New Building, one block only)

3. Type of Occupancy : Educational

4. Type of Case : New5. Details of Previous NOC letter : Nil

6. Fire Safety directive letter No. : NBC part IV

7. Date of Inspection : 12/01/2018

8. Name of the Inspecting officers : ADO Vijay Bahdur

9. Name and designation of Officer

from the building side : Mr. Ashwani, Contractor

10. Year of Construction : 2017

11. Applicant's letter No :Letter No.AE-IV/2017-18/54 dated 21/07/17

Sr.	Minimum Standards on Fire	BBL/NBC	Provided at Site	Remarks				
No.	Prevention and Fire Safety U/R33	Requirement		MR/NMF				
01	Access to Building							
	Road width	06 mtr.	18 mtr.	MR				
	Gate width	4.50 mtr	4.50 mtr	MR				
	Width of internal road	N/A	N/A	N/A				
02	Number, Width, Type and Arrangement of Exits							
	a. Number of Staircases							
	Upper floor	02 nos.	03 nos.	MR				
	Basement	N/A	N/A	N/A				
	B. Width of Staircases							
	Upper floor	1.50 mtr	1.66 mtr, 1.72 mtr & 1.85 mtr	MR				
	Basement	N/A	N/A	N/A				
	c. Protection of Exits							
	Fire check door	N/A	N/A	N/A				
	 Pressurization 	N/A	N/A	N/A				
	d. No. of Continuous Staircases to Terrace	01 nos.	03 nos.	MR				
	e. Width of Corridor	1.50 mtr.	1.71 mtr.	MR				
	f. Door Size	01 mtr.	1.12 mtr.	MR				
03	Compartmentation.							
	Fire check door	N/A	N/A	N/A				
and the same of th	 Sealing of electrical shafts 	N/A	N/A	N/A				
	 Fire rating of shaft door 	N/A	N/A	N/A				
	Water curtain	N/A	N/A	N/A				
	Fire dampers	N/A	N/A	N/A				
)4	Smoke Management System.							
	Basement	N/A	N/A	N/A				
	Upper floor	N/A	N/A	N/A				
5.	Fire Extinguishers							
	Total numbers	08 nos.	10 nos	MR				
	• Types	ABC /CO ₂	ABC & CO ₂	MR				
	IS marking	ISI marked	Provided	MR				

	Total numbers on each floor	02 nos.	02 nos	MR				
	Length of hose reel hose	30 mtr	30 mtrs	MR				
	Nozzle diameter	05 mm	05 mm	MR				
07	Automatic Fire Detection and Alarming System.							
-	Type of detectors	N/A	N/A	N/A				
	 Location of main panel 	N/A	N/A	N/A				
	 Location of repeater panel 	N/A	N/A	N/A				
	Alternate source of power	N/A	N/A	N/A				
	Hooter	N/A	N/A	N/A				
80	MOEFA	N/A	N/A	N/A				
09	Public Address System.	N/A	N/A	N/A				
10	Automatic Sprinkler System.							
	Basement	N/A	N/A	N/A				
	upper floor	N/A	N/A	N/A				
	sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants	14/7	14//	IN//				
	size of riser/down-comer	N/A	N/A	N/A				
	Number of hydrants per floor	N/A	N/A	N/A				
	Hose box	N/A	N/A	N/A				
12	Yard Hydrants.		,	14// \				
	Total number of hydrants	N/A	N/A	N/A				
	Hose box	N/A	N/A	N/A				
13	Pumping Arrangements.	1000	1,777	14//1				
	> Ground Level							
50	Discharge of main pump	N/A	N/A	N/A				
	Head of main pump	N/A	N/A	N/A				
	Number of main pumps	N/A	N/A	N/A				
	Jockey pump out put	N/A	N/A	N/A				
	 Jockey pump head 	N/A	N/A	N/A				
	Standby pump out put	N/A	N/A	N/A				
	Standby pump head	N/A	N/A	N/A				
	Auto starting /manual stopping	N/A	N/A	N/A				
	Pump house access	N/A	N/A	N/A				
	> Terrace Level		No. of the last of					
	Discharge of pump	450 lpm	450 lpm x 2	MR				
	Head of the pump	40 M	40 M	MR				
	Power supply	Required	Provided	MR				
	Auto starting of pump	Required	Provided	MR				
4	Captive Water Storage for Fire Fighting.	H. SHEYE						
	Underground tank capacity	N/A	N/A	N/A				
	Draw-off connection	N/A	N/A	N/A				
1	Fire service inlet	N/A	N/A	N/A				
-	Access to tank	N/A	N/A	N/A				
	Overhead tank capacity	10,000 ltr	10,000 ltr	MR				
15	Exit Signage.	Required	Provided	MR				
10	EXIL Signage.	Required	Provided	MR				

16	Provision of Lifts.						
	Pressurization of lift shaftPressurization of lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	N/A			
	Lift signage	N/A	N/A	N/A			
47		N/A	N/A	N/A			
17	Standby Power Supply	N/A	N/A	N/A			
18	Refuge Area.						
	Total area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector system panel	N/A	N/A	N/A			
	Flow switch panel	N/A	N/A	N/A			
	PA system panel	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
	Building floor plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of Special Risks, if Any:	N/A	N/A	N/A			

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rule, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Name

:- Vijay Bahadur

Designation :- A.D.O (T.Pur)

DOFEDT Submitted for ceptors film

CFC M. SCELL WE 16/1 Sir, fT letter is put up for signature Please

348/CP NIX