GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2018/ 124

Dated: 22/01/12

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya located at DDA Flats of Loni Road, Shahdara, Delhi-110093, comprised of ground plus three floors (New Buildings only), owned/occupied by Sarvodaya Kanya Vidyalaya was inspected by the officer concerned of this department on 03/01/2018 in the presence of Mr. Sunil Kumar Gupta, Civil Contractor and found that the school building have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the school building is fit for occupancy class "B" 'Educational Building' with effect from [and the condition of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

This Fire Safety Certificate does not cover the old building blocks for which shortcomings were issued vide letter No. F6/DFS/MS/School/2015/736 dated 16/04/15.

Issued on 22 11 10 at New Delhi by

(Vipin Kental)
Chief Fire Officer

ole for

To,

The Assistant Engineer (E) PWD Edu. M1 Sub Div. IV, ITI Campus Pusa New Delhi 110012

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

ADO/18

Name & address of the building

: Savodaya Kanyar Vidyalaya

DDA Flats of Loni Raod, Shahdara, Delhi-110093

2. Building is comprised of

: G+ 3 (two separate blocks) New Buildings

3. Type of Occupancy

: Educational

: New

4. Type of Case

5. Details of Previous NOC letter 6. Fire Safety directive letter No.

: Nil

: NBC part IV

7. Date of Inspection

8. Name of the Inspecting officers

: 03/01/18

9. Name and designation of Officer

: ADO V. B. Yadav

from the building side

: Mr. Sunil Kumar Gupta (Civil. Contractor) : 2017

10. Year of Construction 11. Applicant's letter No

:Letter No.AE-IV/2017-18/76 dated 16/11/2017

Sr. No.	Minimum Standards on Fire Prevention and Fire Safety U/R33	NBC Requirement	Provided at Site	Remarks			
01	Access to Building MR/NMR						
	Road width	06 mtr.	06 mtr.	MR			
	Gate width	4.50 mtr	4.50 mtr	MR			
	Width of internal road			N/A			
02	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper floor	(2+1) nos.	(3+2) nos.	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases						
	Upper floor	1.50 mtr	1.60 mtr to 1.82 mtr.	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of Exits						
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	d. No. of Continuous Staircases	01 nos.	01 nos.	MA			
	to Terrace	in each block	in each block	, a 1 10 10 10 10 10 10 10 10 10 10 10 10 1			
	e. Width of Corridor	1.50 mtr.	1.70 mtr.	MR			
		in each block	in each block				
	f. Door Size	01 mtr.	1.10 mtr.	MR			
03	Compartmentation.						
1	Fire check door	N/A	N/A	N/A			
	 Sealing of electrical shafts 	N/A	N/A	N/A			
	 Fire rating of shaft door 	N/A	N/A	N/A			
1	Water curtain	N/A	N/A	N/A			
	Fire dampers	N/A	N/A	N/A			
)4	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
)5.	Fire Extinguishers						
	Total numbers	20 nos.	22 nos.	MR			
	Types	ABC /CO ₂	ABC & CO ₂	MR			
	IS marking	ISI marked	Provided	MR			

06	First-Aid-Hose Reels		A HATTER						
	Total numbers on each floor	02 nos. (01 in each block)	02 nos (01 in each block)	MR					
	 Length of hose reel hose 	30 mtr	30 mtrs	MR					
	Nozzle diameter	05 mm	05 mm	. MR					
07	Automatic Fire Detection and Alarming System.								
	Type of detectors	N/A	N/A	N/A					
	Location of main panel	N/A	N/A	N/A					
	Location of repeater panel	N/A	N/A	N/A					
	Alternate source of power,	N/A	N/A	N/A					
	Hooter	N/A	N/A	N/A					
08	MOEFA	N/A	N/A	N/A					
09	Public Address System.	N/A	N/A	N/A					
10	Automatic Sprinkler System.								
	Basement	N/A	N/A	N/A					
	upper floor	N/A	N/A	N/A					
	 sprinkler above false ceiling 	N/A	N/A	N/A					
11	Internal Hydrants								
	size of riser/down-comer	N/A	N/A	N/A					
	Number of hydrants per floor	N/A	N/A	N/A					
•	Hose box	N/A	N/A	N/A					
12	Yard Hydrants.								
	Total number of hydrants	N/A	N/A	N/A					
	Hose box	N/A	N/A	N/A					
13	Pumping Arrangements.	7 -							
	➢ Ground Level								
		NI/A	NI/A	N/A					
	Discharge of main pump	N/A N/A	N/A N/A	N/A N/A					
	Head of main pump	N/A	N/A	N/A					
	Number of main pumps	N/A	N/A	N/A					
	Jockey pump out put	N/A	N/A	N/A					
	Jockey pump head Standburger automateur	N/A	N/A	N/A					
	Standby pump out put Standby pump bood	N/A	N/A	N/A					
	Standby pump head Auto starting /manual stanning	N/A	N/A	N/A					
	Auto starting /manual stopping Pump house access	N/A	N/A	N/A					
	Pump house accessTerrace Level								
	Discharge of pump in each Block	450 lpm	450 lpm X 2	MR					
		40 M	450 Ipili X 2	MR					
	Head of the pumpPower supply	Required	Provided	MR					
	Auto starting of pump	Required	Provided	MR					
14									
14	Captive Water Storage for Fire Fighting.	N/A	N/A	N/A					
	Underground tank capacity	N/A N/A	N/A	N/A N/A					
	Draw-off connection	N/A N/A	N/A N/A	N/A N/A					
	Fire service inlet	N/A N/A	N/A N/A	N/A N/A					
	Access to tank Access to tank	10,000 ltr	10,000 ltr						
100 at 10	 Overhead tank capacity 	in each block	in each block	MR					
15	Exit Signage.	Required	Provided	MR					

16	Provision of Lifts.						
	Pressurization of lift shaft	N/A	N/A	N/A			
	Pressurization of lift lobbyCommunication in lift car	N/A	N/A	N/A			
		N/A	N/A	N/A			
	 Firemen's grounding switch 	N/A	N/A	N/A			
	 Lift signage 	N/A	N/A	N/A			
17	Standby Power Supply	N/A	N/A	N/A			
18	Refuge Area.						
	Total area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector system panel	N/A	N/A	N/A			
	Flow switch panel	N/A	N/A	N/A			
	PA system panel	N/A	N/A	N/A			
* 1	Battery backup	N/A	N/A	N/A			
	Building floor plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of Special Risks, if Any:	N/A	N/A	N/A			

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under NBC Part IV, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Name

:- Vijay Bahadur

Designation :- A.D.O (T.Pur)

DOVED Submitted for approved film.

EFO - FTM.

M. SCOU 16/1

Six, FT letter in Party for Signatus Please.

CPO/HIG Miscell Meg.