FORM 'H'
FORM FOR ISSUING FIRE SAFETY CERTIFICATE
[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/2018/ www 140

Dated: 21/0) /2018

FIRE SAFETY CERTIFICATE

(Atul Garg) Chief Fire Officer, Delhi Fire Service.

Copy to:

Sh. Sunil Jain

Aggarwal City Mall, Plot No – 05, Road No-44, Pitampura, Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. All the doors, Exits and internal roads must be kept free from any obstruction.
- 9. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry

INSPECTION REPORT

1. Name & address of the building: Aggarwal City Mall, Located at Plot No - 05,

Road No-44, Pitampura, Delhi – 110034

2. Type of Occupancy

: Mercantile(B + G + Three Upper Floors)

3. Type of Case

: Renewal

4. Details of previous NOC : Letter No. F6/DFS/MS/2014/WZ/58 dated 15-01-2014

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/2005/1527 dated19-07-2005

6. Date of inspection

: 04-01-2018

7. Name of the Inspecting Officer: DO/W & ADO (WP)

8. Name and designation of Officer

from the building side

: Ms. Sunil Jain

9. Year of Construction

: 2005-2006

10. Applicant's letter No.: NDPPL/DIR/AMP5/DFS/2K17/0589 Dated-11/12/17

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements		Provided at site		marks R/NMR
1.	Access of building			1 - 1 - 1 - 1 - 1 - 1	NAT)
1.	• Road width 2	24 m 6 m As per sanction plan		24mtr Provided	MI	
	Gate width 6			Provided	MI	
	Width of internal road			Provided	MR	
2.	Number, width, Type & Arrange	ements of e	exits			
۷.	a. Number of staircases				3.6	D
	Upper floors	2		2 Provided	M	
	Basements	2+1 Rai	mp	Provided	M	K
	b. Width of staircases					MR
Contraction	Upper floors	1.5m	1.5m & 1		-	MR(Old
	Basements	1.5m	Varies fro 1to 0.8m	om 1.35 to 1.85m & & 1.8m	1	Case)
	c. Protection of exits					
	• Fire check door	Require	ed	Provided		MR
	Pressurization	Not Re		Not Provided		MR
	d. No of continuous staircase to terrace	Requir	A	Provided		MR
	TYT' 1/1 Of Comidon	1.5m		Hall (Old case)		MR
	f. Door Size	1.m	**	Provided		MR
		1.111				
3.	Compartmentation • Fire check door	Requir	red	Provided		MR
	 Sealing of electrical 	Requir		Provided	VI.	MR
	shaftsFire Rating of shaft doo	or Requi	red	Provided		MR
	Water Curtain	NR		NR		NR
	• Fire Dampers	Requi	red	Provided		MR
		Kequi	i cu			
4.	4. Smoke managements System		per hrs	Functional		MR
	BasementsUpper floors		per hour	Provided (Not		MR

	E' A'III D I					
6.	First – Aid Hose Reels	12		2 P '1 '		
	 Total numbers on each floor 	2	- P-,	2 Provided	MR	
	Length of hose reel hoseNozzle diameter	30 m		Provided	MR	
	1,02220 didirector	5 mm		Provided	MR	
7.	Automatic fire detection and alar	ming sy	stem			
	 Type of detectors 	Smol	ke & Heat	Provided	MR	
		Grou	nd Floor	Provided	MR	
	 Location of Main Panel 					
	 Location of Repeater Panel 	Requ	ired	Provided	MR	
	Alternate source of powerHooters' Location	Requ	ired	Provided	MR	
		At St Locat	rategic tion	Provided	MR	
8.	MOEFA	Requ		Provided	MR	
9.	Public Address System	Requ		Provided	MR	
10.	Automatic Sprinkler System			J. C. Carrier		
	Basements	Requ	uired	Provided	MR	
	Upper Floor	Requ		Provided	MR	
	Sprinkler above false ceiling	Requ	ired	Provided	MR	
11.	Internal Hydrants					
	Size of riser/down- comer	r 150	mm	Provided	MR	
	Number of hydrants per floor	2		2 Provided	MR	
	Hose Box	2 R	equired	2 Provided	MR	
12.	Yard Hydrants			-		
	Total number of hydrantsHose Box	Requi	ired	4 Provided	MR	
	THOSE BOX	Requi	ired	4 Provided	MR	
13.						
	Ground Level				Un	
	Discharge of main pump	978	lpm	2280 lpm	MR \	
	➤ Head of main pump	200	60 m	60 m	MR	
	Number of main pumps		01	01	MR	
	Jockey pump out put		180 lpm	180 lpm	MR	
	Jockey pump head		60 m	60 m	MR	
_	Standby Pump out put		2280 lpm	2280 lpm	MR	
	Standby Pump Head		60 m	60 m	MR	
	Auto Staring/Manual stop	ping	Required	Provided	MR	
	Pump House Access		Required	Provided	MR	
	• Terrace level					
	Discharge of pump		NA	NA ·	NA	
	Head of the pumpPower supply		NA	NA	NA	
	Auto starting of pump		NA	NA NA	NA NA	
	7 Truto starting of pullip		NA	NA	NA NA	
14.	Captive water Storage for fire fig	hting	-	2 2	1	
	Under ground tank capacity		000 litres	Provided	MR	
27	Draw of connection	Requi	red	Provided	MR	
	Fire service inlet	Requi		Provided	MR	
	Access to tank	Requi		Provided	MR	
	Overhead Tank capacity	1	00 litres	Provided	MR	
15	Fyit Signag	Requi	red	Provided	MD	

16.	Diff Rull II	m Ground to 3rd I	Floor)	
NAME OF TAXABLE PARTY.	Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of lift lobby	NA	NA	NA
See The State of t	Communication in liftCar	Required	Provided	MR
MACHINESINGS	Fireman's Grounding	Required	Provided	MR
A CONTRACTOR OF THE PARTY OF TH	Switch > Lift Signage	Required	Provided	MR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area		Trovided	IVIK
COLUMN TO SERVICE	Total areaLocation	NR	NR	NR
19.	Fire control room	NR	NR	NR
-				
DOCUMENTS.	Detector system panel	NA	NA	NA
0	Flow Switch Panel	. NA	NA	NA
detraction	PA System Panel	NA	NA	NA
TOTAL DESCRIPTION	Battery backup	NA	NA	NA
	➤ Building Floor Plans	NA	NA	NA
0.	Special Fire Protection Systems for Protection of special Risks,	Manually operated CO2	Provided	MR
	if any;	system		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide Letter No. F6/DFS/MS/2014/WZ/58 dated 15-01-2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

2010 is recommended.	
Signature of the Inspecting Officer	Signature of the Inspecting Officer
Name Volcu Vir Singh Designation ADO/WP	Name 8h Muhesh Verm
	Designation Nolw
Tytho WZ) Speak	reg internal road et N.187
mentionel o	et N/87)
DOT HAD	N 81118