FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/EH/2018/183

Dated: 36 / 01 / 2018

FIRE SAFETY CERTIFICATE

Certified that the M/s Suravie Restaurant (Unit of Royal Hospitality) Located at 101, FF Plot no. C-4,C-5,C-6, Aggarwal Cyber Plaza Tower -1, Netaji Subhash Palace, Pitampura, Delhi was issued FSC vide Letter No. F6/DFS/MS/EH/2014/WZ/1378 dated 10/11/2014. The premises was re inspected by the officers of this department on 20-12-2017 in the presence of Mr. Sachin (Manager) found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D with effect from 30-01-2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 30.01.2018 at New Delhi by.

Chief Fire Officer, Delhi Fire Service.

Copy to:

- 1. Deputy Health Officer West Zone, Vishal Enclave, New Delhi
- 2. The (Manager) M/s Suravie Restaurant (Unit of Royal Hospitality) Located at 101, FF Plot no. C-4,C-5,C-6, Aggarwal Cyber Plaza Tower -1, Netaji Subhash Palace, Pitampura, Delhi

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSI ECTION RELOKT

1. Name & address of the building: M/s Suravie Restaurant (Unit of Royal Hospitality) 101, FF Plot no. C-4,C-5,C-6, Aggarwal Cyber Plaza Tower -1, Netaji Subhash Palace, Pitampura, Delhi

2. Type of Occupancy

: Assembly

3. Type of Case

: Renewal

4. Details of previous NOC: F6/DFS/MS/2014/EH/WZ/1378 dated 10-11-2014

5. Fire Safety directives Letter No.: FSC Issued to the building

6. Date of inspection

: 20-12-2017

7. Name of the Inspecting Officer: DO/W & ADO (WP)

8. Name and designation of Officer

from the building side

: Mr. Sachin

9. Year of Construction

: 2007,08

10. Applicant's letter No.

: nil dated -27.11.2017

9	10. Applicant's letter No.	. IIII dated	2/111201/			
S No	TVIIIIIII DUNIA	BBL Requirements	Provided at site	Remarks MR/NMR		
1.	Access of building					
		9 m	22.4mProvided	MR		
2	Gate width	6 m	Provided	MR		
	Width of internal road	6 m	Provided	MR		
2.						
	a. Number of staircases					
	 Upper floors 	2	2 Provided	MR		
	 Basements 	2	2 Provided	MR		
	b. Width of staircases		1	3.00		
	 Upper floors 	1.5 m	225cm & 229cm	MR		
		NR for	NR for	NR for		
	 Basements 	Restaurant	Restaurant	Restaurant		
	c. Protection of exits					
	 Fire check door 	NA	NA	NA		
	 Pressurization 	NA	NA	NA		
	d. No of continuous staircase to terrace	NA	NA	NA		
	e. Width Of Corridor	NA	NA	NA		
	f. Door Size	Old Case	175 cm & 140cm (Old Case)			
3.	Compartmentation		(Ora Case)			
	Fire check door	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	 Fire Rating of shaft door	NA	NA	NA		
13	Water Curtain	NA	NA	NA		
	• Fire Dampers	NA	NA	NA		
4.	Smoke managements System					
7.	Basements	30 a/c per	Exhaust Fans	MR		
	Upper floors	hour				
	opportions	12 a/c per	Provided	MR		
		hour				

5.	Fire Extinguishers	05 nos. DCP,	8 Provided	MR		
	Total numbers	CO2 &	Provided	MR		
	• Types	WCO2	Provided	MR		
	IS marking	ISI marked	Provided	IVIK		
	First – Aid Hose Reels					
	 Total numbers on each 	1	Provided	MR		
	floor	30 m	Provided	MR		
	 Length of hose reel hose 	5 mm	Provided	MR		
	 Nozzle diameter 					
	Automatic fire detection and alarming system					
	Type of detectors	Smoke & Heat	Provided	MR		
	 Location of Main Panel 	Required	Provided	MR		
	 Location of Repeater 	Required	Provided	MR		
	Panel		_	9		
	• Alternate source of	Required	Provided	MR		
	powerHooters' Location	Required	Provided	MR		
3.	MOEFA	Required	Provided	MR		
).	Public Address System	Required	Provided	MR		
0.	Automatic Sprinkler System	required	110 11000			
	Basements	Required	Provided	MR		
		Required	Provided	MR		
	Upper Floor Sprinkler above false	Required	Provided	MR		
	 Sprinkler above false ceiling 	required	1 To vided	1111		
11.	Internal Hydrants: common with	the mall				
L I.	Size of riser/down-	150 mm	Provided	MR		
	comer	01	Provided	MR		
	Number of hydrants per		110 vided	1.11		
	• Number of hydrants per floor	Required	Provided	MR		
	Hose Box	Tequitou				
12.	Yard Hydrants					
14.	Total number of	NA	NA	NA		
	hydrants	NA	NA	NA		
	Hose Box					
13.		on with the ma	11)			
IJ.	Pumping Arrangements: (Common with the mall) • Ground Level					
		NA	2850 LPM	NA		
	Discharge of main	NA	100 m	NA		
	pump Head of main pump	NA	02	NA		
	Number of main pumps	NA	180	NA		
	Jockey pump out put	NA	100m	NA		
	Jockey pump bead	NA NA	NA	NA		
	Standby Pump out put	NA NA	NA NA	NA NA		
	Standby Pump Head	NA NA	NA NA	NA NA		
	➤ Auto Staring/Manual	Required	Provided	MR		
	stopping	1.04.00				
	Pump House Access					
	Terrace level	450 lpm	Provided	MR		
	Discharge of pump	40 m	Provided	MR		
	> Head of the pump	Required	Provided	MR		
	> Power supply	Required	Provided	MR		
	> Auto starting of pump	Required	Tiovided	IVIIC		
	The second second second second	Lite Ballion				

14.	Captive water Storage for fire fighting: Common with the mall						
	 Under ground tank capacity 	100000 litres	Provided	MR			
	Draw off connection	Required	Provided	MR			
	> Fire service inlet	Required	Provided	MR			
	Access to tank	Required	Provided	MR			
	 Overhead Tank 	10,000 ltrs	Provided	MR			
	capacity		50000 ltrs				
15	Exit Signage	Required	Provided	MR			
16.	Provision of Lifts						
	Pressurization of Lift Shaft	NA	NA	NA			
	Pressurization of lift	NA	NA	NA			
	lobby	NA	NA	NA			
	Communication in liftCar	NA	NA	NA			
-	Fireman's GroundingSwitchLift Signage	NA	NA	NA			
17.	Standby power supply	Required	Provided	MR			
18.	Refuge Area						
10.	> Total area	NA	NA	NA			
	> Location	NA	NA	NA			
19.	Fire control room						
	Detector system panel	NA	NA	NA			
	> Flow Switch Panel	NA	NA	NA			
	> PA System Panel	NA	NA	NA			
	Battery backup	NA	NA	NA			
	Building Floor Plans	NA	NA	NA			
20.	Special Fire Protection	Co2 Flooding	Provided	MR			
	Systems for Protection of	for DG HT &					
1	special Risks, if any;	LT Pannel					

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide Letter No.: **F6/DMS/MS/2014/WZ/325, Dated- 10-03-2014** renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Uda Vir Lingh

Designation ADO WP

Name Sh Mohesh Verm

Designation ____/w

Pytho (W2)