FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/Metro/2018/ W2 170

Dated: 29/01/2018

FIRE SAFETY CERTIFICATE

Certified that the **ESI Hospital Metro Station (Elevated)** Located at **ESI Hospital,** Ring Road, New Delhi comprised of (Ground + Concourse + Platform) owned/occupied by DMRC, have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 08-01-2018 in the presence of **Mr Inderject Ajey (Assit. Construction Manager)** and found that the building / premises is fit for the occupancy class "Assembly" Group D Sub Division D–7 (**Except PD Area**) with effect from **AGATION** or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .39.1.1.13...... at New Delhi by.

Chief Fire Officer, Delhi Fire Service.

Copy to:

 Sh. V P Singh, DY. CEE/RC-1, DMRC, Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi – 110001.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used as per building bye laws 1983.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The proposal of PD Area, if any shall be referred to this department separately for approval and FSC.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1. Name & address of the building: ESI Hospital Metro Station (Elevated) Located at ESI Hospital Ring Road, New Delhi.

2. Type of Occupancy

: Assembly

3. Type of Case

: New (Ground + Concourse Level + Platform)

4. Details of previous NOC

: Nil

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/2013/248 dated-22-08-2013

6. Date of inspection

: 08-12-2017

7. Name of the Inspecting Officer: DO/W & ADO (WP)

8. Name and designation of Officer

from the building side :Sh Indeerjeet Ajey (Assit. Construction Manager)

Year of Construction

: 2017

9. Applicant's letter No.: DMRC/Elect/Cee/RC-1/CE-1/Lot-1/DFS/L7dated 5/12/17

	11	THE PEROOF C	boiled 17	CE-1/Lot-1/DFS/L/dated 5/1	2/1/		
S No	Minimum standards on fire prevention and fire safety U/R 33	NFPA/NBC Requirements		Provided at site		Remar ks MR/N MR	
1.	Access of building						
0	Road width			Provided		MR	
	Gate width			On main road		MR	
	 Width of internal road 			NA		NA	
2.	Number, width, Type & Arrangements of exits						
	a. Number of staircases			A			
	 Upper floors 			Provided		MR	
	• Basements			NA .	NA		
-	b. Width of staircases	1					
	• Upper floor	Required 2mtrs	C to F	C= 1x272,1x411cm PF=2x475cm,1x274cm,1x274cm uding Railing)		M R	
	Basements	NA NA NA NA NA NA NA Required 458cm					
	c. Protection of exits			***	NA		
	Fire check door			NA	N	٨	
	Pressurization					A	
	d. No of continuous				N		
	staircase to terrace			150000			
	e. Width Of Corridor			Provided		R	
	f. Door Size			Flovided	M	K	
3.	Compartmentation						
1000	Fire check door	Required Required NA NA		Provided		R	
Section 200	 Sealing of electrical shafts 			Not Provided		R	
				Provided		R	
	Water Curtain			NA		A	
	Fire Dampers			NA		A	
4.	Smoke managements System						
	Basements	NA		NA	N/	1	
	Upper floors	NA		NA	NA		
E	Pi P			*		-	

	•	Total numbers on each Platform	2			Provided		MR
	•	Length of hose reel hose	45m		-	Provided		MR
	•	Nozzle diameter		25mm Provided				MR
7.	Autor	matic fire detection and ala	fire detection and alarming system					
	•	Type of detectors	Smok		Pro	ovided	N	1R
	•	Location of Main	Requi	red	Pro	Provided		1R
		Panel	D .					
	•	Location of Repeater	Requi	red	Provided		M	IR.
		Panel	De surius 1		Dave	ovided		(1)
	•	Alternate source of power	Required		Pro	ovided	IV.	IR.
		Hooters' Location	Required		Pro	Provided		IR.
0	NOT		*					
8.	MOE		Required		_	rovided rovided		IR.
9.		Address System	Requi				M	IR.
10.		natic Sprinkler System (R Basements	NA	eu in Comm	NA		3.7	A
		77			NA		N	-
		Sprinkler above false	NA		NA		N	- 1
		ceiling	_ 14 &		1 42	> 7	114	1
11.	Intern	al Hydrants						
	•	Size of riser/down-	150m	ım	Pro	ovided	M	IR
		comer						
	•	Number of hydrants	2 on		Pro	vided	M	IR
		per floor	platform		-			and a second
	•	Hose Box	Required		Pro	vided	M	R
12.	Yard Hydrants							
,	•	Total number of hydrant	S	2	+	vided	M	2
13.	Dumni	Hose Box		Required	Pro	vided	M	R
13.	Pumping Arrangements Ground Level							
		 Discharge of main pump 		2850 lpm	Pro	vided	M	D
	>	Head of main pump				vided	M	
	>	Number of main pumps		70m	-	vided	M	
	>	Jockey pump out put		280 lpm	Pro	vided	M	
	>	Jockey pump head		70m	Pro	vided	M	R
	>	Standby Pump out put		2850lpm		vided	M	R
	A A	Standby Pump Head Auto Staring/Manual sto		70m		vided	M	
		Pump House Access	pping	Required	Fu	nctional	M	R
		Terrace level		Dagwinad	Duo	vided	1	7
	>	Discharge of pump		Required NA	NA NA	N. P. S.	M	
,	>	Head of the pump		NA	NA		N ₂	
	>	Power supply		NA	NA		NA NA	-
		Auto starting of pump		NA	NA		N/	_
14.	Captiv	ve water Storage for fire fig	ghting					
	•	Under ground tank capac	ity 100000 ltrs			rovided	M	R
	A	Draw of connection	Required		Provided		M	1
	A	Fire service inlet	Required		Provided		M	
¥/	>	Access to tank	Required			rovided	M	
15	Exit Si	Overhead Tank capacity	10,000 ltrs				M	
13	DAIL 2	ignage		Required	Pı	rovided	M	K
16.	Provis	ion of Lifts						
		Pressurization of Lift Sha	aft	NA	NA		N/	
		Pressurization of lift lobb	-	NA	NA		NA NA	
	>	Communication in lift Ca	ar	Required		vided	MI	

1							
18.	Refuge Area						
	> Total area	NA	NA		NA		
90000000	> Location	NA NA			NA		
19.	Fire control room						
	Detector system panel	Required NA Required Required		Provided	MR		
	> Flow Switch Panel			NA	NA		
	> PA System Panel			Provided	MR		
	> Battery backup			Provided	MR		
	Building Floor Plans	Required		Provided	MR		
20.	Special Fire Protection Systems for	NOVEC 1230 flooding for ASS, HT, LT panel		Provided	MR		
	Protection of special Risks, if any;						
	-						

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbersNIL.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name UdaiVir Singh

Name Sh Mukesh Verma

Designation ADO/WP

Designation DO/W

ONW F.T./FEL is put up for signature please.

(philosophia Machine Machine)

(philosophia M