GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2018/ 2 20

Dated :- 7-1-2-1-8-

FIRE SAFETY CERTIFICATE

Certified that the Amber Restaurant located at N-19, Connaught Circus, New Delhi comprises of Ground + 02 Upper floor, Restaurant is running at Ground + Mezzanine floor was granted FSC by this department vide letter No.F6/DFS/MS/EH/2014/NDZ/1212 dated 17/09/14. The premises was re-inspected by the officer concerned of this department on 23/01/18 in the presence of Mr. I.M Sandhu (General Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D with effect from -7/2/1/2-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -----at New Delhi by.

(Vipin Kental) Chief Fire officer Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.

2. The Manager,

Amber Restaurant at N-19, Connaught Circus, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1/15

INSPECTION REPORT

1. Name & address of the building Amber Restaurant at N-19, Connaught

Circus, New Delhi

2. Type of occupancy:- Assembly Building Group-D

Gr. + 02 upper floors, Restaurant is running at

Ground + Mezzanine floor

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/EH/2014/NDZ/1212 dated

17/09/14

5. Fire safety directives No.- N/A

6. Date of inspection:- 23/01/18

7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

from the building side:- Mr. I.M Sandhu (General Manager)

9. Year of construction:- Old Heritage Bldg.

10. Applicant's letter No:- Nil diary dated 20/12/2017

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR			
1.	Access to Building						
	1) Road width	09 mtr	16 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arr	angement of Ex	tits				
	A. Number of staircases						
	1. Upper floors	02 No.	02 No.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase						
	1. Upper floors	0.80 mtr. Old Heritage Bldg.	1.0 mtr. each	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits	N/A	N/A	N/A			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01	01	MR			
	staircase to terrace						
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	1 mtr.	1.5 mtr.	MR			
3.	Compartmentation						
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			
5.	Fire Extinguishers						
	1) Total numbers	06 Nos.	10 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR			
	3) ISI marking	Required	Provided	MR			

6.	First-Aid Hose Reel	0.5		0.1		M	D
	1) Total number of eachfloor 01			01	1	M	
	2) Length of hose reel hose	30 1			mtr.	M	
19	3) Nozzle diameter	05 1			mm	IVI	R
7.	Automatic Fire Detection &	Alar	ming Syste	m		M	ID.
	1) Type of detectors		quired		ovided	9	/A
	2) Location of main panel	N/A		N/			/A
	3) Location of repeater panel	N/A		N/		_	/A
	4) Alternate source of power	N/A		N/		7	/A
	5) Hooter's Location	N/A		N/			
8.	MOEFA		quired		ovided		IR
9.	Public Address System	N/A	4	N/	Α	IN	/A
10.	Automatic Sprinkler System			2.7		N	7 / A
230.00	1) Basement	N/2		N/			/A
	2) Upper floors		quired	-	ovided	_	IR .
	3) Sprinkler above false	N/A	A	N/	A		[/A
	ceiling		w	_		+	
11.	Internal Hydrants	1 1 0		1.0	10	N	1R
	1) Size of riser/down-comer	_	0 mm	-	00 mm		IR IR
	2) Number of hydrants per	01		01		IV	
	floor	0.1		0.1	1	N	/IR
	3) Hose box	01		01		110	/IK
12.	Yard Hydrants	- T/	A .	NI	/ A		J/A
	1) Total number of hydrants		N/A N/A	N/A N/A	N/A N/A		
	2) Hose box	IN/	A	IN	/A		VA
13.	Pumping Arrangement					-	
	1) Ground level		450 I DM		450 LPM	-	MR
	a) Discharge of main		450 LPM		430 LFW		IVIIC
	pump		30 mtr.		30 mtr.		MR
	b) Head of main pump		The second secon		N/A		N/A
	c) Number of main pu		N/A		N/A		N/A
-	d) Jockey pump out pu	ut	N/A		N/A	1	N/A
	e) Jockey pump head		N/A	15	N/A		N/A
	f) Stand by pump out		N/A		N/A		N/A
	g) Stand by pump hea		N/A N/A		N/A	i i	N/A
	h) Auto starting/Manu	ıal	IN/A		11/12		1 11/2 2
	stopping						
	2) Terrace level		180 LPM		180 LPM		MR
					30 mtr.		MR
					Provided		MR
	c) Power supply	100 10	Required Required		Provided		MR
-	d) Auto starting of pu	mp	1	т	TTOVICCE		17111
14.			ire Fighting N/A N/A			N/A	
	1) Under ground tank		N/A		TV//X		1011
	capacity	2.55	N/A		N/A		N/A
	a) Draw-off connection	on	N/A N/A		N/A		N/A
	b) Fire service inlet		N/A Required		Provided	8.1	MR
	c) Access to tank	1	Reduired		TTOVIGEG	- 1	
	d) Over head tank capacity		5,000 ltr.		5,000 ltr.	K	MR

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	•		1111
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
*7	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: ABC & Co2	em for Protect	tion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2014/NDZ/1212 dated 17/09/14 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- M.K. Sharma Designation :- ADO (CC)

Do 607 (m/m) 8

Dyc60(1102)

F.G. M.scell

FT/01.

4111 COND