GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

NO.F6/DFS/MS/School/2018/SZ/ 2 3 2

Dated: 9/2/18

FIRE SAFETY CERTIFICATE

Certified that the New Ring Midways Public School, located at E-109, Nanhey Park Uttam Nagar, New Delhi-110059, comprised of ground plus two upper floors was granted Fire Safety Certificate vide this department letter F6/DFS/MS/School/2013/SZ/1015 dated 3.10.2013. The said building was re-inspected by the officer concerned of this department on 24.1.2018 in presence of Sh. Satbir Solanki (owner) and found that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education GNCT of Delhi Circular dated 1.3.2011, and that the building is fit for occupancy class "Educational building" for ground plus three upper floors with printed overleaf.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. Director (Education), GNCT of Delhi, Old Secretariat, New Delhi.

2. Manager, New Ring Midways Public School, located at E-109, Nanhey Park Uttam Nagar, New Delhi-110059.

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

mohne

		INSPECTION RE	PORT				
1	Name & address of the building	New Ring Midways Public School at F-109 Nanhey Park Littor					
2	Type of Occupancy	INagar, New Delni.		raik, Ottaili			
3	Type of case		Educational Building "B"				
4	Details of previous NOC		Renewal (G+2)				
4	Fire safety directives letter No	F6/DFS/MS/School/2013/SZ/1015 dated 3.10.2013					
5		Directorate of Education:F-16/Estate/CC/fire Safety/2011/3298-3398 Dated 1.3.2011					
6	Date of inspection	24.1.2018					
7	Name of the inspecting Officers :	ADO S.P. Bhardwaj	ADO S.P. Bhardwaj				
8	Name and designation of officers from the building side	Sh. Satbir Solanki (o	Sh. Satbir Solanki (owner)				
9	Year of construction	before 2010					
10	Applicant's letter No.	MISC/NRMPS/AR/2017 dated 4.1.2018					
S. NO.	Minimum Standards on fire preventio						
	and fire safety U/R 33	letter dated 3.10.2013	Provided at site	Remarks MR / NMR			
1	Access to building						
	1) Road width	6 Mtrs.	0.14				
	2) Gate width	4.50 Mtrs.	6 Mtrs.	MR			
	3) Width of internal road	N/A	Direct Accessible from road	MR			
2	Number, width Type & arrangement of		N/A	N/A			
	a. Number of staircases	exits					
	1. Upper floors	2 No.	2 No.	MR			
	2. basements	N/A	N/A	N/A			
	b. Width of staircase		1				
	1. Upper floors	1.50 Mtrs. if less than 1.50 Mtrs. additional stairecase of .75 Mtr. is regiired	1.25 Mtrs. each	MR			
	2. basements	N/A	N/A				
-	c. Protection of exits	1071	IN/A	N/A			
	1. Fire check door	N/A	NIA				
	2. Pressurization	N/A	N/A	N/A			
	d. No. of continuous staircase to	14//	N/A	N/A			
	terrace	1 No.	1 No.	MR			
	e. Width of corridor	N/A	N/A	N/A			
	f. Door size	1 Mtr.	1Mtr.	MR			
	Compartmentation.						
	1. Fire check door	N/A	N/A	N/A			
	2. Sealing of electrical shafts	N/A	N/A	N/A			
	3. Fire Rating of shaft door	N/A	N/A	N/A			
	4. water curtain	N/A	N/A	N/A			
	5. Fire dampers	N/A	N/A	N/A			
	Smoke Management system.						
b	4	N/A	N/A	N/A			
	ipper fipors	12 a/c charge	Natural Ventilation	MD			
	ire Extinguishers		tatarar ventilation	MR			
THE REAL PROPERTY.		One No. CO2 OR	S Nos.	MR			
I	Types	ABC for every 300		MR			
14		Sq.Mtrs.		IVIIX			
	SI marking	ISI Marked	SI Marked	MR			

	6	First-Aid Hose Reels.			
		total numbers on each floor	1 No.	Provided	MR
		Length of Hose reel hose	30 m	Provided	
		Nozzle Diameter	5 mm	Provided	MR
	7	Automatic fire detection and alarmin		irrovided	MR
		Type of detectors	N/A	N/A	N/A
		location of Main Panel	N/A	N/A	N/A
		location of Repeater panel	N/A	N/A	N/A
		Alternate source of power	N/A	N/A	N/A
		hooter's location	N/A	N/A	N/A
	8	MOEFA	N/A	N/A	N/A
	9	Public Address System.	N/A	Provided	N/A
L	10	Automatic Sprinkler System.			INA
		basement	N/A	N/A	N/A
		upper floors	N/A	N/A	N/A
L		sprinkler above false ceiling	N/A	N/A	N/A
_	11	Internal Hydrants			IN/A
		Size of riser/down-corner	N/A	N/A	N/A
		Number of Hydrants per floor	N/A	N/A	N/A
-		hose Box	N/A	N/A	N/A
L	12	Yard Hydrants.			11477
		total number of hydrants	N/A	N/A	N/A
-		hose box	N/A	N/A	N/A
-	13	Pumping arrangements	. V		1.07,
		1. Ground level			
		a. Discharge of main Pump	N/A	N/A	N/A
		b.Head of main pump	N/A	N/A	N/A
		c.Number of main pumps	N/A	N/A	N/A
		d.jockey pump out put	N/A	N/A	N/A
		e.jockey pump head	N/A	N/A	N/A
		f. Standby Pump output	N/A	N/A	N/A
		g.Stanby Pump head	N/A	N/A	N/A
		h.Auto Starting/Manual stopping	N/A	N/A	N/A
		pump house access	N/A	N/A	N/A
		2.Terrace level			
		a. Discharge of pump	450 Lpm.	Provided	MR
		b. head of the pump	35 Mtrs.	Provided	MR
		c. Power supply	Required	Provided	MR
		d. Auto starting of pump	Required	Provided	MR
	14	Captive water storage for fire fighting			
		Underground tank capacity	N/A	N/A	N/A
		a. Draw-off connection	N/A	N/A	N/A
		b. fire service inlet	N/A	N/A	MR
		c.Access to tank	N/A	N/A	N/A
		Over head tank Capacity	10000 Lts.	Provided	MR
		Exit Signage.	Required	Provided	MR
16		Provision of lifts.			
		a. Pressurization of lift shaft	N/A	N/A	N/A
	- 1	b. pressurization of lift lobby	N/A	N/A	N/A
		c. communication in lift car	N/A	N/A	N/A
		d. Fireman's grounding switch	N/A	N/A	N/A
		e. Lift signage	N/A	N/A	N/A

			N/II				
	17	Standby	y power supply	N/A	N/A	N/A	
1	18	Refuge	Area.		Not Required		
	0	total are	a				
		location					
	19	Fire cor	itrol room				
		a. detec	tor system Panel	N/A	N/A	N/A	
		b. Flow	switch Panel	N/A	N/A	N/A	
		c. PA sy	stem Panel	N/A	N/A	N/A	
		d. Battei	backup	N/A	N/A	N/A	
			ng floor plans	N/A	N/A	N/A	
	20	Special electric	Fire Protection systems for prot meter.	tection of special risks	s, if any: ABC Fire extinguisher MR	provided near	
	The fire protection systems provided in the building were checked and found functional at the time of inspection. The shortcomings vide letter dated 18.1.2017 found rectified. Keeping in view deemed compliance of the minimum standards on fire prevention and fire safety requirements as per DOE CIR. dated 1.3.2011, renewal of FSC issued vided letter no.F6/DFS/MS/School/2013/SZ/1015 dated 3.10.2013 is recommended. Accordingly DFA is put up for approval and signature please.						
					S.P. Bhardwaj ADO (Dwarka)		
	96	AW _	J28/1/2018				
3	7/00/00		DCFO (SZ)				
2	9/1/2018	region à academic					
THE WORLD	36-1-16 1730 576 CF	200	Larg 3011 Crossts n.sce	U FTD. U LEFZ			
			Cfo/s 2+	scell legz	Semi Semi 7/2/18		