GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

Fax No. 011-23412593, Ph. 011-23412225

No. F.6/DFS/MS/GH/2018/SZ/ 3 7

Dated: 15/02/18

FIRE SAFETY CERTIFICATE

Colony, New Delhi-110065, comprised of **Basement**, **Stilt**, **Ground plus three upper floors** was issued Fire Safety Certificate by this department vide letter No. F.6/MS/DFS/GH/2015/SZ/07 dated 02/01/2015. The premises was re-inspected by the officer concern of this department on 01/02/2018 in presence of Mr. Sharda Prasad (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "**Residential**" (Guest House) as above with effect from the date of issue of this certificate for a period of **Three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 1512 at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to: -

0

- 1. The Addl. Comm. of Police (Lic.), First floor, P.S. Defence Colony, New Delhi-110049
- 2. M/s Hotel Emblem, E-5, Kalindi Colony, Near New Friends Colony, New Delhi-110065

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

Y	INSPECTION					
1	Name & Address of the Building	M/s HOTEL EMBLEM, E-5, KALINDI COL				
		(Near New Friends Colony), New Delhi-11006			10065	
2	Type of Occupancy	Residential, "Group – A" (Guest House)				
3	Building Comprised of	Basement, Stilt, Ground + 03 upper floors.				
4	Type of Case	Renewal				
5	Details of Previous NOC	F.6/DFS/MS/GH/2015/SZ/07 Dated 02-01-2015				
6	Fire Safety Directives Letter No	Nil				
7	Date of Inspection	01-02-2018				
8	Name of the Inspecting Officers	R.N. Singh, ADO (BCP)				
9	Name & Designation of Officers from the building side	Mr. Sharda Prasad (Manager)				
10	Year of construction	2009 Basement (Storage), Stilt (Parking), Ground floor (Rec. & 02 G/Rooms), 1 st floor (06 G/Rooms) 2 nd floor (06 G/Rooms) 3 rd floor (06 G/Rooms) Total 20 Guest Rooms.				
11	Applicant letter No.	Nil dated 01-01-2018, ODD No. 753 I				
S. No	Minimum standards on Fire Prevention	Old NOC		Provided at Site	Remarks	
3	and Fire Safety U/R 33	requi	rements		MR/NMR	
1	Access to Building.				1	
	Road width.		uired	6 mtr	MR	
	Gate width	N/A		Accessible from main road	N/A	
	Width of internal road	N	/A	N/A	N/A	
2	Number, width, type & arrangement of exits.	Section 1				
	a. Number of Staircase				GP =	
	Upper floors	Required		2 Nos	MR	
	Basement floor	Required		2 Nos	MR	
	b. Width of Staircase					
	Upper floors.	1.25	mtr	1.25m each	MR	
	Basement floor.	1.25	mtr	1.15-1.25m & 1.25m (Iron)	MR	
	c. Protection of exits					
	Fire check door	N/A		N/A	N/A	
	Pressurization	N/A		N/A	N/A	
	d. No. of continuous staircase to terrace	Required		2 Nos	MR	
	e. Width of corridor	N/A		N/A	N/A	
	f. Door size	1 mtr		1.15 mtr (final exit)	MR	
3	Compartmentation.			(
	Fire check door.	N/A		N/A	N/A	
	Sealing of electrical shafts.	N/A		N/A	N/A	
	 Fire rating of shaft door. 	N/A		N/A	N/A	
	Water curtain.	N/A		N/A	N/A	
	Fire dampers.	N/A		N/A	N/A	
4	Smoke Management system.	14/11		14/11	1 1/11	
4.	Basement	30 ACPH		Exhaust fan provided	MR	
	Upper floors		CPH	N/A	N/A	
5.	Fire Extinguishers.	1211				
	Total numbers	TO TO MAKE THE PARTY OF THE PAR		20 Nos	MR	
6.	Types	ISI m	arked	W.CO2-10, Co2-04, ABC-06	MR	
	ISI Marking	121 111		Yes	MR	
	First Aid Hose Reels.	100		100	1	
0.	Total numbers on each floor.			One	MR	
. 1		Носо	-reels	30 m	MR	
	Length of hose-reel hose. Normal Diameter	11050	10015	5 mm	MR	
	Nozzle Diameter			3 IIIII	IVIK	

7	Automatic fire detection & alarming system.	2		
	Type of detectors	N/A	Smoke type	N/A
	 Location of Main Panel 	N/A	Ground floor	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	Provided	N/A
	Hooter's location	N/A	Each floor	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	Basement	Required	Provided	MR
	Upper floors	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants.		14/1	IVA
	Size of Riser / Down-comer	Required	100 mm	MR
	Number of Hydrant per floor	Required	One	
				MR
10		Required	One	MR
12.	Yard Hydrants.			
	Total number of hydrants.	N/A	N/A	N/A
	Hose box.	N/A	N/A	N/A
13.	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	N/A	N/A	N/A
	Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	Jockey Pump output.Jockey Pump head.	N/A	N/A	N/A
	Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting/Manual Stopping.	N/A	N/A	N/A
		N/A	N/A	N/A
	 Terrace Level Discharge of pump. 	900 LPM	000 0 100 I DM) (D
	Head of pump.	40 mtr	900 & 180 LPM 40 mtr each	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR MR
14.	Captive water storage for Fire Fighting.	required	TIOVIUCU	IVIN
	Underground tank capacity.	N/A	N/A	N/A
	Draw-off connection.	N/A	N/A	N/A
	Fire Service Inlet.	N/A	N/A	N/A
	Access to tank.	N/A	N/A	N/A
	Overhead tank capacity.	10,000 Ltr.	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft.	N/A	N/A	N/A
	Pressurization of lift lobby.	N/A	N/A	N/A
	Communication in lift car.	Required	Provided	MR
-	Fireman's switch.	Required	Provided	MR
	Lift signage.	Required	Provided	MR
17	Standby Power Supply	Required	Provided	MR
18.	Refuge Area		×	
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A

Hotel Emblem located at E-5, Kalindi Colony (Near New Friends Colony), New Delhi

19.	Fire Control Room.							
	Detector System Panel.Flow Switch Panel.	N/A	N/A	N/A				
		N/A	N/A	N/A				
	D	N/A	N/A	N/A				
	PA system Panel.Battery backupBuilding floor plan	N/A	N/A	N/A				
		N/A	N/A	N/A				
20.	Special Fire Protection System for the Protection of special Risk, if any.	Required	CO2 type fire extinguisher	MR				
			provided near elect. panel					

The Fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/07 dated 02-01-2015, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: R.N. Singh Designation: ADO (BCP)

Hotel Emblem located at E-5, Kalindi Colony (Near New Friends Colony), New Delhi

DO (8D)