# GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 283

Dated: 23/2/18

### FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Singh International located at 4/64, Padam Singh Road Road, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus four upper floors, using basement as hall/stoag, ground floor as reception, office & 03 guest rooms, first, second and third floor each having 08 guest rooms respectively (total 27 guest rooms) and a pantry with store room on fourth floor was granted FSC by this department vide letter No. F6/DFS/MS/GH/2014/SZ/1433 dated 20.11.2014. The premises was re-inspected by the officer concerned of this department on 31/01/2018 in presence of Sh. Vishal Kumar, manager of the guest house, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 23 1118 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23/21/8 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

## Copy to:-

- 1. The Manager, M/s. Hotel Singh International, 4/64, Padam Singh Road Road, Sarol Bagh, New Delhi- 110005
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

#### Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

1. Name & address of the building

: M/s. Hotel Singh International, 4/64, Padam Singh

Road, Karol Bagh, New Delhi- 110005

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/GH/2014/SZ/1433 dated 20.11.2014

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 31-01-2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Vishal Kumar, manager

9. Year of Construction

: 2003-2004

10. Applicant's letter No.

: Form 'J' dated nil

The said guest house is comprised of basement, ground plus four upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 20.11.2014	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	06 mts	Provided	MR
	Gate width		Directly accessible	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangement	t of Exits	*	
2	a. Number of staircases	-	, <del>-</del>	-
	• Upper Floors	01	01	MR
	Basements	02	02	MR
	b. Width of staircases	-	-	
	Upper Floors	Old Case	1.37 mts	MR being old case
	Basements	Old Case	1.62, 0.94 mts	MR being old case
	c. Protection of exits	-	-	-
	Fire check door	N/A	N/A	N/A
	Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	Old case	0.78 mts	MR being old case
3	Compartmentation.			
	Fire check door	N/A	N/A	N/A
	• Sealing of electrical shafts	Required	Sealed	MR
	Fire Rating of shaft door	N/A	N/A	N/A
	• Water Curtain	N/A	N/A	N/A
	Fire Dampers	N/A	N/A	N/A
4	Smoke Management System.			

	Basements	30 a/c per hour	Exhaust fan provided	MR				
	Upper floors	12 a/c per hour	Natural Ventilation	MR 🍮				
5	Fire Extinguishers							
	<ul> <li>Total numbers</li> </ul>	20	Provided	MR				
	• Types	CO <sub>2</sub> , ABC, WCO <sub>2</sub>	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6	First-Aid Hose Reels.							
	<ul> <li>Total numbers on each floor</li> </ul>	01	Provided	MR				
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7	Automatic fire detection and alarming system.							
	• Type of detectors	N/A	N/A	N/A				
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/A				
	Alternate source of power	Required	D.G. set 125 KVA	MR				
	Hooters' Location	N/A	N/A	N/A				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	Required	Provided	MR				
10	Automatic Sprinkler System.							
	• Basement	Required	Provided	MR				
	• Upper Floor	N/A	N/A	N/A				
	Sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants							
	Size of riser/down-comer	N/A	N/A	N/A				
	Number of hydrants per floor	N/A	N/A	N/A				
•	Hose Box	N/A	N/A	N/A				
12	Yard Hydrants.							
	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.		•					
	Ground Level							
	Discharge of main Pump	N/A	N/A	N/A				
	Head of Main pump	N/A	N/A	N/A				
	Number of main pumps	N/A	N/A	N/A				
	Jockey Pump out put	N/A	N/A	N/A				
	Jockey pump head	N/A	N/A	N/A				
	Standby Pump out put	N/A	N/A	N/A				
	Standby Pump Head	N/A	N/A	NI/A				

		Pump House Access	N/A	N/A	N/A			
		Terrace level						
		Discharge of pump	450 LPM	450 LPM	MR			
		► Head of the pump	30 mts	30 mts each	MR			
		Power Supply	Required	Provided	MR			
		> Auto Starting of pump	Required	Provided	MR			
14	Capt	Captive Water Storage for fire fighting.						
	•	Underground tank capacity	N/A	N/A	N/A			
	>	Draw-off connection	N/A	N/A	N/A			
	>	Fire service inlet	N/A	Provided				
	>	Access to tank	N/A	Provided				
	•	Overhead Tank capacity	5,000 lts	5,000 lts	MR			
15	Exit S	Signage.	Required	Provided	MR			
16	Provi	sion of Lifts.						
	•	Pressurization of Lift Shaft	N/A	N/A	N/A			
		Pressurization of Lift lobby	N/A	N/A	N/A			
	• (	Communication In lift Car	Required	Provided	MR			
Simol &	• 1	Fireman's Grounding Switch	Required	Provided	MR			
0		Lift Signage	Required	Provided	MR			
17	Stand	lby power supply	Required	Provided	MR			
18	Refuge Area.							
	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	N/A	N/A			
19	Fire (	C <mark>ontrol Room</mark>						
	Shir	Detector System Panel	N/A	N/A	N/A			
		Flow Switch Panel	N/A	N/A	N/A			
		PA System Panel	N/A	N/A	N/A			
		Battery backup	N/A	N/A	N/A			
		Building Floor Plans	N/A	N/A	N/A			
20		al Fire Protection Systems for	N/A	N/A	N/A			
	Protec	ction of special Risks, if any:						

The fire protection systems provided in the building were checked and found functional at the time of inspection.



In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2014/SZ/1433 dated 20.11.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

DGF0 (32)

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

Cho Sh

m-slell

FIM.

19/2

F.T. letter is put up for Sign. please.

CFO (soutd)

m.scell

Ve 21/2.

16/20/500



1631/cfos2\_ 22/2.