GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2018/355

Dated: 06/03/2018

FIRE SAFETY CERTIFICATE

Certified that the Yuvraj Deluxe Guest House located at 38, Arakashan Road, Pahar Ganj, New Delhi. comprises of Basement, Ground + 5 upper floor, Basement - storage, ground floor - 05 guest rooms +Reception + office,1st floor - to 4th floor 08 guest rooms at each floor & fifth floor found sealed total 37 guest rooms owned/occupied by Yuvraj Guest House was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/NDZ/ 111 dated 22/01/15. The premises was re-inspected by the officer concerned of this department on 17/02/18 in the presence of Mr. Ajit Singh Sisodia(Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Residential Group -A-1' for total 37 guest rooms only as above with effect from -06/03/2018 --- for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below. Issued on ... 96 103 2018 at New Delhi by.

> (Vipin Kental) Chief Fire Officer Delhi Fire Service

Ph: - 011-2341,2225

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

The Licensee, Yuvraj Deluxe Guest House, 38, Arakashan Road, Pahar Ganj, New Delhi.

Conditions:-

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.

3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building:- Yuvraj Deluxe Guest House, 38, Arakashan

Road, Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential Group A-1 Basement, Ground + 5

upper floor

(37 guest rooms) Basement – storage, ground floor – 05 guest rooms +Reception + office, 1st floor – to 4th floor 08 guest rooms at each floor & fifth floor

found sealed. Renewal

4. Details of previous FSC:- F6/DFS/MS/GH/2015/NDZ/111

dated 22/01/15

5. Fire safety directives No.-

6. Date of inspection:-

3. Type of case:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10 Applicant's letter No:-

17/02/18

D.O. Gurmukh Singh

Mr. Ajit Singh Sisodia (Manager).

1982.

N/A

Nil. dated 12/01/18.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety measures	Provided at site (PSS)	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	6 mtr. (Approx.)	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	01 No.	01 No.	MR	
	B. Width of staircase				
	1. Upper floors	80 cms.	1.25 mtr.	MR	
	2. Basements	80 cms.	1.25 mtr.	MR	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	

	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	30 ACPH	Mechanical	MR
	2) Upper floors	12 ACPH	Natural	MR
5.	Fire Extinguishers		11000101	IVIIC
	1) Total numbers	20 Nos.	20 Nos.	MR
	2) Types	ABC & CO2	ABC &CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel	1	1101100	IVIIC
	1)Total number at each	01 no.	01 no.	MR
	floor	67.100 100.000000	32 1101	1711
	2) Length of hose reel hose	30 mtr	30 mtr.	MR
	3) Nozzle diameter	5 mm	5 mm.	MR
7.	Automatic Fire Detection & A		J 111111.	IVIIC
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	required	Tiovided	IVIIX
	1) Basement	Required	Provided	MR
	2) Upper floors	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A N/A
	ceiling	IVA	IN/A	IN/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	100 mm.	100 mm.	MR
	2) Number of hydrants per	01 no.	01 no.	MR
	floor	or no.	01 110.	IVIK
	3) Hose box	01 no.	01 no.	MR
12.	Yard Hydrants	01 110.	01 110.	IVIK
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	17/12	IVA	14/71
13.	1) Ground level	N/A	N/A	NI/A
	a) Discharge of main	N/A	N/A N/A	N/A
		IN/A	IN/A	N/A
	b) Head of main pump	N/A	N/A	NT/A
	c) Number of main pump		N/A N/A	N/A
	d) Jockey pump out put	N/A	1. No. 2 4200-1-1-1	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A N/A	N/A	N/A
	h) Auto starting/Manual	N/A N/A	N/A	N/A
		IN/A	N/A	N/A
	stopping 2) Terrace level			
	a) Discharge of pump	450 T DM	450 T D3 5	MD
	a) Discharge of pullip	450 LPM	450 LPM	MR

	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
1.4	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire Fighting					
	Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
1.5	d) Over head tank capacity	5,000 ltrs.	5,000 ltrs.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.			IVIIC		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	Required	Provided	MR		
	d) Fireman's switch	Required	Provided	MR		
	e) Lift signage	Required	Provided	MR		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System any:	for Protection of	special Risk, if	N/A		

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules FSC issued vide the F6/DFS/MS/GH/2015/NDZ/111 dated 22/01/2015, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

> Gurmukh Singh Divisional Officer

Dycro(102) M. 23/2

CFG. M. SCEU 23/2