GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/Motel/SZ/2018/352

Dated: 06 03 2018

FIRE SAFETY CERTIFICATE

Certified that the The Nandi Greens situated at KH No. 43, 46, 47, 48, Village Sultanpur, M. G. Road, Adjoining Ghitorni Metro Station, New Delhi comprised of Basement, Ground and 1st floor (BF-storage, GF-Halls, restaurants & office, 1st Floor-four Guest rooms) has already been issued FSC by this department vide letter No. F6/DFS/MS/Motel/2013/SZ/1329 dated 20/12/2013. The Farm House was re-inspected by the officer concerned of this department on 26/02/2018 in the presence of Mr. Atul Nagpal & found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010and that the building is fit for occupancy class A "Residential" (Motel) Building with effect O6/03/1-2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on 66 03/2018 New Delhi by.

(Vipin Kental) Chief Fire Officer Ph:-011-23412235

Copy to:-

5

1. The Addl. C.P.(Lic), 1st Floor P. S. Defence Colony, New Delhi-110024.

2. Mr. Atul Nagpal, The Nandi Greens, KH No. 43, 46, 47, 48, Village Sultanpur, M. G. Road, Adjoining Ghitorni Metro Station, New Delhi.

Conditions for the validity of fire safety certificate:

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of firefighting system.

4. The owner/ occupier shall submit a declaration **every year** in **Form 'K'** provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if

any.

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	1710	reduction of cons, xxxxxxxxxx	INSPECTIO	N REPORT					
1 N	Name & address of the building. The Nandi Greens, KH No. 43, 46, 47, 48, Village Sultanpur,								
1. 1	M G Road Adjoining Unitern Metro Station, New Delin								
2. T	ype o			esidential"(Motel)	Building [basemen	t+GF+I*F]			
3. T	ype o	f Case	: Renewal	1/2010/07/1	220 1 1 20/12/20	1.2			
4. D	etails	of Previous NOC	: F6/DFS/MS/Motel/2013/SZ/1329 dated 20/12/2013						
		e Safety directives letter No : F6/MS/DFS/BP/2006/488 Dated 27/02/2006							
6. D	Date of inspection : 26/02/2018								
7. N	Name of Inspecting Officer : A.K. Malik.								
8. N	Name and designation of officers From the building side : Mr. Atul Nagpal								
0 1	Vear of Construction : 2009								
	D. Applicant's letter No. : Form "J" outdoor diary no. 1684 dated 02/02/2018								
S.	Min	mum Standards on fire		Old NOC	Provided at site	Remarks			
No		fire safety U/R 33		(26-11-2010)		MR/NMR			
				Requirement					
1.	Acc	ess to building				MD			
		D 1 '1/1		Approachable	30m	MR			
		Gate width		Adequate	5m	MR -NA-			
		Width of internal road		-NA-	6m	-NA-			
2.	Nun	ber, Width, Type & Ari	rangement of	Exits					
	a. N	umber of staircases			n 111	MD			
		Upper Floors		Three	Provided	MR			
		Basements		Four	Provided	MR			
	h V	Vidth of staircases				N (T)			
	0. ,	Upper Floor		1.5m	1.5m	MR			
		Basements		$3 \times 1.5 \text{m} + \text{one}$	3 x 1.5m + one of 1.2-1.5m	MR			
	o P	rotection of exits		of 1.2-1.5m	1.2-1.5111				
	C. 1	Fire check door		Required	Provided	MR			
		Pressurization		-NA-	-NA-	-NA-			
	d.	2 :		Three	Three	MR			
		Width of Corridor		NA	NA	NA			
	f.	Door Size		NA	1m (Final Exit)	NA			
	1. Door size								
3. Compartmentation • Fire check door Required Provided						MR			
		• Fire check door			Provided	MR			
		Sealing of electrical sl		Required					
		• Fire Rating of shaft do	oor	-NA-	-NA-	-NA-			
		Water Curtain		-NA-	-NA-	-NA-			
		• Fire Dampers		-NA-	-NA-	-NA-			
4.	Sm	oke Management Systen	n) (D)			
		• Basements		30 ACPH	M.V.S.	MR			
		 Upper floors 		12 ACPH	Natural ventilation	-NA-			
5.	Fiv	e Extinguishers							
3.	1,11	Total numbers		Portable Fire	20 No's	MR			
		Total numbersTypes		Extinguishers	ABC/ W.Co ₂ / Co ₂ -	MR			
		IS marking		ISI Marked	10/10/- Yes	MR			
					1 05	IVIIC			
6.	Fi	rst-Aid Hose Reels	1 0	Hose Reels	2 No's	MR			
		Total numbers on each		nose Reels	30m	MR			
		• Length of hose reel h	iose		5mm	MR	1		
	Nozzle diameter								
7.	D mined Smoke & Heat WK								
		• Type of detectors		_	Ground Floor	-NA-			
		• Location of Main Pa		-NA-		-NA-	-		
		• Location of Repeater		-NA-	-NA- Provided	MR			
		 Alternate source of p 	ower	Required	Provided	IVIIX	-		

9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System						
	Basement	Required	Provided	MR			
	 Ground Floor 	Required	Provided	MR			
	 Sprinkler above false ceiling 	Required	Provided	MR			
11.	Internal Hydrants						
	 Size of riser/down-comer 	Required	100mm	MR MR			
	 Number of hydrants per floor 	Required	2 Nos	MR			
	• Hose Box						
12.	Yard Hydrants						
	 Total number of hydrants 	Required	4 No's provided	MR MR			
	Hose Box	Required	4 No's provided	IVIN			
13.	Pumping Arrangements						
	Ground Level	Dagwingd	1620 LPM	MR			
	Discharge of main Pump	Required	56m	MR			
	Head of Main pump	Required		MR			
	Number of main pumps	Required	One	MR			
	Jockey Pump out put	Required	180 LPM				
	Jockey pump head	Required	56m	MR			
	Standby Pump out put	Required	1620 LPM	MR			
	Standby Pump Head	Required	56m	-NA-			
	Auto Starting/Manual Stopping	Required	Provided	MR			
	> Pump House Access	Required	Provided	MR			
	Terrace level						
	Discharge of pump	Required	900 LPM	MR			
	Head of the pump	Required	36m	MR			
	Power Supply	Required	Provided	MR			
	Auto Starting of pump	Required	Provided	MR			
14.	Captive Water Storage for fire fighting						
17.	1	1,00,000 Lts	1,00,000 Lts	MR			
	 Underground tank capacity Draw-off connection 	Required	Provided	MR			
	Fire service inlet	Required	Provided	MR			
	Access to tank	Required	Provided	MR			
	Overhead Tank capacity	10,000 Lts	10,000 Lts	MR			
15.	Exit Signage.	Required	Provided	MR			
16.	Exit Signage.						
10.	Pressurization of Lift Shaft	-NA-	-NA-	-NA-			
	Pressurization of Lift lobby	-NA-	-NA-	-NA-			
	Communication In lift Car	-NA-	-NA-	-NA-			
	Fireman's Grounding Switch	-NA-	Provided	-NA-			
	Lift Signage	-NA-	-NA-	-NA-			
			Provided	MR			
17.		Required	Flovided	IVIIC			
18.	Refuge Area.	-NA-	-NA-	-NA-			
	Total Area Location	-NA-	-NA-	-NA-			
19.		-11/17-	1111				
19.		-NA-	-NA-	-NA-			
	Detector System Panel Flow Switch Panel	-NA-	-NA-	-NA-			
	Flow Switch Panel			-NA-			
	PA System Panel	-NA-	-NA-				
	Battery backup	-NA-	-NA-	-NA-			
	Building Floor Plans	-NA-	-NA-	-NA-			
20	Special Fire Protection System for Protection of special Risks, if any:						

elhi dated omly

tion fety The Nandi Greens, KH No. 43, 46, 47, 48, Village Sultanpur, M. G. Road, Adjoining Ghitorni Metro Station, New Delhi Shortcomings communicated vide letter no. F6/DFS/MS/Motel/2016/SZ/2507 dated 21/10/2016 found complied. The fire protection systems provided in the building were randomly

tested, checked and found functional at the time of inspection.

Keeping in view of the above substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Accordingly Form "H" in shape of DFA is put up for approval.

Signature of Inspecting Officer

Name: A. K. Malik Designation: DO (SD)

Dy. CFO (SZ)

dagrif

CFO (5.7) M-scell

+T/0, 1/3.

Sin F.F. is putulp for Sis-please.

CP6(82)

DO(20)

m-scell

Ve 6/3.

1652/cf. S2.