# GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No FG DFS MS Metro 392

Dated-12/03/2018

#### FIRE SAFETY CERTIFICATE

Issued on 1203 2018 at New Delhi by.

(Atul Garg) Chief Fire Officer Ph:- 011-23414250

#### Copy to:

1. Sh. Jagdish Kumar (Chief General Manager/E etrical/RC-2), Ground Floor, Airport Metro Station, Dhaulakuan, New Delhi – 110021.

### Following fire safety directives must be adhered to:-

- 1. All fire safety arrangement provided therein shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.
- 5. The Basement shall be used as per building bye laws 1983.
- 6. This certificate may not be treated in any case for regularizations of unauthorized construction if any.
- 7. The Proposal of PD Area, if any shall be referred to this department separately for approval and FSC.
- 8. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.Delhigovt.nic.in">www.dfs.Delhigovt.nic.in</a>.

## **INSPECTION REPORT**

1. Name & address of the building: Tikri Border Metro Station

(Elevated), Tikri Border, Delhi-110041.

2. Type of Occupancy : Assembly

3. Type of Case : New (Ground, Concourse Level & Platform)

4. Details of previous NOC : Nil

5. Fire Safety directives Letter No. : F6/DFS/MS/BP/2013/335 dated 11/11/13

6. Date of inspection : 05/03/2018

7. Name of the Inspecting Officers: A. K. Jaiswal, ADO(Jwp) & Mukesh Verma, D.O.(W.)

8. Name and designation of Officer

from the building side : Mr. Parvez Alam (Dy. C.E.E. / E. & M.)

9. Year of Construction : 2017-18

10. Applicant's letter No.

S	Minimum standards on fire	NFPA	/ NBC	Provided at	Remarks	
No	prevention and fire safety		rements	site	MR/NM	
1.	U/R 33				1	
1,	Access of building				*	
	Road width	On Main Road		On Main Road	MR	
	• Gate width	5 mtr		On Main Road	ad MR	
2.	• Width of internal road			N/A	N/A	
۷.	Number, width, Type & Arra	ingements	of exits	· ·		
	a. Number of staircases					
	• Upper floors	2 + 4		2 + 4	MR	
	Basements     b. Width of staircases	NA		NA	NA	
	Total of Staff Cases		,		8	
	<ul> <li>Upper floors</li> </ul>	2 mtr	1. Ground 4.50 mtr x1	to Concourse 2.50 m	ntr x 1 & MF	
			5.0 9000	se to platform 3.68n	ata 4	
	<ul> <li>Basements</li> </ul>	NA		NA	NA NA	
	c. Protection of exits		6		IVA	
	Fire check door	NA		NA	NIA	
	<ul> <li>Pressurization</li> </ul>	NA	0	NA	NA	
	d. No of continuous	NA		NA	NA	
	staircase to terrace			IVA	NA	
	e. Width Of Corridor	1.50 mt	•	Hall	MR	
	f. Door Size	1.00 mtr		1.00 mtr	MR	
3.	Compartmentation				14117	
	<ul> <li>Fire check door</li> </ul>	Required	t	Provided	MR	
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	d	Provided	MR	
	<ul> <li>Fire Rating of shaft door</li> </ul>	Required		Provided	MR	
	<ul> <li>Water Curtain</li> </ul>	N/A		N/A	N/A	
	<ul> <li>Fire Dampers</li> </ul>	N/A		N/A	N/A	
	Smoke managements System				14//1	
	<ul> <li>Basements</li> </ul>	NA		NA	NA	
	<ul> <li>Upper floors</li> </ul>	NA		NA	NA	
. F	Fire Extinguishers					
	<ul> <li>Total numbers</li> </ul>	20		30	MR	
	• Types	ISI marked	ABC/CO <sub>2</sub>	Provided	MR	
	IS marking	Required			VIR VIR	
	Alex					

6	T:	4.1.2		4/	<b>b</b>					
6	. Firs	t – Aid Hose Reels								
	-	• Total numbers on each floor		2	Co	2 at Ground Floor, 3 at Concourse level & 4 at Platform		at at	MR	
	•	<ul> <li>Length of hose reel hose</li> </ul>		45 Mtr.	45.84		45 Mtr.		MR	
	•	Nozzle diameter		6.5 mm		91	6.5 mm		MR	
7.	Auto	matic fire detection a	nd	aloma:						
	•	Type of detector	IIU a	Smoke	ystem					
	Location of Main			Required			Provided	*	MR	
	•	Panel				Provided			MR	
		Location of Repeat Panel		Required			Provided		MR	
	•	Alternate source of power	•	Required	•	F	Provided		MR	
	<ul> <li>Hooters' Location</li> </ul>			Required		Provided			MR	
8.	MOEF			Required						
9.	Public Address System			Required			rovided		MR	
10.	Autom	natic Sprinkler Systen	n	Required			Provided		MR	
	•	Basements		N/A		N	/Δ	T	AL/A	
	•	Upper Floor		N/A		N/A N/A			N/A	
	<ul> <li>Sprinkler above false ceiling</li> </ul>		е	N/A			/A		N/A N/A	
11.	Internal Hydrants									
	<ul> <li>Size of riser/down- comer</li> </ul>			150 mm		150 mm			MR	
		<ul> <li>Number of hydrants per floor</li> </ul>		2 2 at Gro Concour Platform		ourse	urse level & 4 at		MR	
		Hose Box		Required		Provided		-	AD	
2.	Yard Hy	drants			Provided				ΛR	
	• Total number of hydrants		F	Required		Pro	Provided N		1R	
3.		Hose Box	F	Required		Provided		N	MR	
•	Grang	Arrangements								
•		d Level								
A	Head	rge of main pump	-	800 LPM		180	O LPM	M	R	
7	Numbe	f main pump	-	0 mtr	-15	70 n	ntr	M		
7	Jockey	er of main pumps	1			1		M		
>	1 1		_	180 LPM		180 LPM		M	R	
7	Standby	Pump out put	_	mtr		70 m	ntr	M	R	
>	Stonday D. III		_	1800 LPM 70 mtr				MI	3	
>	Auto St	aring/Manual	-	quired		70 m		M	?	
A	stopping	g Iouse Access				Provided		MF	?	
•	Terrace	level	N/	A			N/A		N/A	
7		ijscharge C								
7	Head of	the pump	N/				N/A N		4	
7	Power si	upply	N/			N/A		N/A	N/A	
	Auto ata d' C		N/		14/					
	rato sta	ting of pump	N/A	4		N/A		N/A		

		MIA	-					
14.	Captive water Storage for fire fighting							
	<ul> <li>Under Ground tank capacity</li> </ul>	50,000 ltr	50,000 ltr	MR				
	Draw of connection	Required	Provided	MR				
	> Fire service inlet	Required	Provided	MR				
	Access to tank	Required	Provided	MR				
	<ul> <li>Overhead Tank capacity</li> </ul>	10,000 Ltr.	10,000 Ltr.	MR				
15	Exit Signage	Required	Provided	MR				
16.	Provision of Lifts	· · · · · · · · · · · · · · · · · · ·						
	<ul><li>Pressurization of Lift Shaft</li></ul>	N/A	N/A	N/A				
	<ul><li>Pressurization of lift lobby</li></ul>	N/A	N/A	N/A				
	Car Communication in lift	Required	Provided	MR				
	<ul><li>Fireman's Grounding Switch</li></ul>	Required	Provided	MR				
	➤ Lift Signage	Required	Provided	MR				
17.	Standby power supply	Required	Provided	MR				
18.	Refuge Area	N/A	N/A					
	Total area	N/A	N/A	N/A				
	Location	N/A	N/A	N/A				
19.	Fire control room							
	Detector system panel	Required	Provided	MR				
	Flow Switch Panel	N/A	N/A	N/A				
	PA System Panel	Required	Provided	MR				
	Battery backup	Required	Provided	MR				
	Building Floor Plans	N/A	N/A	N/A				
20.	Special Fire Protection	NOVEC-1230	NOVEC-1230	MR				
	Systems for Protection of special Risks, if any;	flooding for ASS, HT, LT panel	flooding for ASS, HT, LT panel	9				

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal

Designation : A.D.O. (Jwala Puri)

Signature of the Inspecting Officer

Name : Mukesh Verma Designation : D.O. (West)

Dy. (fo (pr) - 4/2 cfo 4/5) for 1/8 ft P/s

TOM ce put up for