GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

Fax No. 011-23412593, Ph. 011-23412225

No. F.6/DFS/MS/EH/2018/SZ/ 3 \$ 8

Dated: .8/.3/18

FIRE SAFETY CERTIFICATE

Certified that the Restaurant in the name & style of M/s Haldiram Marketing Pvt. Ltd., located at Shop No-31, Ground floor & Shop No-103, First floor, Multilevel Car Parking cum Commercial Complex, DLF South Squire Mall, Sarojini Nagar, New Delhi-110023, comprised of Basement, Ground plus Eight upper floors. The restaurant premise was inspected by the officer concerned of this department on 23/02/2018 in presence of Mr. Nandan (Manager) and found that the said restaurant premise have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Assembly" Group—D (Restaurant) as above with effect from the date of issue of this certificate for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

Issued on 3/3/8 at New Delhi by

(Vipin Kental) Chief Fire Officer

12-

Copy to: -

- 1. The Manager (Admn & Liaison), M/s Haldiram Marketing Pvt, B-1/H-3, Mohan Co-operative Industrial Estate, Main Mathura Road, new Delhi-110 044
- 2. The Medical Officer of Health, N.D.M.C, Palika Kendra, New Delhi-110 001

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

1		TON REPORT	1 1 2 7			
1	Name & Address of the Building	M/s Haldiram Marketing Pvt. Ltd, Shop No-31, Ground Floor and Shop No-103, First Floor, Multilevel Car				
			nmercial Complex, DLF S	outh Squire		
		Mall, Sarojini Nagar, New Delhi-110 023				
2	Type of Occupancy	Assembly, Group	-D (Restaurant)			
3	Building comprised of	Basement, Groun	d plus Eight upper floors.			
4	Type of Case	New				
5	Details of Previous NOC	Nil				
6	Fire Safety Directives Letter No	F.6/DFS/MS/BP/2008/3507 Dated 22-12-2008 an				
	The Saidty Directives Edited 110	F.6/DFS/MSBP/2014/17 Dated 17/01/2014				
7	Date of Inspection	23-02-2018				
8	Name of the Inspecting Officers					
9	Name & Designation of Officers	R.N. Singh, ADO (BCP)				
9		Mr. Nandan (Manager)				
10	from the building side	l contract of the contract of				
10	Year of construction	2011 Restt running at ground & 1 st floor of the bldg				
11	Applicant letter No.	Nil dated 07-02-				
S. No	Minimum standards on Fire Prevention	Old NOC Provided at Site Rem		Remark		
	and Fire Safety U/R 33	requirement		MR/NMI		
1	Access to Building.	FSC No.F.6/DFS/I	MS/Parking/2015/SZ/1509 [pt. 18/08/201		
	 Road width 	Restt. within	9 mtr	MR		
	Gate width	Multilevel Car	4.5 mtr	MR		
	Width of internal road	Parking	6 mtr from two sides	MR		
2	Number, width, type & arrangement of exits	0	o ma nom two sides	IVIIC		
	a. Number of Staircase			*		
	Upper floors	Dogwined	02 + 01 N-2- (01 N) M		
	• Opper Hoors	Required	03 + 01 No's (01 No	MR		
	Basement floor	N/A	from inside of the Restt N/A	N/A		
	b. Width of Staircase	IN/A	IN/A	IN/A		
		1.50	,			
	Upper floors Basement floor	1.50m	1.5m each	MR		
	Dascinent 11001	N/A	N/A	N/A		
	c. Protection of exits		Y			
	Fire check door	Required	Provided	MR		
	Pressurization	Required	Provided	MR		
	d. No. of continuous staircase to terrace	Required	Three	MR		
	e. Width of corridor	1.5 / 2m	Provided	MR		
	f. Door size	1.5m & 2m	1.5m & 2m	MR		
3	Compartmentation.					
	Fire check door.	Required	Provided	MR		
	 Sealing of electrical shafts. 	Required	Provided	MR		
	Fire rating of shaft door.	Required	2 Hrs	MR		
	Water curtain	N/A	N/A	N/A		
	Fire dampers.	Required	Provided	MR		
4.	Smoke Management system.	1		1111		
	Basement	30 ACPH	N/A	N/A		
	Upper floors	12 ACPH	Exhaust fan provided	MR		
5.	Fire Extinguishers.	12/10/11	LAndust Idii provided	IVIK		
	Total numbers	6 No's	10 Nata) III)		
	• Types	ABC / Co2	10 No's	MR		
	ISI Marking	ISI marked	ABC type	MR		
6.	First Aid Hose Reels.		Provided	MR		
U.			stem is common for entir			
	Total numbers on each floor.	2 No's	02 No's	MR		
	 Length of hose-reel hose. 	30 m	30 m	MR		
all de	Nozzle Diameter	5 mm	5 mm			

M/s Haldiram Marketing Pvt Ltd at Shop No-31 (GF) & 103 (FF), MLCPCCC, Sarojini Nagar, New Delhi

7	Automatic fire detection & alarming system.				
	Type of detectors	Required	Smoke & Heat type	MR	
	 Location of Main Panel 	Required	Ground floor	MR	
	 Location of Repeater Panel 	Control Room	Control Room	MR	
	 Alternate source of power 	Required	Provided	MR	
	 Hooter's location 	Required	Each floor	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	Fire fighting system is common for entire compl			
	Basement	N/A	N/A	N/A	
	Upper floors	Required	Provided	MR	
	 Sprinkler above false ceiling 	Required	Provided	MR	
11.	Internal Hydrants.	Fire fighting system is common for enti		re compl	
	 Size of Riser/Down-comer 	Required	150 mm	MR	
	 Number of Hydrant per floor 	Required	02 No's	MR	
	 Hose box. 	Required	02 No's	MR	
12.	Yard Hydrants.	Fire fighting sy	stem is common for enti	9	
	Total number of hydrants.	Required	04 No's	MR	
	 Hose box. 	Required	04 No's	MR	
13.	Pumping arrangements.		stem is common for enti		
	Ground Level				
	Discharge of main pump.	2850 LPM x 2	2850 LPM x 2	MR	
	Head of main pump.	60 mtr	60 mtr	MR	
	Number of main pumps.	02 No's	02 No's	MR	
	Jockey Pump output.	180 LPM	180 LPM	MR	
	Jockey Pump head.	60 mtr	60 mtr	MR	
	Standby Pump output.	2850 LPM	2850 LPM	MR	
	Standby Pump head.	60 mtr	60 mtr	MR	
	Auto Starting/Manual Stopping.	Required	Provided	MR	
	Pump House Access	Required	Provided	MR	
	Terrace Level		1101100	TVIIC	
	Discharge of pump.	900 LPM	900 LPM	MR	
	> Head of pump.	40 mtr	40 mtr	MR	
	Power supply.	Required	Provided	MR	
	Auto starting of pump.	Required	Provided	MR	
14.	Captive water storage for Fire Fighting. Fire fighting system is common for entire				
	Underground tank capacity.	1,50,000 ltrs	1,50,000 ltrs	MR	
	Draw-off connection.	Required	Provided	MR	
	Fire Service Inlet.	Required	Provided	MR	
	Access to tank.	Required	Provided	MR	
	Overhead tank capacity.	25,000 ltrs	25,000 ltrs	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	 Pressurization of lift shaft. 	Required	Provided	MR	
	 Pressurization of lift lobby. 	Required	Provided	MR	
	 Communication in lift car. 	Required	Provided	MR	
	 Fireman's switch. 	Required	Provided	MR	
			Provided	MR	
	Lift signage.	Required	1 IOVIGCG	AVAM &	
	Lift signage. Standby Power Supply	Required *	Provided	MR	
17 18.	Standby Power Supply		Provided		

M/s Haldiram Marketing Pvt Ltd at Shop No-31 (GF) & 103 (FF), MLCPCCC, Sarojini Nagar, New Delhi

19.	Fire Control Room.	Fire fighting system is common for entire complex		
	Detector System Panel.	N/A	Provided	N/A
	Flow Switch Panel.	N/A	N/A	N/A
	PA system Panel.Battery backupBuilding floor plan	N/A	N/A	N/A
		N/A	Provided	N/A
		N/A	N/A	N/A
20.	Special Fire Protection System for the	Required	Provided CO2 flooding	MR
	Protection of special Risk, if any:		system for LT & HT panel	

The Fire protection systems provided in the building were test checked at random and found functional at the time of inspection. The shortcomings communicated vide even letter dated 17/06/2016 found complied.

Keeping in view the substantial satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules, 2010.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name : R.N. Singh Designation: ADO (BCP)

M/s Haldiram Marketing Pvt Ltd at Shop No-31 (GF) & 103 (FF), MLCPCCC, Sarojini Nagar, New Delhi

F.T letter is but up for signifile.

Provided the signification of the s