GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2018/ 49/

Dated: 23/3/18

FIRE SAFETY CERTIFICATE

Certified that the Shivaji Stadium Complex located at New Delhi comprised of 2B + Ground + 04 Upper floors was granted FSC by this department vide letter F6/DFS/MS/Stadium/2013/49 dated 04/01/2013. The premises was re-inspected by the officer concerned of this department on 08/03/18 in the presence of Sh. Sajjan Kumar (Fire Officer) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building with effect from --2-2/-2-1-13- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --- 2-3-13-- at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. Sh. Sajjan Kumar, Fire Officer, New Delhi Municipal Council, Palika Kendra, New Delhi.
- The Chief Architect,
 Department of Architecture and Environs,
 New Delhi Municipal Council, Palika Kendra, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building: Shivaji Stadium Complex at New Delhi

2. Type of occupancy

: Assembly Building 2B + Gr.+4 Upper Floors

3. Type of case:-

: Renewal

4. Details of previous FSC

: F6/DFS/MS/Stadium/2013/49 dated 04/01/2013

5. Fire safety directives No.

: N/A

6. Date of inspection:-

08/03/18

7. Name of the inspecting officer

8. Name & designation of officer From the building side

: A.D.O. M.K Sharma

9. Year of construction

: Sh. Sajjan Kumar (Fire Officer) : 2010

10. Applicant's letter No

: 287/Fire/D-/2018Dated 19/02/18

S.No.	Standards on the	1	Provided at site	Old Case Remarks			
	Prevention and fire safety U/R 33	Existing		MR/NMF			
1.	Access to Building	_	1				
	1) Road width	12 mtr.	16 mtr.	MR			
	2) Gate width	06 mtr.	06 mtr.	MR			
	3) Width of internal road	06 mtr.	06 mtr.				
2.	Number, Width Type & Arra	angement of Exite	oo mu.	MR			
	A. Number of staircases						
	1. Upper floors	08	08	MD			
	2. Basements	10	10 + 02 ramp	MR			
	B. Width of staircase		10 + 02 Tallip	MR			
	1. Upper floors	1.5 mtr.	1.5 mtr. each	MD			
	2. Basements	1.5 mtr. & 02	1.5 mtr. each & 02	MR			
		ramp	ramp	MR			
	C. Protection of exits						
	1. Fire check door	Required	Provided	MR			
	2. Pressurization	Required	Provided	MR			
	D. No. of continuous	N/A	N/A	N/A			
	staircase to terrace		1771	IN/A			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	2 Mtr.	2 Mtr.	MR			
3.	Compartmentation			IVIIX			
	1) Fire check door	Required	Provided	MD			
	2) Sealing of electrical shafts	Required	Provided	MR			
	3) Fire rating of shaft door	Required	Provided	MR			
	4) Water curtain	N/A	N/A	MR N/A			
	5) Fire Dampers	Required	Provided				
	Smoke Management System Required Provided MR						
	1) Basements	30 ACPH	Provided	MD			
	2) Upper floors	12 ACPH	Natural	MR MR			
•	Fire Extinguishers		Tratarar	IVIR			
	1) Total numbers	125 Nos.	125 Nos.	MR			
	2) Types	-	ABC, CO2 &	MR			
		ABC & CO2	W.CO2	IVIK			
	3) ISI marking	Required	Provided	MR			
	First-Aid Hose Reel		2.071404	IVIIV			
	1)Total number of each	02 No.	02 No. at each	MR			
	floor		floor	IVIK			
2	2) Length of hose reel hose	30 m	30 m	MR			
3	3) Nozzle diameter	05 mm	05 mm.	IVIK			

				1
7.	Automatic Fire Detection &	Alarming System		
	1) Type of detectors	Required	Provided	MR
	2) Location of main panel	Required	Provided	MR
	3) Location of repeater panel	Required	Provided	MR
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Required	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System		71011404	WIIX
	1) Basement	Required	Provided	MR
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling		1471	IVA
11.	Internal Hydrants			
	1) Size of riser/down-comer	150 mm	150 mm	MR
	2) Number of hydrants per	04	04	MR
	floor	04	04	IVIK
	3) Hose box per flor	04	04	MD
12.	Yard Hydrants	04	04	MR
12.	1) Total number of hydrants	08	0.0	1.00
	2) Hose box	08	08	MR
13.		08	08	MR
13.	Pumping Arrangement			
	1) Ground level			
	a) Discharge of main	2280 LPM	2280 LPM	MR
	pump			5
	b) Head of main pump	90 mtr.	90 mtr.	MR
	c) Number of main pump		02	MR
	d) Jockey pump out put	220 LPM	220 LPM	MR
	e) Jockey pump head	90 mtr.	90 mtr.	MR
	f) Stand by pump output	2280	2280	MR
	g) Stand by pump head	90 mtr.	90 mtr.	MR
	h) Auto starting/Manual	Required	Provided	MR
	stopping			
	2) Terrace level			
	a) Discharge of pump	900 LPM	900 LPM	MR
	b) Head of pump	90 mtr	90 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
4.	Captive Water Storage for Fire		Trovided	TVIIC
	1) Under ground tank	2,00,000 ltr.	2,00,000 ltr.	MR
	capacity	2,00,000 141.	2,00,000 111.	IVIIC
	a) Draw-off connection	Required	Provided	MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank	20,000 Ltr.	20,000 ltr.	
	capacity	20,000 Ltt.	20,000 Itr.	MR
5.	Exit Signage.	Required	Provided	MD
5.	Provision of Lifts.	Required	Provided	MR
•				
	a) Pressurization of lift	Required	Provided	MR
	shaft			u u
	b) Pressurization of lift	Required	Provided	MR
	lobby			
	c) Communication in	Required	Provided	MR
	lift car			
	d) Fireman's switch			

NIA

~	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room			
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/2016/807 dated 01/04/2016 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/Stadium/2013/49 dated 04/01/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- M.K. Sharma
Designation :- ADO (CC)

Do(co) (15/13)18