GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 517

Dated: 27/03/2018

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel C Park located at 6/13, WEA, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus three upper floors, using basement as hall/storage, ground floor as reception & office, first, second and third floor each having 08 guest rooms respectively (total 24 guest rooms) and a kitchen with two staff rooms on terrace was granted FSC by this department vide letter No. F6/DFS/MS/GH/2014/SZ/1531 dated 09.12.2014. The premises was re-inspected by the officer concerned of this department on 20/03/2018 in presence of Sh. Rakesh Chadha, proprietor, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 27 62 2019 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 27/03/20/18 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Sh. Rakesh Chadha (Owner), M/s. Hotel C Park, 6/13, WEA, Karol Bagh, New Delhi-110005.

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.

3. The trained firefighting staffs should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. The basement shall be used as per the provisions of BBL.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

: M/s. Hotel C Park, 6/13, WEA, Karol Bagh, New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2014/SZ/1531 dated 09.12.2014

5. Fire Safety directives letter No : Nil

6. Date of inspection : 20.03.2018

7. Name of the Inspecting Officers : M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side : Sh. Rakesh Chadha, Owner

9. Year of Construction : 2005

10. Applicant's letter No. : nil dated 23.01.2018

The said guest house is comprised of basement, ground plus three upper floors.

S. No.	Minimum Standards on f prevention and fire safety U	arrangements as	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	06 mts	Provided	MR			
	Gate width		Directly accessible	MR			
	Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases						
	Upper Floors	01	01	MR			
	Basements	01	01	MR being old case			
	b. Width of staircases		-				
	Upper Floors	Old Case	1.30 mts	MR			
	Basements	Old Case	1.25 mts	MR			
	c. Protection of exits	7 7 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	-				
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	e. No. of continuous stairc terrace	ases to 01	01	MR			
	g. Width of Corridor	1.25mt.	1.52 mts.	MR			
	h. Door Size	Old case	0.87 mts	MR being old case			
3 .	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shat	fts N/A	Sealed				
	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.		Some of the second	Apple			
	Basements	30 a/c per hour	Exhaust fan	- 4 4 4			

5 Fire Extinguishers • Total numbers • Types • IS marking • Total numbers • IS marking • Total numbers on Expensive of Provided • Is marking • Total numbers on each floor • Length of hose reel hose • Nozzle diameter • Type of detection and alarming system. • Type of detectors • Location of Main Panel • Location of Repeater Panel • Hooters' Location • Hooters' Location • Basement • Upper Floor • Sprinkler above false ceiling • Size of riser/down-comer • Number of hydrants • Total numbers on each floor • Length of hose reel hose • 30 m Provided • MR N/A N/A N/A N/A N/A N/A N/A N/		• Upper floors	12 a/c per hour	N		
• Types • IS marking • IS marking 6 First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose • Nozzle diameter 7 Automatic fire detection and alarming system. • Type of detectors • Location of Main Panel • Alternate source of power • Hooters' Location 8 MOEFA Provided N/A Required Provided MR Provided MR Provided MR Provided MR Provided MR N/A N/A N/A N/A N/A N/A N/A N/	5	Fire Extinguishers	are per nour	Natural Ventilation	MR	
• Types • IS marking • IS marking • IS marking • ISI marked • ISI marked • First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose • Nozzle diameter • Type of detection and alarming system. • Type of detectors • Type of detectors • Location of Main Panel • Alternate source of power • Hooters' Location • Hooters' Location • Required • Provided • MR MR MR Provided • MR MR MR Provided • MR MR MR MR Provided • MR	· ·	Total numbers	16		0	
• IS marking ISI marked Provided MR 6 First-Aid Hose Reels. • Total numbers on each floor 01 Provided MR • Length of hose reel hose 30 m Provided MR • Nozzle diameter 5 mm Provided MR 7 Automatic fire detection and alarming system. • Type of detectors N/A N/A N/A • Location of Main Panel N/A N/A N/A • Location of Repeater Panel N/A N/A N/A • Alternate source of power Required D.G. set 25 KVA MR • Hooters' Location N/A N/A N/A N/A 8 MOEFA Required Provided MR 9 Public Address System. Required Provided MR 10 Automatic Sprinkler System. • Basement Required Provided MR 10 Automatic Sprinkler System. • Basement Required Provided MR 10 Internal Hydrants • Size of riser/down-comer N/A N/A N/A N/A • Number of hydrants per floor N/A N/A N/A N/A • Number of hydrants per floor N/A N/A N/A N/A • Hose Box N/A N/A N/A N/A N/A • N/A N/A N/A N/A N/A • N/A N/A N/A N/A N/A • N/A N/A N/A N/A •		• Types		Provided	MR	
6 First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose • Nozzle diameter 7 Automatic fire detection and alarming system. • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location 8 MOEFA 9 Public Address System. • Basement • Upper Floor • Sprinkler above false ceiling • Size of riser/down-comer • Number of hydrants per floor • Hose Box • Total numbers on each floor 0 1 Provided MR Provided MR Provided MR N/A N/A N/A N/A N/A N/A N/A N/		IS marking			MR	
Length of hose reel hose Nozzle diameter Nozzle diameter Smm Provided MR MR MR MA N/A	6	First-Aid Hose Reels.	101 marked	Provided	MR	
Length of hose reel hose Nozzle diameter Nozzle diameter Smm Provided MR MR MR MA N/A		Total numbers on each floor				
Nozzle diameter 5 mm Provided MR Automatic fire detection and alarming system. Type of detectors N/A N/A N/A N/A Location of Main Panel N/A N/A N/A N/A Location of Repeater Panel N/A N/A N/A N/A Alternate source of power Required D.G. set 25 KVA MR Hooters' Location N/A N/A N/A N/A MOEFA Required Provided MR Public Address System. Required Provided MR O Automatic Sprinkler System. Basement Required Provided MR Upper Floor N/A N/A N/A N/A N/A Sprinkler above false ceiling N/A N/A N/A N/A Internal Hydrants Size of riser/down-comer N/A	-			Provided	MR	
7 Automatic fire detection and alarming system. • Type of detectors			1 8	Provided	MR	
• Type of detectors • Location of Main Panel • Location of Main Panel • Location of Repeater Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location • Hooters' Location N/A Required Provided MR Public Address System. Required Provided MR Provided MR Automatic Sprinkler System. • Basement • Upper Floor • Sprinkler above false ceiling N/A N/A N/A N/A N/A N/A N/A N/	7 A	Provided				
Location of Main Panel Location of Repeater Panel Location of Repeater Panel Location of Repeater Panel Alternate source of power Hooters' Location N/A MOEFA Required Public Address System. Required Provided MR Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling N/A N/A N/A N/A N/A N/A N/A N/				of the last of		
Location of Repeater Panel Alternate source of power Hooters' Location N/A N/A N/A Required D.G. set 25 KVA MR Hooters' Location N/A N/A N/A N/A N/A N/A N/A Required Provided MR Public Address System. Required Provided MR Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling N/A N/A N/A N/A Internal Hydrants Size of riser/down-comer N/A	*		IN/A	N/A	N/A	
Location of Repeater Panel Alternate source of power Hooters' Location N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A			N/A	N/A	N/A	1
 Alternate source of power Hooters' Location N/A <li< td=""><td></td><td> Location of Repeater Panel </td><td>N/A</td><td>N/A</td><td></td><td>-</td></li<>		 Location of Repeater Panel 	N/A	N/A		-
• Hooters' Location N/A N/A N/A N/A N/A N/A N/A N/			Required	D.G. set 25 KVA		
Public Address System. Required Provided MR Required Provided MR Automatic Sprinkler System. Basement Required Provided MR Upper Floor N/A N/A N/A Internal Hydrants Size of riser/down-comer N/A N/A N/A N/A Number of hydrants per floor Hose Box N/A N/A N/A N/A N/A	8 100		N/A	N/A		
10 Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling N/A Internal Hydrants Size of riser/down-comer N/A	TV.		Required	Provided	*MD	
Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling N/A N/A N/A N/A N/A N/A N/A N/A	1 4		Required			
 Upper Floor Sprinkler above false ceiling N/A 	10 Au		-		IVIK	
Sprinkler above false ceiling N/A N/A N/A 11 Internal Hydrants N/A N/A N/A • Size of riser/down-comer N/A N/A N/A • Number of hydrants per floor N/A N/A N/A • Hose Box N/A N/A N/A	-		Required	Provided	MR	
N/A N/A N/A Internal Hydrants Size of riser/down-comer N/A		The state of the s	N/A	N/A		
Internal Hydrants Size of riser/down-comer N/A Number of hydrants per floor Hose Box N/A N/A N/A N/A N/A N/A N/A N/	-		N/A	N/A		
 Number of hydrants per floor Hose Box N/A N/A N/A N/A N/A N/A N/A 	11 Inte	ernal Hydrants		IN/A		
 Number of hydrants per floor Hose Box N/A N/A N/A N/A N/A N/A 			N/A	N/A		
N/A N/A N/A	•	Number of hydrants per floor	N/A		N/A	
N/A N/A	•	• Hose Box	N/A	N/A	N/A	
14 I di II d	12 Vand	d IIl	IV/A	N/A	N/A	
 Total number of hydrants Hose Box N/A N/A N/A 			N/A	N/A	N/A	
N/A N/A			N/A	N/A		
13 Pumping Arrangements. • Ground Level					11/11	

Discharge of main Pump N/A N/A N/A N/A			N/A	N/A	N/A	
Number of main pumps N/A N/A N/A N/A		Parip	N/A	N/A		
Joekey D. N/A	>		N/A			i.
Jockey numer band	>		N/A			
Standby Duna						
Standby D. V.						
Auto Starting/ Manuel starting / N/A N/A N/A		Tana Tump riead				
Pump House Access	>	Pump House Access		IV/A	N/A	

1		Terrace level		N/A	N/A	N/A			
1		Discharge of pump							
		Head of the pump		450 LPM	450 LPM	MR			
1		Power Supply		30 mts	30 mts each	MR			
		> Auto Starting of pump		Required	Provided	MR			
		a sure desired and a party		Required	Provided	MR			
14	Capti	Captive Water Storage for fire fighting.							
		Underground tank capacity		N/A	N/A	N/A			
	>	Draw-off connection		N/A	N/A	N/A			
0	>	Fire service inlet		N/A	Provided				
2.	- Common D	Access to tank		N/A	N/A	N/A			
199		Overhead Tank capacity	C	old case	Provided (6,000 lts)	MR			
15	Exit S	ignage.	R	equired	Provided	MR			
16	Provision of Lifts.								
	•	Pressurization of Lift Shaft		N/A	N/A	N/A			
	•	Pressurization of Lift lobby		N/A	N/A	N/A			
	•	Communication In lift Car	R	equired	Provided	MR			
	•	Fireman's Grounding Switch	R	equired	Provided	MR			
	•	Lift Signage	R	equired	Provided	MR			
17	Stand	by power supply	R	equired	Provided	MR			
18									
	>	Total Area		N/A	N/A	N/A			
	>	Location		N/A	N/A	N/A			
19	19 Fire Control Room								
		Detector System Panel		N/A	N/A	N/A			
		Flow Switch Panel		N/A	N/A	N/A			
	•	PA System Panel		N/A	N/A	N/A			
	•	Battery backup		N/A	N/A	N/A			
		Building Floor Plans		N/A	N/A	N/A			
20		Il Fire Protection Systems for tion of special Risks, if any:		N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2014/SZ/1531 dated 09.12.2014, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West)

F-T. letter is put up for Sign. please.

CFO (South)

M. SCELL W26/3.