GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2018/ 518

Dated: 27/03/2018

FIRE SAFETY CERTIFICATE

Certified that M/s. Hotel Garden View located at 5/12, WEA, Saraswati Marg, Karol Bagh, New Delhi- 110005 comprised of basement, ground plus three upper floors, using basement (hall/storage), ground floor (reception, office,pantry & 01 guest rooms), first floor (10 guest room), second floor (10 guest rooms), third floor (09 guest rooms) (total 30 guest rooms), was granted FSC by this department vide letter No. F6/DFS/MS/GH/2015/SZ/195 dated 10.02.2015. The premises was re-inspected by the officer concerned of this department on 20/03/2018 in presence of Sh. Narayan (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from 27/182 2018 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 27 13 2018 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. Sh. Sh.Dinesh Ahuja (Owner) M/s. Hotel Garden View, 5/12, WEA, Saraswati Marg Karol Bagh, New Delhi- 110005

2. The Joint C.P. (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel Garden View located at 5/12, WEA, Saraswati Marg , Karol Bagh, New Delhi- 110005

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2015/SZ/195 dated 10.02.2015

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 20.03.2018

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Sh. Narayan (Manager)

9. Year of Construction

: Before 2001

10. Applicant's letter No.

: 1303/ADDL/ C.P./Lic (H) dated 23.02.2018

The said guest house is comprised of basement, ground plus three upper floors.

Minimum Standards on fire prevention and fire safety U/R 33	Fire safety arrangements as per letter dt. 16.02.2015	Provided at site	Remarks MR/NMR			
Access to building						
Road width	06 mts	Provided	MR			
Gate width		Directly accessible	MR			
Width of internal road	N/A	N/A	N/A			
Number, Width, Type & Arrangement of Exits						
a. Number of staircases	-	-	-			
 Upper Floors 	01	01	MR			
• Basements	01	01	MR			
b. Width of staircases	-	-	- ,			
 Upper Floors 	1.25 mts	1.25 mts	MR, Old case			
Basements	1.25 mts	1.25 mts	MR, Old case			
c. Protection of exits	_	-	_			
Fire check door	N/A	N/A	N/A			
 Pressurization 	N/A	N/A	N/A			
e. No. of continuous staircases to terrace	01	01	MR			
g. Width of Corridor	1.25 mt.	1.52 mts.	MR			
h. Door Size	Old case	0.78 mts	MR being old case			
Compartmentation.		^				
Fire check door	N/A	N/A	N/A			
Sealing of electrical shafts	N/A	Sealed				
Fire Rating of shaft door	N/A	N/A	N/A			
Water Curtain	N/A	N/A	N/A			
Fire Dampers	N/A	N/A	N/A			
• Fin	AM	re Dampers N/A N/A	re Dampers N/A N/A N/A N/A			

	Basements	30 a/c per hour	provided	MR
-,-	Upper floors	12 a/c per hour	Natural Ventilation	MR
5	Fire Extinguishers			
	Total numbers	10	Provided	MR
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR
	IS marking	ISI marked	Provided	MR
6	First-Aid Hose Reels.			and the second s
	Total numbers on each floor	01	Provided	MR
	Length of hose reel hose	30 m	Provided	MR
*	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarming	g system.		
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
-	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	Required	D.G. set 62 KVA	MR
	Hooters' Location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.			
	Basement	N/A	N/A	N/A
	• Upper Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			516
	Size of riser/down-comer	N/A	N/A	N/A
2	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.		4	
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A

Auto Starting/ Wanuar Stop	ping N/A	N/A	N/A
Pump House Access	N/A	N/A	N/A
Terrace level			
Discharge of pump	450 LPM	450 LPM	MR
Head of the pump	30 mts	30 mts each	MR
Power Supply	Required	Provided	MR
Auto Starting of pump	Required	Provided	MR
Captive Water Storage for fire fighti	ng.		
Underground tank capacity	N/A	N/A	N/A
> Draw-off connection	N/A	N/A	N/A
Fire service inlet	N/A	N/A	N/A
Access to tank	N/A	N/A	N/A
Overhead Tank capacity	Old Case	5000 lts	MR being old case
Exit Signage.	Required	Provided	MR
Provision of Lifts.			
Pressurization of Lift Shaft	N/A	N/A	N/A
Pressurization of Lift lobby	N/A	N/A	N/A
Communication In lift Car	N/A	N/A	N/A
Fireman's Grounding Switch			Old lift
Lift Signage	Required	Provided	MR
Standby power supply	Required	Provided	MR
Refuge Area.			
> Total Area	N/A	N/A	N/A
> Location	N/A	N/A	N/A
Fire Control Room			
Detector System Panel	N/A	N/A	N/A
Flow Switch Panel	N/A	N/A	N/A
PA System Panel	N/A	N/A	N/A
Battery backup	Required	Provided	MR
Building Floor Plans	N/A	N/A	N/A
Special Fire Protection Systems for	N/A	N/A	
	 Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting of pump Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans 	Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Overhead Tank capacity Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Required Standby power supply Refuge Area. Total Area Location PA System Panel PA System Panel Building Floor Plans N/A Head of the pump A 450 LPM A50 LPM A50 LPM A50 LPM A50 LPM A60 LPM A6	Pump House Access

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2015/SZ/195 dated 10.02.2015, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DEA:

1.0

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West) Cho 1/2 m-s/cell FTD.

Webs

F. T. letter is put up for Sign.