## 1

# GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/Hospital/NDZ/2018/ 466

Dated: 21/3/18

### FIRE SAFETY CERTIFICATE

Certified that the M.R.D. Block Lok Nayak Hospital at New Delhi comprised of Basement + Ground + 06 Upper floor have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 30/11/2017 in the presence of Sh. Subhash Chand AE (E) & Sh. Kiran Kumar JE (E), PWD that the premises is fit for occupancy class Business Building with effect from -2+1-3-13---------------------------for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010 printed below.

Issued -2-1-13-148----at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Medical Superintendent, Lok Nayak Hospital, New Delhi.

2. The Assistant Engineer (E),
Health Maint. Elect. Division (C),
PWD, Lok Nayak Hospital, New Delhi.

#### Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

#### INSPECTION REPORT

1. Name & address of the building : M.R.D. Block at L.N. Hospital, New Delhi.

2. Type of occupancy

: Business Building

Basement + Ground + 06 Upper floors

3. Type of case:-

: New case

4. Details of previous FSC

: N/A: N/A

5. Fire safety directives No.

6. Date of inspection:-

30/11/17

7. Name of the inspecting officer

: Sh. Gurmukh Singh DO/CD, Sh. M.K. Sharma ADO/CC

8. Name & designation of officer from the building side

: Sh. Subhash Chand AE (E) &

Sh. Kiran Kumar JE (E), PWD

9. Year of construction

: 1960

	Year of construction Applicant's letter No	: 1960 : AE(E)-II/PV	VD/W.F./2017-18/451	dated 16/11/17	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	13 mtr.	15 mtr.	MR	
	2) Gate width	05 mtr.	05 mtr.	MR	
	3)Width of internal road	6 mtr.	6 mtr. Two side on road	MR	
2.	Number, Width Type & Arran	gement of Exits			
	A. Number of staircases				
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	01 No.	01 No. & ramp	MR	
	B. Width of staircase		4		
	1. Upper floors	1.25 mtr.	1.25 mtr.	MR	
	2. Basements	1.25 mtr.	1.25 mtr. & Ramp 2 mtr.	MR	
	C. Protection of exits		1	× ×	
	1. Fire check door	Required	Provided	MR	
	2. Pressurization	Required	Provided	MR	
	D. No. of continuous	01	01	MR	
	staircase to terrace	*	1 x		
	E. Width of corridor	2.3 mtr.	2.3 mtr.	MR	
	F. Door size	2.10 x 2.10 mtr.	2.10 x 2.10 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	Required	Provided	MR	
	2) Sealing of electrical shafts	Required	Provided	MR	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	Exhaust fan	MR	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	45 Nos.	50 Nos.	MR	
	2) Types	ABC & CO2	ABC, CO2 &	MR	
	3) ISI marking	Required	Provided	MR	

6.	First-Aid Hose Reel						
	1)Total number of each	01					
	floor		0·1	MR			
	2) Length of hose reel hose	36 m					
	3) Nozzle diameter	5	36 m	MR			
7.	Automatic Fire Detection &	3 mm	5 mm	MR			
	1) Type of detectors						
	2) Location of main panel	Smoke/ heat	Smoke/ heat	MR			
	3) Location of repeater pane	C. Room	Provided	MR			
	4) Alternate source of power		floor wise	MR			
	5) Hooter's Location		Provided	MR			
8.	MOEFA	Every floor	Provided	MR			
9.		Required	Provided	MR			
10.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System		- I Taba	IVIK			
	1) Basement	Required	Provided	MD			
	2) Upper floors	N/A	N/A	MR			
	3) Sprinkler above false	NIA		N/A			
11.	ceiling	NA	NA	NA			
11.	Internal Hydrants						
	1) Size of riser/down-comer	150 MM	150 MM	1.00			
	2) Number of hydrants per	01	01	MR			
	floor		01	MR			
	3) Hose box each floor	01	01				
12.	Yard Hydrants		01	MR			
	1) Total number of hydrants	05	05				
	2) Hose box	05	05	MR			
3.	Pumping Arrangement	Common pump	05	MR			
		with MAIDS					
	1) Ground level						
	a) Discharge of main	2850 LPM	2850 LPM	100			
	pump		2030 LF [V]	MR			
	b) Head of main pump	70 mtr.	70 mtr.	3.00			
	c) Number of main pump	02	02	MR			
	d) Jockey pump out put	180 LPM	180 LPM	MR			
	(2 Nos.)	21111	100 LPIVI	MR			
	e) Jockey pump head	70 mtr.	70 mt=	7			
	f) Stand by pump output	2850 LPM	70 mtr.	MR			
	g) Stand by pump head	70 mtr.	2850 LPM	MR			
	h) Auto starting/Manual	Required	70 mtr.	MR			
	stopping	required	Provided	MR			
	2) Terrace level						
	a) Discharge of pump	N/A	27/4				
Γ	b) Head of pump		N/A	N/A			
	c) Power supply	N/A	N/A	N/A			
	d) Auto starting of pump	N/A	N/A	N/A			
	Captive Water Storage for Fire F	N/A	N/A	N/A			
	1) Under growth	ighting					
	1) Under ground tank 2	2,00,000 ltr.	2,00,000 ltr.	MR			
	capacity			1411/			

	a) Draw-off connection b) Fire service in let	n Required	Provided	
	Set vice intel	Required		MR
-	c) Access to tank	Required	Provided	MR
	d) Over head tank	20,000 Ltrs.	Provided	MR
15.	capacity	J, CO Etis.	20,000 Ltrs.	MR
16.	Exit Signage.	Required	D	
10.	Provision of Lifts.	- toquired	Provided	MR
	a) Pressurization of lift	DT/A		
	shaft	N/A	N/A	N/A
	b) Pressurization of lift	27/4		IVA
	lobby	N/A	N/A	N/A
	c) Communication in	-		IVA
	lift car	Required	Provided	MR
	d) Fireman's switch		1000	MR
1	e) Lift signage	Required	Provided	MD
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	Required	Provided	MR
		N/A	N/A	MR
	Total area location	N/A		N/A
10		IVA	N/A	N/A
19.	Fire Control Room			
	a) Detector system	_		
	panel	Required	Provided	MR
	b) Flow switch panel		14.04	MR
	c) PA system panel	Required	Provided	MD
	d) Pottor 1	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Duilli a		TOVIDED	MR
).	and floor plan	Required	Provided	
<i>)</i> .	Special Fire Protection System for Protection		Tovided	MR
	Special Fire Protection System for Protection of special Risk, if			MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/2016/2836 dated 07/12/2016 have been rectified.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, grant of fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / is recommended please.

Name: - G.S Chauhan

Designation :- DO (CD)

Signature of the Inspecting Officer

Mens Name:- M.K. Sharma

Designation: - ADO (CC)

Dycho (xbz) dy.

CF. P. P. speak 12/14/7.

Difoloz + M.

Doco.