## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2018/513

Dated: 27 03 2018

## **FIRE SAFETY CERTIFICATE**

Certified that the M/s Snow White Inn located at 2530/7-8, Chuna Mandi, Pahar Ganj, New Delhi-110055 comprised of Ground + 4 upper floors – ground floor – reception, 1<sup>st</sup> floor to 4<sup>th</sup> floor 04 guest rooms at each floor total 16 guest rooms owned/occupied by M/s Snow White Inn Guest House have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 15/11/17 in the presence of Mr. Sidheswar Mandal (Manager) that the premises is fit for occupancy of class Residential Group –A-1` for total 16 guest rooms only as above with effect from – 21/23/2017 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, mentioned below.

Issued on 27.03.2018 at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi
- 2. The Licensee, M/s Snow White Inn,2530/7-8,Chuna Mandi, Pahar Ganj,New Delhi-110055.
- 3. The Commissioner, NDMC, Civic Centre, New Delhi. with the request to get the height measured & apprise this department.

## Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

## INSPECTION REPORT

1. Name & address of the building:-

M/s Snow White Inn,2530/7-8,Chuna Mandi,

Pahar Ganj, New Delhi-110055.

2. Type of occupancy:-

Residential Group A-1Ground + 4 upper floor (16 guest rooms) ground floor – reception ,1<sup>st</sup> floor to 4<sup>th</sup> floor 04 guest rooms at each floor.

New.

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10 Applicant's letter No:-

No N/A

15/11/17

D.O. Gurmukh Singh

Mr. Sidheswar Mandal (Manager),

2003 (revised) h

2875-79/Addl/C.P./Lic. dated 30/10/17.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety measures	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	12 mtr. (Approx.)	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases		19:			
	1. Upper floors	01 No.	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase	\ <u></u>	26.			
	1. Upper floors	125 cms.	125 cms to 150 cms.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	N/A	N/A	N/A		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation		-			
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System		-			
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR .		

	Fire Extinguishers	10 NT		10 No:	c c	MR	
8	1) Total numbers	10 No		ABC		MR	-
2	2) Types	Requi	& CO2			MR	
	J) IDI marking		rea	Provided		1411	
•		irst-Aid Hose Reel		01 no.		MF	?
	1)Total number at each 01		•	01 110.	•	1411	
	floor	20	mtr Provided		ded	MR	
	2) Length of hose reel hose	30 mt		Provided		MR	
8			111111.		ucu	1411	
7.	Automatic Fire Detection & A	Jarmin	g System	N/A		N/	A
	1) Type of detectors N/A			N/A		N/A	
	2) Location of main panel N/A			N/A N/A		N/A	
	3) Location of repeater panel N/A			The same of the sa		N/A	
	4) Alternate source of power	wer N/A		N/A		N/A N/A	
	5) Hooter's Location	N/A		N/A		N/A N/A	
8.	MOEFA	N/A		N/A		N/A	
9.	Public Address System	n N/A		N/A		N/A	
10.	Automatic Sprinkler System					N.T	/A
	1) Basement	N/A	T	N/A			
	2) Upper floors	N/A		N/A		N/A N/A	
	3) Sprinkler above false	N/A		N/A		IN IN	/A
	ceiling					tt a	- I
11.	Internal Hydrants					-	
11.	1) Size of riser/down-comer N			N/A		1	[/A
	2) Number of hydrants per	N/A		N/A			I/A
	floor						T / A
	3) Hose box	N/A		N/A	0	N	I/A
12.	Yard Hydrants	0.5					
12.	1) Total number of hydrants		N/A N/A			1	I/A
	2) Hose box	N/A		N/A		1	V/A
12	Pumping Arrangement						
13.	1) Ground level	N	/A	N/A	A		N/A
	a) Discharge of main		/A	N/A	4		N/A
	pump						
		N	/A	N/A	A		N/A
			/A	N/	A		N/A
			/A	N/.	A		N/A
	1 1	-	//A	N/.	A		N/A
			//A	N/	A		N/A
	1) Starta of post-p		I/A	N/	A		N/A
	. 73 5 1		I/A	N/	Ά		N/A
		1					
	stopping 2) Terrace level						
			50 LPM	45	0 LPM	1	MR
	a) Discharge of pump		0 mtr.		) mtr.		MR
	b) Head of pump		Required		ovided		MR
	c) Power supply			The second secon	rovided		MR
	d) Auto starting of pump Required Provided  Captive Water Storage for Fire Fighting						
14.						III	

		1 ' 4	
 /	1		

	Under ground tank     capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
1.5	d) Over head tank capacity	5,000 ltrs.	5,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MD
16.	Provision of Lifts.		Tiovided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
17.	e) Lift signage	N/A	N/A	N/A N/A
	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	NI/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A N/A
		N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, grant of fire Safety Certificate, under rule 35 of the Delhi Fire Service Rules 2010, is recommended please.

> Gurmukh Singh Divisional Officer

Stuits are newled 1.50 med lock to MCD Shuld be